

## Chapter 26

# Use of GIS and Remote Sensing for Landslide Susceptibility Mapping

**Arzu Erener**

*Kocaeli University, Turkey*

**Gulcan Sarp**

*Suleyman Demirel University, Turkey*

**Sebnem Duzgun**

*Middle East Technical University, Turkey*

### ABSTRACT

*In recent years, geographical information systems (GISs) and remote sensing (RS) have proven to be common tools adopted for different studies in different scientific disciplines. GIS is defined as a set of tools for the input, storage, retrieval, manipulation, management, modeling, analysis, and output of spatial data. RS, on the other hand, can play a role in the production of a data and in the generation of thematic maps related to spatial studies. This study focuses on use of GIS and RS data for landslide susceptibility mapping. Five factors including normalized difference vegetation index (NDVI) and topographic wetness index (TWI), slope, lineament density, and distance to roads were used for the grid-based approach for landslide susceptibility mappings. Results of this study suggest that geographic information systems can effectively be used to obtain susceptibility maps by compiling and overlaying several data layers relevant to landslide hazards.*

### INTRODUCTION

In recent years, geographical information systems (GISs) and Remote Sensing (RS) have proven to be common tools adopted for various studies in different scientific disciplines. GIS provides as a set of tools for the input, storage, retrieval, manipulation, management, modeling, analysis and output of spatial data. RS, on the other hand, offers earth observation data for thematic maps related to spatial studies. The use

DOI: 10.4018/978-1-5225-7359-3.ch026

of GIS and RS data for landslide susceptibility mapping are demonstrated by three different landslide susceptibility maps with five different variables (Normalized Difference Vegetation Index (NDVI), Topographic Wetness Index (TWI), slope; lineament density and distance to roads). The comparison of the generated final susceptibility maps with historical landslide locations is given with important factors affecting the accuracy of susceptibility map. The accuracy analysis of the final susceptibility maps for various weighting strategies is performed. The results indicate that assignment of weights to the slope parameter impacts the accuracy in the high susceptible zones.

## **BACKGROUND**

Landslides are among the most common natural hazards and are the most damaging, leading to substantial economic, human, and environmental losses throughout the world. The quantitative assessment of landslide hazards for a large area is critical for mitigation of the associated risks. They are often triggered by natural phenomena and/or human activity, such as earthquakes, precipitation, erosion, deforestation etc. and are difficult to predict. One of the greatest limiting factors in predicting and mapping landslide activity is the lack of understanding of scale-dependent processes, such as erosion, weathering, and fracturing (Glenn et al., 2006). Such maps normally aim at providing a document that depicts the likelihood or possibility of new movements occurring in an area, and therefore helping to reduce future damages. To express the potential for occurrence of landslides in a quantitative manner, maps must incorporate the concept of probability, which is an assessment of the relative frequency of occurrence (Ohlmacher & Davis, 2003). Susceptibility expresses the likelihood that a landslide will occur in an area on the basis of the local terrain conditions (Soeters & Van Westen, 1996); return period or annual probability of occurrence is not considered. The main difference between susceptibility and hazard is therefore that the latter considers the temporal factor, by estimating the probability of occurrence of the phenomenon within a specified period of time (Varnes, 1984) whereas the former considers the likelihood of landslide occurrence. There are many studies in the literature about use of GIS to evaluate landslide susceptibility (e.g. Gokceoglu et al. 2005; Akgun et al. 2011; Akgun 2012; Pradhan et al. 2013; Kavzoglu et al. 2013)

## **MAIN FOCUS**

The purpose of this study is to apply the grid based GIS techniques for landslide susceptibility mapping using five different factors including Normalized Difference Vegetation Index (NDVI), Topographic Wetness Index (TWI), slope, lineament density, and distance to roads. The scope includes the preparation of landslide susceptibility map to identify highly susceptible areas and, the accuracy assessment related to the obtained maps.

The susceptibility assessment methodology is demonstrated for More and Romsdal region in Norway (Erener & Duzgun, 2010). The study area occupies approximately 606.755 km<sup>2</sup> in the west part of Norway. The upper left coordinates on 112707,770408 m - 6952112,603469 m and lower right coordinates 6929466,479194 m -144909,272731 m respectively (Figure 1).

13 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

[www.igi-global.com/chapter/use-of-gis-and-remote-sensing-for-landslide-susceptibility-mapping/211885](http://www.igi-global.com/chapter/use-of-gis-and-remote-sensing-for-landslide-susceptibility-mapping/211885)

## Related Content

---

### Polycyclic Aromatic Hydrocarbon Compounds as Emerging Water Pollutants: Toxicological Aspects of Phenanthrene on Aquatic Animals

Krishna Bhuyanand Anirudha Giri (2020). *Effects of Emerging Chemical Contaminants on Water Resources and Environmental Health* (pp. 45-67).

[www.irma-international.org/chapter/polycyclic-aromatic-hydrocarbon-compounds-as-emerging-water-pollutants/248375](http://www.irma-international.org/chapter/polycyclic-aromatic-hydrocarbon-compounds-as-emerging-water-pollutants/248375)

### Methodology of Climate Change Impact Assessment on Forests

Mostafa Jafari (2019). *Advanced Methodologies and Technologies in Engineering and Environmental Science* (pp. 200-219).

[www.irma-international.org/chapter/methodology-of-climate-change-impact-assessment-on-forests/211873](http://www.irma-international.org/chapter/methodology-of-climate-change-impact-assessment-on-forests/211873)

### Quantum Dots Searching for Bondots: Towards Sustainable Sensitized Solar Cells

Mihai V. Putz, Marina A. Tudoranand Marius C. Mirica (2017). *Renewable and Alternative Energy: Concepts, Methodologies, Tools, and Applications* (pp. 1805-1874).

[www.irma-international.org/chapter/quantum-dots-searching-for-bondots/169659](http://www.irma-international.org/chapter/quantum-dots-searching-for-bondots/169659)

### Remanufacturing, an Added Value Product Recovery Strategy

Adnan Corum (2016). *Handbook of Research on Waste Management Techniques for Sustainability* (pp. 347-367).

[www.irma-international.org/chapter/remanufacturing-an-added-value-product-recovery-strategy/141904](http://www.irma-international.org/chapter/remanufacturing-an-added-value-product-recovery-strategy/141904)

### Remote Sensing-Based Evapotranspiration Modelling for Agricultural Water Management in the Limpopo Basin

Berhanu F. Alemaw, Thebeyame Ronald Chaokaand Brighton Munyai (2019). *Environmental Information Systems: Concepts, Methodologies, Tools, and Applications* (pp. 249-286).

[www.irma-international.org/chapter/remote-sensing-based-evapotranspiration-modelling-for-agricultural-water-management-in-the-limpopo-basin/212947](http://www.irma-international.org/chapter/remote-sensing-based-evapotranspiration-modelling-for-agricultural-water-management-in-the-limpopo-basin/212947)