Chapter 10 Incremental Approach to Classification Learning

Xenia Alexandre Naidenova

Research Centre of Military Medical Academy – Saint Petersburg, Russia

ABSTRACT

An approach to incremental classification learning is proposed. Classification learning is based on approximation of a given partitioning of objects into disjointed blocks in multivalued space of attributes. Good approximation is defined in the form of good maximally redundant classification test or good formal concept. A concept of classification context is introduced. Four situations of incremental modification of classification context are considered: adding and deleting objects and adding and deleting values of attributes. Algorithms of changing good concepts in these incremental situations are given and proven.

INTRODUCTION

By classification we mean partition of a given object's set into disjoint blocks or classes. We assume that objects are described by a set U of symbolic or numeric attributes and each object can have one and only one value of each attribute. Then each attribute generates, by its values, partition of a given set of objects into mutually disjoint classes the number of which is equal to the number of values of this attribute. To give a target classification of objects, we use an additional attribute KL not belonging to U. In Table 1, we have two classes: KL+ (positive objects) and KL– (negative objects).

By classification learning we mean approximation of given object classification in terms of attributes names or values of attributes (Naidenova, 2012). This approximation is reduced to extracting logical rules in the form of functional or implicative dependencies from observable datasets. These dependencies allow to distinguish between classes of given classification. For our example in Table 1, we have some rules based on implicative (ID) and functional dependencies (FD): Color_of_Hairs, Color_of_Eyes \rightarrow KL (FD); if Blond, Blue, then KL = "+"; if Hazel, then KL = "-"; if Brown, Blue, then KL = "-" (IDs).

The task of classification learning based on inferring implicative rules is equivalent to the task of concept formation (Banerji, 1969, Ganter & Wille, 1999). The goal of this task is to describe/classify new objects according to description/classification of existing objects. Inferring good diagnostic (classification)

DOI: 10.4018/978-1-5225-7368-5.ch010

Index of Example	Height	Color of Hair	Color of Eyes	KL
1	Low	Blond	Blue	+
2	Low	Brown	Blue	_
3	Tall	Brown	Hazel	_
4	Tall	Blond	Hazel	_
5	Tall	Brown	Blue	_
6	Low	Red	Blue	_
7	Tall	Red	Blue	+
8	Tall	Blond	Blue	+

Table 1. Example of classification

sification) tests (GDTs) is the formation of the best descriptions of a given object class KL+ against the objects not belonging to this class (KL-).

Let $M = (\cup \text{dom}(\text{attr}), \text{attr} \in U)$, where dom(attr) is the set of all values of attr. Let $X \subseteq M$ and G be the set of indices of objects considered (objects for short), $G = G + \cup G -$, where G + and G - the sets of positive and negative objects, respectively. Denote by d(g) the description of object $g \in G$. Let $P(X) = \{g | g \in G, X \subseteq d(g)\}$. We call P(X) the interpretation of X in the power set 2^G . If P(X) contains only positive objects and the number of these objects more than 2, then we call X a description of some positive objects and (P(X), X) a test for positive objects. Let us define a good test or good description of objects.

Definition 1: A set $X \subseteq M$ of attribute values is a good description of positive (negative) objects if and only if it is the description of these objects and no such subset $Y \subseteq M$ exists, that $P(X) \subset P(Y) \subseteq G+ (\subseteq G-)$.

It has been shown (Naidenova, 1992) that the problem of good tests inferring is reduced to searching for implicative dependencies in the form $X \rightarrow v$, $X \subseteq M$, $v \in dom(KL)$ for all positive (negative) objects.

The concept of good classification (diagnostic) test has firstly been introduced in (Naidenova & Polegaeva, 1986). In (Naidenova, 2012), it is considered the link between classification learning based on inferring good tests and formal concepts in the FCA.

BACKGROUND DEFINITIONS

Let $G = \{1, 2, ..., N\}$ be the set of objects' indices (objects, for short) and $M = \{m_1, m_2, ..., m_j, ..., m_q\}$ be the set of attributes' values (values, for short). Each object is described by a set of values from M. The object descriptions are represented by rows of a table R the columns of which are associated with the attributes taking their values in M. Let D(+) and G(+) be the sets of positive object descriptions and the set of indices of these objects, respectively. Then D(-) = D/D(+) and G - = G/G + are the sets of negative object descriptions and indices of these objects, respectively.

The definition of good tests as a dual construction or formal concept is based on two mapping $2^G \rightarrow 2^M$, $2^M \rightarrow 2^G$ determined as follows. $A \subseteq G$, $B \subseteq M$. Denote by Bi, $Bi \subseteq M$, i = 1, ..., N the description of object with index *i*. We define the relations $2^G \rightarrow 2^M$, $2^M \rightarrow 2^G$ as follows: $A' = \text{val}(A) = \{\text{intersection} \}$

11 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: <u>www.igi-global.com/chapter/incremental-approach-to-classification-</u> learning/213122

Related Content

Artificial Intelligence in Computer Science: An Overview of Current Trends and Future Directions

Arun Prasad G, A. V. Senthil Kumar, Priyanka Sharma, Indrarini Dyah Irawati, Chandrashekar D. V., Ismail Bin Musirin, Hesham Mohammed Ali Abdullahand Manjunatha Rao L (2023). *Advances in Artificial and Human Intelligence in the Modern Era (pp. 43-60).*

www.irma-international.org/chapter/artificial-intelligence-in-computer-science/330397

Unpacking the Role of Service Quality of AI Tools in Catalyzing Digital Transformation: A Bibliometric Analysis

Namita Sharmaand Urvashi Tandon (2024). *Digital Technologies, Ethics, and Decentralization in the Digital Era (pp. 59-79).*

www.irma-international.org/chapter/unpacking-the-role-of-service-quality-of-ai-tools-in-catalyzing-digitaltransformation/338866

Negative Exponent Fraction: A Strategy for a New Virtual Image into the Financial Sector

Francisco V. Cipolla-Ficarra (2014). Advanced Research and Trends in New Technologies, Software, Human-Computer Interaction, and Communicability (pp. 255-268). www.irma-international.org/chapter/negative-exponent-fraction/94235

Benefits and Challenges of Mobile Learning in Education

Abha Vishwakarma (2016). *Human-Computer Interaction: Concepts, Methodologies, Tools, and Applications (pp. 1919-1931).* www.irma-international.org/chapter/benefits-and-challenges-of-mobile-learning-in-education/139128

Particle Shape Analysis Using Digital Image Processing

Katia Tannousand Fillipe de Souza Silva (2019). Advanced Methodologies and Technologies in Artificial Intelligence, Computer Simulation, and Human-Computer Interaction (pp. 377-391). www.irma-international.org/chapter/particle-shape-analysis-using-digital-image-processing/213143