Chapter 44 N-Tuple Algebra as a Unifying System to Process Data and Knowledge

Boris Alexandrovich Kulik

Institute of Problems in Mechanical Engineering RAS, Russia

Alexander Yakovlevich Fridman

Institute for Informatics and Mathematical Modelling, Kola Science Centre of RAS, Russia

ABSTRACT

Information technologies for analysis and processing heterogeneous data often face the necessity to unify representation of such data. To solve this problem, it seems reasonable to search for a universal structure that would allow for reducing different formats of data and knowledge to a single mathematical model with unitized manipulation methods. The concept of relation looks very prospective in this sense. So, with a view to developing a general theory of relations, the authors propose n-tuple algebra (NTA) developed as a theoretical generalization of structures and methods applicable in intelligence systems. NTA allows for formalizing a wide set of logical problems (deductive, abductive and modified reasoning, modeling uncertainties, and so on).

BACKGROUND

Theory of relations is mostly used in databases modeled by means of relational algebra (Codd, 1971). However, many diverse and (at first sight) different mathematical objects, namely graphs, semantic networks, expert rules, predicates, logical formulas, etc., can be expressed as relations. Relational algebra does not provide sufficient techniques to deal with such models and structures.

Modern intelligence systems comprise two types of dissimilar objects, namely databases (DBs) and knowledge bases (KBs). Their structures are quite distinct since they exploit fundamentally different theoretical approaches. Nowadays, data structures (numbers, vectors, graphs, networks, texts, etc.) correspond to algebraic methods (Wirth, 1976). As for KBs, their basic models (predicates, frames, semantic networks, rules and so on) are designed on the basis of declarative approach (Russel & Norvig, 2003).

DOI: 10.4018/978-1-5225-7598-6.ch044

N-Tuple Algebra as a Unifying System to Process Data and Knowledge

This incompatibility results in significantly different programming systems and structures for DBs and KBs, and consequently, in big difficulties to integrate a DB and a KB within one software system.

Conventional attempts to do so relate to the declarative approach mostly. The model of deductive databases (Ullman, 1989; Ceri, Gotlob, & Tanca, 1990) gives an example of such attempts. It is grounded on a modification of Prolog language designed within the declarative approach.

Conversely, some shortcomings inhere in this approach. One of the major problems is in the necessity to reduce many tasks of logical analysis to satisfiability checks for a certain logical formula, this check being able to return only two possible answers ("yes" or "no"). Such a reduction is not simple. Moreover, it is unrealizable in cases when one needs to not only receive a binary answer but also to estimate the value of some parameters in the formal system or to assess the structure and/or number of objects that satisfy the given conditions.

To model and analyze modified reasoning (that is reasoning with hypotheses and abductive conclusions), many authors propose usage of non-classical logics (Russel & Norvig, 2003). However, such logics often have no interpretation or their interpretations do not correspond to semantics of the objects to be modeled. In the authors' opinion, there are some reasons to suppose that problems in modeling modified reasoning within classical logic result from features of the declarative approach rather than from drawbacks of classical logic.

Algebraic approach to logical modeling can be originated from Aristotle's syllogistics and Boole's logical matrices, in more recent times only Arkady Zakrevskij (for instance, see (Zakrevskij & Gavrilov, 1969)) investigated set-theoretical approach to logic and proposed a programming language LYaPAS (Logical Language for Representation of Synthesis Algorithms) oriented toward programming of synthesis algorithms for finite-state and discrete devices. However, this language does not provide any means for logical inference.

To overcome the mentioned and other problems, the mathematical model of relational algebra was generalized by the authors to a more universal system for processing *n*-ary relations called *n*-tuple algebra (Kulik, 1995, 2007; Kulik, Fridman, & Zuenko, 2013, 2015).

N-TUPLE ALGEBRA: BASICS AND FEATURES

N-tuple algebra is a mathematical system to deal with arbitrary *n*-ary relations. In NTA, such relations can be expressed as four types of structures called *NTA objects*. Every NTA object is immersed into a certain space of *attributes*. Names of NTA objects contain an identifier followed by a sequence of attributes names in square brackets; these attributes determine the *relation diagram* in which the NTA object is defined. For example, *R*[*XYZ*] denotes an NTA object defined within the space of attributes

 $X \times Y \times Z$ that is $R[XYZ] \subseteq X \times Y \times Z$.

From the mathematical point of view, NTA is an *algebraic system* $A = \langle A, O, R \rangle$, where *carrier* A is an arbitrary totality of relations expressed as NTA objects; O is a set of *operations* comprising *algebra of sets' operations* (union, intersection, complement) and *operations on attributes* (see below); R is a set of verified *relations* between NTA objects, namely equality and inclusion. This algebraic system is proved to be complete (i.e. all operations and checks of relations are feasible for any totalities of NTA objects).

12 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/n-tuple-algebra-as-a-unifying-system-to-process-

data-and-knowledge/214646

Related Content

Dynamic Scheduling Model of Rail-Guided Vehicle (RGV) Based on Genetic Algorithms in the Context of Mobile Computing

Chen Xu, Xueyan Xiong, Qianyi Du, Shudong Liu, Yipeng Li, Deliang Zhongand Liu Yaqi (2021). International Journal of Mobile Computing and Multimedia Communications (pp. 43-62). www.irma-international.org/article/dynamic-scheduling-model-of-rail-guided-vehicle-rgv-based-on-genetic-algorithms-inthe-context-of-mobile-computing/271387

A Mobile Computing Framework for Passive RFID Detection System in Health Care

Masoud Mohammadianand Ric Jentzsch (2009). *Mobile Computing: Concepts, Methodologies, Tools, and Applications (pp. 3368-3386).*

www.irma-international.org/chapter/mobile-computing-framework-passive-rfid/26730

Research on Soft Computing Techniques for Cognitive Radio

Subhashree Mishra, Sudhansu Sekhar Singh, Bhabani Shankar Prasad Mishraand Prabin Kumar Panigrahi (2016). *International Journal of Mobile Computing and Multimedia Communications (pp. 53-73).* www.irma-international.org/article/research-on-soft-computing-techniques-for-cognitive-radio/161756

The Impact of Zoning Concept on Data-Flow Management within LBS System Components

Suleiman Almasriand Ziad Hunaiti (2012). *Emergent Trends in Personal, Mobile, and Handheld Computing Technologies (pp. 41-60).*

www.irma-international.org/chapter/impact-zoning-concept-data-flow/65331

Research on Double Energy Fuzzy Controller of Electric Vehicle Based on Particle Swarm Optimization of Multimedia Big Data

Xiaokan Wang (2017). International Journal of Mobile Computing and Multimedia Communications (pp. 32-43).

www.irma-international.org/article/research-on-double-energy-fuzzy-controller-of-electric-vehicle-based-on-particleswarm-optimization-of-multimedia-big-data/188622