

Chapter 68

Agent–Development Framework Based on Modular Structure to Research Disaster–Relief Activities

Shunki Takami

University of Tsukuba, Japan

Kazuo Takayanagi

Aichi Institute of Technology, Japan

Shivashish Jaishy

Aichi Institute of Technology, Japan

Nobuhiro Ito

Aichi Institute of Technology, Japan

Kazunori Iwata

Aichi University, Japan

ABSTRACT

This article describes approaches to the RoboCup Rescue Simulation league which is a part of the response to recent large-scale natural disasters. In particular, the project provides a platform for studying disaster-relief agents and simulations. The aim of the project is to contribute to society by making widely available the findings of our research into disaster relief. Some disaster-relief agents contain excellent algorithm modules, which should ideally be shareable among developers. However, this is hindered when the program structure of the agents are different among different teams. Therefore, this article designs and implements a modular agent-development framework that unifies the structure within RoboCup Rescue Simulation agents to facilitate such technical exchange.

DOI: 10.4018/978-1-7998-1754-3.ch068

SUMMARY OF THE RRS

In this section, we explain the simulation content, agent type and behavior, themes of agent development and development environment issues.

Overview of RRS

The RRS is a research platform that simulates disaster-affected areas and disaster-relief activities on a computer (Takahashi, 2001). It can handle disaster-relief activities over approximately 5 hours from the occurrence of a disaster.

Figure 1 shows the activities of agents in the RRS. In the disaster-relief activities, we control six types of agents, namely AmbulanceTeam, FireBrigade, PoliceForce, and the headquarters of each of these units (AmbulanceCentre, FireStation, and PoliceOffice). In addition, there are Civilian agents to simulate civilians in disaster situations.

- AmbulanceTeam
These agents rescue other agents that cannot move by themselves. They rescue targets from debris and transport them to evacuation centers.
- FireBrigade
These agents extinguish fires in buildings. They extinguish the fire by discharging the water stored in their tank. It is necessary to supply water when the tank becomes empty.
- PoliceForce
These agents clear road blockages. They enable other agents to access certain areas by removing obstacles.
- AmbulanceCentre, FireStation, and PoliceOffice
These agents are headquarters. These agents are only for enabling communication. They cannot move but they are also not injured.
- Civilian
In the competition, these agents move automatically to evacuation centers.

The RRS simulator consists of a kernel that manages the progress of the simulation. In addition, there are sub-simulator components that simulate disaster situations and agent programs. The simulation proceeds at the rate of one step per minute. The time allowed for calculating one step of an agent is limited to 1 s. Before the start of the simulation, as a pre-calculation stage, it is possible to calculate initial data using only topographical information (Faraji, 2016).

The RRS can be used to research applications of artificial intelligence and information science to natural-disaster rescue problems. In the RRS, five research tasks of are advocated in particular, namely Group Formation, Path Planning, Search, Multi-task Allocation, and Communication (Skinner, 2010). Every year, competitions using agent programs are held for the purpose of technical exchange.

Agent Development in the RRS

The disaster-relief problems handled by the RRS are complex compound problems in which damage situations such as fire, building collapse, and the availability or otherwise of wireless communication

13 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/agent-development-framework-based-on-modular-structure-to-research-disaster-relief-activities/244066

Related Content

Near-Optimal Trajectory Generation of a Two-Legged Robot with Soft Sole on Staircase using PSO and ABC

Naga Sudha Rani Band Vundavilli Pandu Ranga (2015). *International Journal of Robotics Applications and Technologies* (pp. 1-19).

www.irma-international.org/article/near-optimal-trajectory-generation-of-a-two-legged-robot-with-soft-sole-on-staircase-using-psy-and-abc/152359

Integrating Linear Physical Programming and Fuzzy Logic for Robot Selection

Mehmet Ali Ilgn (2017). *International Journal of Robotics Applications and Technologies* (pp. 1-17).

www.irma-international.org/article/integrating-linear-physical-programming-and-fuzzy-logic-for-robot-selection/197421

Intention and Body-Mood Engineering via Proactive Robot Moves in HRI

O. Can Görürand Aydan M. Erkmn (2015). *Handbook of Research on Synthesizing Human Emotion in Intelligent Systems and Robotics* (pp. 255-282).

www.irma-international.org/chapter/intention-and-body-mood-engineering-via-proactive-robot-moves-in-hri/127567

Autonomous Intelligent Robotic Navigation System Architecture With Mobility Service for IoT

Subbulakshmi T.and Balaji N. (2017). *International Journal of Robotics Applications and Technologies* (pp. 32-48).

www.irma-international.org/article/autonomous-intelligent-robotic-navigation-system-architecture-with-mobility-service-for-iot/197423

Modeling the Experience of Emotion

Joost Broekens (2010). *International Journal of Synthetic Emotions* (pp. 1-17).

www.irma-international.org/article/modeling-experience-emotion/39001