Chapter 9 Interval Type 2 Fuzzy Fireworks Algorithm for Clustering

Juan Barraza

b https://orcid.org/0000-0002-1647-5102 *Tijuana Institute of Technology, Mexico*

Fevrier Valdez

Tijuana Institute of Technology, Mexico

Patricia Melin

b https://orcid.org/0000-0001-5798-1426 *Tijuana Institute of Technology, Mexico*

Claudia I. Gonzalez https://orcid.org/0000-0003-1631-033X *Tijuana Institute of Technology, Mexico*

ABSTRACT

This chapter presents Interval Type 2 Fuzzy Fireworks Algorithm for clustering (IT2FWAC). It is an optimization method for finding the optimal number of clusters based on the centroid features which uses the Fireworks Algorithm (FWA), but with a dynamic adjustment of parameters using an Interval Type 2 Fuzzy Inference System (IT2FIS). Three variations of the IT2FWAC are proposed to find the optimal number of clusters for different datasets: IT2FWAC -I, IT2FWAC -II, and IT2FWAC –III. They are explained in detail.

INTRODUCTION

To imitate the human functions, methodologies such as fuzzy logic (Simoes, Bose & Spiegel, 1997; Zadeh, 1989), algorithms based on nature (Aladwan, Alshraideh & Rasol, 2015; Barraza, Rodríguez, Castillo, Melin, & Valdez, 2018), swarm intelligence (Melián & Moreno, 2003), physical (Can & Alatas, 2015), and/or neural networks (Soto & Melin, 2015) we are using computational science; with the DOI: 10.4018/978-1-7998-1659-1.ch009

goal of learning or solving problems the methodologies mentioned above are added into the machines or robots (Wolpert & Macready, 1997).

The optimization topic means to maximize or minimize a solution to a problem depending on a corresponding objective function; there are different mathematical problems and optimization types: single objective and multi-objective, and, the problems of clustering validation are considered as multi-objective optimization, therefore, in the proposed method IT2FWAC we apply two different clustering validations: Intra-cluster and Inter-cluster.

Speaking about clustering (Sanchez, Castillo, Castro & Melin, 2014), we know that there are clustering algorithms which, have been applied to solve classification problems such as pattern recognition, image segmentation, among other research areas with good results (Soler, Tenc'e, Gaubert & Buche, 2013).

On the other hand, Type-I Fuzzy Logic Inference Systems are unable to directly handle rule uncertainties, because they use type-1 fuzzy sets that are certain (i.e., fully described by single numeric values); on the other hand in the Interval Type 2 Fuzzy Logic Inference Systems are useful in circumstances where it is difficult to determine an exact numeric membership function, and there are measurement uncertainties.

Fireworks Algorithm (FWA)

The conventional Fireworks Algorithm (FWA) is a swarm intelligence algorithm as mentioned above, and it is composed of 4 general steps: initialization of locations, calculation of the number of sparks, calculation of the explosion amplitude for each firework and selection of the best location (Tan, 2015; Tan & Zhu, 2010).

In this Section, the main equations of the algorithm are presented:

Number of Sparks

The number of sparks is calculated with the Equations 1 and 2.

$$Minimize f(x_i) \in R, x_i _min \le x_i \le x_i _max$$
(1)

where $x_{imin} \le x_i \le x_{imax}$ represents the bounds of the search space.

$$S_{i} = m \cdot \frac{y_{\max} - f(x_{i}) + \epsilon}{\sum_{i=1}^{n} (y_{\max}) - f(x_{i})) + \epsilon}$$

$$\tag{2}$$

In Equation 2, *m* is a constant parameter, y_{max} is the worst value of the objective function and ϵ is a smallest number in the computer.

Explosion Amplitude

The explosion amplitude for each firework is calculated using Equation 2:

15 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/interval-type-2-fuzzy-fireworks-algorithm-forclustering/252909

Related Content

Unified Swarm Intelligence Algorithms

Yuhui Shi (2018). *Critical Developments and Applications of Swarm Intelligence (pp. 1-26).* www.irma-international.org/chapter/unified-swarm-intelligence-algorithms/198919

Comparison of Zipper and Non-Zipper Merging Patterns Near Merging Point of Roads

Y. Wakita, T. Iguchi, H. Shimizu, T. Tamakiand E. Kita (2010). *International Journal of Natural Computing Research (pp. 19-39).*

www.irma-international.org/article/comparison-zipper-non-zipper-merging/49123

Simulating the Spread of an Epidemic in a Small Rural Kansas Town

Todd Easton, Kyle Carlyle, Joseph Andersonand Matthew James (2011). *International Journal of Artificial Life Research (pp. 95-104).*

www.irma-international.org/article/simulating-spread-epidemic-small-rural/54750

Defect Detection of Fabrics by Grey-Level Co-Occurrence Matrix and Artificial Neural Network

Dilip k. Choudhuryand Sujata Dash (2018). Handbook of Research on Modeling, Analysis, and Application of Nature-Inspired Metaheuristic Algorithms (pp. 285-297).

www.irma-international.org/chapter/defect-detection-of-fabrics-by-grey-level-co-occurrence-matrix-and-artificial-neuralnetwork/187691

Automatic Texture Based Classification of the Dynamics of One-Dimensional Binary Cellular Automata

Marcelo Arbori Nogueiraand Pedro Paulo Balbi de Oliveira (2019). *International Journal of Natural Computing Research (pp. 41-61).*

www.irma-international.org/article/automatic-texture-based-classification-of-the-dynamics-of-one-dimensional-binarycellular-automata/237983