Chapter 6

Emerging Trends in 3D Image Reconstruction and Modeling: 3D Construction From Multiple Images

Parimala Boobalan

Vellore Institute of Technology, India

ABSTRACT

In recent years, there is a demand for 3D content for computer graphics, communications, and virtual reality. 3D modelling is an emerging topic that is applied in so many real-world applications. The images are taken through camera at multiple angles and medical imaging techniques like CT scan and MRI are also used. From a set of images, intersection of these projection rays is considered to be the position for 3D point. This chapter discusses the construction of 3D images from multiple objects. Various approaches used for construction, triangulation method, challenges in building this model, and the application of 3D models are explained in this chapter.

INTRODUCTION

There is an essential need for generating 3D models from multiple images in movie industry, gaming and in mapping. Creating a three dimensional model from group of images is called 3D construction from multiple images. When an image is projected from a 3D scene onto a 2D view, the depth of the image is lost. To perform this reverse process of obtaining 2D from 3D images, image point for a specific images ie., line of sight has to be found. But it is impossible to determine which point is the line of sight for a specific image. If two images are present then the intersection of two projections is found to be the position of 3D point. The process used to find this intersection of projection is called as triangulation. The important task for this process is to find the relation between multiple views which delivers the information that corresponds to set of points that contain the structure related to poses and calibration of the camera.

The significance of 3D images is highly visible in computer graphics, virtual reality and communications. The traditional system that is used for constructing 3D images results in high cost and cannot

DOI: 10.4018/978-1-5225-5294-9.ch006

satisfy the need of new application. This gap is filled with the use of digital mapping facilities. Recently, various approaches are developed to extract three dimensional images from sequence of images.

The sequence of processing steps involved in converting multiple 2D images into 3D model is as follows.

- (i) Depth determination: This step involves in finding the missing depth component from any 3D image. The matching position of two images can then be triangulated in 3D space. Finding this matching position is the biggest challenge in depth determination.
- (ii) Registration: Multiple depth maps are combined and final mesh is created by calculating the depth and projection out of camera.
- (iii) Material Application: This step involves in applying the colour from original photographs to the mesh.

In late decades, there is an important urge for 3D content for personal digital assistant graphics, virtual reality and communication, triggering a need in elaboration for the requirements. Many current systems for constructing 3D models are built over specialized hardware (e.g. audio sound system) bring about a steep cost, which cannot answer the specification of new applications. This defoliated area stimulates the act mutually regard to digital imaging facilities (like a camera). Moore's law furthermore tells us that more fields can be done in software. Affine factorization approach is used to recognize 3D from image sequences. However, the chief ingredient of orthographic outlook is an important limitation about system.

The difficulty of converting multiple 2D images into 3D model consists of a chain of processing steps. Autocalibration or self-calibration is an traditional approach, in which camera proposition and parameters are recovered sooner, for rigidity, then structure is well calculated. Two methods implementing this subject are presented as follows, Kruppa equations and Mendonca and cipolla. Another way of doing Startification consists of Projective reconstruction, Afffine reconstruction and Euclidean reconstruction. The concept of 3D models has been a popular research topic earlier for a long time now, and important advance has literally been made as a result of the early days. Nonetheless, the research society is well observant of the specific that still for all practical purposes remains subsequent done.

There is a wide variety of techniques for creating 3D models, but limited to the geometry and material characteristics of the object or scene, a well-known technique may be much better qualified than another. For concrete illustration, untextured objects are illusion for traditional stereo, but too much texture may interfere by the whole patterns of structured-light techniques. Hence, a well-known method can be developed to deal with the variability of objects — e.g., in a museum — to be modeled. As a case of picture, having to model the realized collections of different museums is a useful investigation aspect to visualize about, as it poses large amount of the unanswered challenges, constantly all at once. Another trend is 3D city modeling, which has all of a sudden grown in importance everywhere the last years. It is another extreme in terms of demand under which report have to be captured, in that cities describe an absolutely uncontrolled and considerable environment. Also in that application aspect, multiple problems remain to be resolved.

Given the above considerations, the 3D reconstruction of shapes from infinite, uncalibrated images are one of the practically promising 3D acquisition techniques. In terms of taxonomy of techniques, self-calibrating structure-from-motion is a passive, multi-vantage point strategy. It offers valuable degrees of power in that one can easily move a camera around an object or scene. Most people have a camera and recognize how to handle it. Objects or scenes can be small or large, assuming that the optics and

12 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/emerging-trends-in-3d-image-reconstruction-and-modeling/254589

Related Content

Content-Based Image Retrieval: From the Object Detection/Recognition Point of View

Ming Zhangand Reda Alhajj (2009). Artificial Intelligence for Maximizing Content Based Image Retrieval (pp. 115-144).

www.irma-international.org/chapter/content-based-image-retrieval/4154

Visual Behavior Based Bio-Inspired Polarization Techniques in Computer Vision and Robotics

Abd El Rahman Shabayek, Olivier Moreland David Fofi (2013). Developing and Applying Biologically-Inspired Vision Systems: Interdisciplinary Concepts (pp. 243-272).

www.irma-international.org/chapter/visual-behavior-based-bio-inspired/72032

Intelligent Vision Systems for Landmark-Based Vehicle Navigation

Wen Wu, Jie Yangand Xilin Chen (2011). Computer Vision for Multimedia Applications: Methods and Solutions (pp. 1-19).

www.irma-international.org/chapter/intelligent-vision-systems-landmark-based/48310

Microscopic Biopsy Image Segmentation Using Hybrid Color K-Means Approach

Rajesh Kumar, Rajeev Srivastavaand Subodh Srivastava (2017). *International Journal of Computer Vision and Image Processing (pp. 79-90).*

www.irma-international.org/article/microscopic-biopsy-image-segmentation-using-hybrid-color-k-means-approach/177202

Edge Detection by Maximum Entropy: Application to Omnidirectional and Perspective Images

Ibrahim Guelzim, Ahmed Hammouch, El Mustapha Mouaddiband Driss Aboutajdine (2011). *International Journal of Computer Vision and Image Processing (pp. 1-15).*

www.irma-international.org/article/edge-detection-maximum-entropy/59875