



Chapter 2

Principles and Applications of Thermal Spray Coatings

John Henao

 <https://orcid.org/0000-0002-8954-6039>
CONACYT-CIATEQ A.C., Mexico

Astrid L. Giraldo-Betancur

 <https://orcid.org/0000-0002-5056-7270>
CONACYT-CINVESTAV, Mexico


Carlos A. Poblano-Salas

CIATEQ A.C., Mexico

Jorge Corona-Castuera

CIATEQ A.C., Mexico

Fabio Vargas

 <https://orcid.org/0000-0003-4484-3950>
University of Antioquia, Colombia

Oscar Sotelo-Mazón

Universidad Autónoma del Estado de Morelos
(UAEM), Mexico

ABSTRACT

The goal of the chapter is to address the fundamental theory of thermal spraying and its modern industrial applications, in particular, those involving flame spray, HVOF, plasma spray, and cold spray processes. During the last 30 years, thousands of manuscripts and various book chapters have been published in the field of thermal spray, displaying the evolution of thermally sprayed coatings in many industrial applications. Thermal spray coatings are currently interesting for different modern applications including prosthesis, thermal barriers, electrochemical catalysis, electrochemical energy conversion devices, biofouling, and self-repairing surfaces. The chapter will explain the fundamental principles of the aforementioned thermal spraying processes and discuss the effect of different controlling parameters on the final properties of the produced coatings. This chapter will also explore current and future industrial applications of thermal spray coatings.

LIST OF COMMON ABBREVIATIONS

APS: Atmospheric Plasma Spray

ASI: Adiabatic Shear Instabilities

CAPS: Controlled Atmosphere Plasma Spray

DOI: 10.4018/978-1-7998-4870-7.ch002

CGS: Cold Gas Spray
dB: Decibels (dBA is noise power measured in dB)
DC: Direct Current
D-Gun: Detonation Spray
HPCS: High Pressure Cold Gas Spray
HV: Hardness Vickers
HVOF: High Velocity Air Fuel
HVOLF: High Velocity Oxygen Liquid Fuel
HVOF: High Velocity Oxygen Fuel
HRC: Hardness Rockwell C
HVSFS: High Velocity Suspension Flame Spray
LPCS: Low Pressure Cold Gas Spray
LPPS: Low Pressure Plasma Spray
PS-PVD: Plasma Spray Physical Vapor Deposition
SPS: Shrouded Plasma Spray
TS: Thermal Spray
TWA: Twin Wire Arc
VPS: Vacuum Plasma Spray

INTRODUCTION TO THERMAL SPRAY

General Background

Surface modification of materials is a topic that has been intensively studied for the last hundred years to improve, transform, or provide specific functions to a surface originally designed to perform a definite task. Different methods have been employed to modify the surface of materials; for instance, the deleterious effects of corrosion on steels are controlled by applying a layer of a reactive and low melting point metal such as Zn (Marder et al., 2000). A similar protective effect is produced on the surface of iron-based materials when a polymer is deposited on their surface (Ates et al., 2016); however, the pursued application and the specific surface requirements dictate the procedure and more suitable materials for protecting or modifying the surface. Large numbers of materials and processes have been developed for providing surface modification to different substrate materials, from polymers, metals, and ceramics, to electronics, composites, biomaterials, and a myriad of possible combinations in the middle. Thermal spraying (TS) occupies a very specific niche among the technologies developed for providing specific surface features to metallic, ceramic, and composite materials. TS encompasses a group of coating technologies employed for applying metallic and nonmetallic materials on different types of substrates in order to provide them with specific features such as elevated corrosion resistance, biocompatibility, lubrication, high abrasion resistance, electrical and thermal insulation, etc. (Knight et al., 1998). Raw materials employed in such technologies can be in the form of powders, wire, or rods, depending on the selected TS process. All TS processes encompass thermal and kinetic contributions to the overall energy balance between the energy source and the sprayed material (Pawlowski, 2008). Depending on the TS process configuration, thermal and kinetic contributions to that energy balance can be modified; for instance, in high energy processes such as plasma, raw materials receive a larger amount of thermal

38 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/principles-and-applications-of-thermal-spray-coatings/262345

Related Content

Study of Chip Morphology, Flank Wear on Different Machinability Conditions of Titanium Alloy (Ti-6Al-4V) Using Response Surface Methodology Approach

Kalipada Maity and Swastik Pradhan (2017). *International Journal of Materials Forming and Machining Processes* (pp. 19-37).

www.irma-international.org/article/study-of-chip-morphology-flank-wear-on-different-machinability-conditions-of-titanium-alloy-ti-6al-4v-using-response-surface-methodology-approach/176059

Tool Wear and Surface Integrity Analysis of Machined Heat Treated Selective Laser Melted Ti-6Al-4V

Manikandakumar Shunmugavel, Ashwin Polishetty, Moshe Goldberg, Rajkumar Prasad Singhand Guy Littlefair (2016). *International Journal of Materials Forming and Machining Processes* (pp. 50-63).

www.irma-international.org/article/tool-wear-and-surface-integrity-analysis-of-machined-heat-treated-selective-laser-melted-ti-6al-4v/159821

Impact of Call Drop Ratio Over 5G Network

Jay Kumar Pandey, Shahanawaj Ahamad, Vivek Veeraiah, Nishchal Adil, Dharmesh Dhabliya, Ashok Koujalagi and Ankur Gupta (2023). *Innovative Smart Materials Used in Wireless Communication Technology* (pp. 201-224).

www.irma-international.org/chapter/impact-of-call-drop-ratio-over-5g-network/319927

Optimization of Cutting Parameters for AISI H13 Tool Steel by Taguchi Method and Artificial Neural Network

Hrshikesh Pathak, Sanghamitra Das, Rakesh Doley and Satadru Kashyap (2015). *International Journal of Materials Forming and Machining Processes* (pp. 47-65).

www.irma-international.org/article/optimization-of-cutting-parameters-for-aisi-h13-tool-steel-by-taguchi-method-and-artificial-neural-network/130698

Surface Hardening on Wheel Steel Using Electrolytic Plasma: Formation of Fine Structure and Phase Composition of Wheel Steel Due to Plasma Hardening

Yerkezhan Tabiyeva, Bauyrzhan Rakhadilov, Gulzhaz Uazyrkhanova and Waqar Ahmed (2023). *Innovations in Materials Chemistry, Physics, and Engineering Research* (pp. 197-210).

www.irma-international.org/chapter/surface-hardening-on-wheel-steel-using-electrolytic-plasma/331123