Chapter 7.15 Biomedical Data Mining Using RBF Neural Networks

Feng Chu

Nanyang Technological University, Singapore

Lipo Wang

Nanyang Technological University, Singapore

INTRODUCTION

Accurate diagnosis of cancers is of great importance for doctors to choose a proper treatment. Furthermore, it also plays a key role in the searching for the pathology of cancers and drug discovery. Recently, this problem attracts great attention in the context of microarray technology. Here, we apply radial basis function (RBF) neural networks to this pattern recognition problem. Our experimental results in some well-known microarray data sets indicate that our method can obtain very high accuracy with a small number of genes.

BACKGROUND

Microarray is also called gene chip or DNA chip. It is a newly appeared biotechnology that allows biomedical researchers monitor thousands of genes simultaneously (Schena, Shalon, Davis, & Brown, 1995). Before the appearance of microarrays, a traditional molecular biology experiment usually works on only one gene or several genes, which makes it difficult to have a "whole picture" of an entire genome. With the help of microarrays, researchers are able to monitor, analyze and compare expression profiles of thousands of genes in one experiment.

On account of their features, microarrays have been used in various tasks such as gene discov-

ery, disease diagnosis, and drug discovery. Since the end of the last century, cancer classification based on gene expression profiles has attracted great attention in both the biological and the engineering fields. Compared with traditional cancer diagnostic methods based mainly on the morphological appearances of tumors, the method using gene expression profiles is more objective, accurate, and reliable. More importantly, some types of cancers have subtypes with very similar appearances that are very hard to be classified by traditional methods. It has been proven that gene expression has a good capability to clarify this previously muddy problem.

Thus, to develop accurate and efficient classifiers based on gene expression becomes a problem of both theoretical and practical importance. Recent approaches on this problem include artificial neural networks (Khan *et al.*, 2001), support vector machines (Guyon, Weston, Barnhill, & Vapnik, 2002), k-nearest neighbor (Olshen & Jain, 2002), nearest shrunken centroids (Tibshirani, Hastie, Narashiman, & Chu, 2002), and so on.

A solution to this problem is to find out a group of important genes that contribute most to differentiate cancer subtypes. In the meantime, we should also provide proper algorithms that are able to make correct prediction based on the expression profiles of those genes. Such work will benefit early diagnosis of cancers. In addition, it will help doctors choose proper treatment. Furthermore, it also throws light on the relationship between the cancers and those important genes.

From the point of view of machine learning and statistical learning, cancer classification using gene expression profiles is a challenging problem. The reason lies in the following two points. First, typical gene expression data sets usually contain very few samples (from several to several tens for each type of cancers). In other words, the training data are scarce. Second, such data sets usually contain a large number of genes, for example, several thousands. That is, the data are high dimensional. Therefore, this is a special pattern recognition problem with relatively small number of patterns and very high dimensionality. To provide such a problem with a good solution, appropriate algorithms should be designed.

In fact, a number of different approaches such as k-nearest neighbor (Olshen and Jain, 2002), support vector machines (Guyon *et al.*,2002), artificial neural networks (Khan *et al.*, 2001) and some statistical methods have been applied to this problem since 1995. Among these approaches, some obtained very good results. For example, Khan *et al.* (2001) classified small round blue cell tumors (SRBCTs) with 100% accuracy by using 96 genes. Tibshirani *et al.* (2002) successfully classified SRBCTs with 100% accuracy by using only 43 genes. They also classified three different subtypes of lymphoma with 100% accuracy by using 48 genes. (Tibshirani, Hastie, Narashiman, & Chu, 2003)

However, there are still a lot of things can be done to improve present algorithms. In this work, we use and compare two gene selection schemes, i.e., principal components analysis (PCA) (Simon, 1999) and a t-test-based method (Tusher, Tibshirani, & Chu, 2001). After that, we introduce an RBF neural network (Fu & Wang, 2003) as the classification algorithm.

MAIN THRUST

After a comparative study of gene selection methods, a detailed description of the RBF neural network and some experimental results are presented in this section.

Microarray Data Sets

We analyze three well-known gene expression data sets, i.e., the SRBCT data set (Khan *et al.*, 2001), the lymphoma data set (Alizadeh *et al.*, 2000), and the leukemia data set (Golub *et al.*, 1999).

6 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-

global.com/chapter/biomedical-data-mining-using-rbf/26357

Related Content

A Measure to Study Skin Reflectance using Non-Invasive Photosensor with Economic Design

Prabhu Ravikala Vittal, N. Sriraam, C.K. Malaand J. Saritha (2015). *International Journal of Biomedical and Clinical Engineering (pp. 51-63).*

www.irma-international.org/article/a-measure-to-study-skin-reflectance-using-non-invasive-photosensor-with-economicdesign/136236

Prototype of a Low-Cost Impedance Tomography Based on the Open-Hardware Paradigm

David Edson Ribeiro, Valter Augusto de Freitas Barbosa, Clarisse Lins de Lima, Ricardo Emmanuel de Souzaand Wellington Pinheiro dos Santos (2021). *Biomedical Computing for Breast Cancer Detection and Diagnosis (pp. 1-15).*

www.irma-international.org/chapter/prototype-of-a-low-cost-impedance-tomography-based-on-the-open-hardwareparadigm/259706

Innovative Hospital Management: Tracking of Radiological Protection Equipment

Holger Fritzsche, Elmer Jeto Gomes Ataide, Afshan Bi, Rohit Kalva, Sandeep Tripathi, Axel Boese, Michael Friebeand Tim Gonschorek (2020). *International Journal of Biomedical and Clinical Engineering (pp. 33-47).* www.irma-international.org/article/innovative-hospital-management/240745

A New, Non-Invasive in vivo Optical Blood Glucose Measurement Technique Using Near-Infrared Radiation ("Pulse Glucometry") and a Proposal for "Pulse Hemo-Photometry" Blood Constituent Measurements

Mitsuhiro Ogawa, Takehiro Yamakoshi, Kenta Matsumura, Kosuke Motoiand Ken-Ichi Yamakoshi (2013). *Technological Advancements in Biomedicine for Healthcare Applications (pp. 18-26).* www.irma-international.org/chapter/new-non-invasive-vivo-optical/70844

Elimination of Power Line Interference in ECG Signal Using Adaptive Filter, Notch Filter and Discrete Wavelet Transform Techniques

Srinivasa M.G.and Pandian P.S. (2019). *International Journal of Biomedical and Clinical Engineering (pp. 32-56).*

www.irma-international.org/article/elimination-of-power-line-interference-in-ecg-signal-using-adaptive-filter-notch-filter-anddiscrete-wavelet-transform-techniques/219305