This paper appears in the publication, International Journal of Information Technology and Web Engineering, Volume 3, Issue 1 edited by Ghazi I. Alkhatib © 2008, IGI Global

The Impact of Ontology on the Performance of Information Retrieval: A Case of WordNet

Maria Indrawan, Monash University, Australia Seng Loke, La Trobe University, Australia

ABSTRACT

The debate on the effectiveness of ontology in solving semantic problems has increased recently in many domains of information technology. One side of the debate accepts the inclusion of ontology as a suitable solution. The other side of the debate argues that ontology is far from an ideal solution to the semantic problem. This article explores this debate in the area of information retrieval. Several past approaches were explored and a new approach was investigated to test the effectiveness of a generic ontology such as WordNet in improving the performance of information retrieval systems. The test and the analysis of the experiments suggest that WordNet is far from the ideal solution in solving semantic problems in the information retrieval. However, several observations have been made and reported in this article that allow research in ontology for the information retrieval to move towards the right direction.

Keywords: ontology; semantic information retrieval; WordNet

INTRODUCTION

Semantic understanding is crucial to the success of many information technology applications. Much information technology research is still battling to solve the problem of semantic understanding for their research domain. Ontology adoption is currently the most popular approach taken by many researchers. The proliferation in the use of ontology to support semantic analysis has been found in many domains of information

technology such as context awareness (Rack, Arbanowski, & Steglich, 2000; Yan & Li, 2006), service oriented computing (Bramantoro, Krishnaswamy, & Indrawan, 2005; Jingshan, Hunhns, 2006), and Semantic Web (Caliusco, Galli, & Chiotti, 2005; Dou, LePendu, Kim, & Qi, 2006). Some of the researchers adopt a specific built ontology whereas others investigate the use of a general purpose ontology, such as WordNet.

WordNet is an English lexical referencing system built in the early 1990s at Princeton University. Since its introduction, many researchers have used this lexical system for different purposes, such as multimedia retrieval (Benitez, Chang, & Smith; 2001), text summarization (Hachey & Grover, 2004), and automatic creation of domain-based ontology (Chen, Alahakoon, & Indrawan, 2005; Khan & Luo, 2002). In information retrieval research, the impact of WordNet has been investigated by a number of researchers. WordNet has been used to improve the performance of information retrieval systems by way of query expansion (Voorhees, 1993), semantic distance measure (Richrdson & Smeaton, 1995), and semantic indexing (Wang & Brookes, 2004) to name a few. The results showed by these studied are varied. Voorhees (1993) and Richrardson and Smeaton (1995) report that the recall and precision of the retrieval decreased with the inclusion of WordNet. Wang and Brookes (2004), on the other hand, report the opposite. We were encouraged by Wang and Brookes' report and decided to investigate further since we perceived a further improvement can be applied to their model. In addition, we also would like to explore the debate over the impact of WordNet in information retrieval researches. At the end of the investigation we would like to enrich the debate by reporting our experience and observations during the investigation. In order to achieve this, we organize this article as follows. In the next section, the article presents a short description of WordNet for those readers unfamiliar with this lexical system. In the third section, we lay out the current debate on the impact of WordNet in information retrieval. We introduce our improvement to Wang and

Brookes' model in the forth section. The following section presents the experiment design and results. We conclude our discussion in the last section.

WordNet

The main construct of WordNet as a lexical system is the synonym set or synset. The synsets are divided into four major speech categories of noun, verb, adjective, and adverb. Within each of these categories, several semantic relations between synsets are defined. Included in the noun category are the hypernym, hyponym, meronym, and holonym.

Definition 1: Semantic Relations of Synsets

 $Let assume synsets S = \{s_i s_i, ..., s_n\} \text{ and } L = \{l_i l_j, ..., l_n\}$ exist in the WordNet.

Hypernym: S is considered to be hypernym of L, if every L is a (kind-of) S.

Hyponym: S is considered to be a hyponym of L, if every S is a (kind-of) L.


Meronym: S is considered to be a meronym of L, if every S is a part-of L.

Holonym: S is considered to be a holonym of L, if every L is a part-of S.

In an example of taxonomy of synsets depicted in Figure 1, a canine is considered to be a hyponym of carnivore and a hypernym of dog.

Figure 2 shows that an engine is a meronym of a car and a holonym of a piston. The hypernym/hyponym relations are often referred as hyponomic relations. The meronym/holonym relations are referred as part-whole relations.

Figure 1. A hypernym/hyponym relations



12 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/article/impact-ontology-performance-information-retrieval/2639

Related Content

Text Summarization Based on Conceptual Data Classification

Jihad M. ALJa'am, Ali M. Jaoua, Ahmad M. Hasnah, F. Hassan, H. Mohamed, T. Mosaid, H. Salehand F. Abdullah (2009). *Agent Technologies and Web Engineering: Applications and Systems (pp. 195-209).*

www.irma-international.org/chapter/text-summarization-based-conceptual-data/5034

Efficiency and Risk Management Models for Cloud-Based Solutions in Supply Chain Management

Dothang Truong (2016). Web-Based Services: Concepts, Methodologies, Tools, and Applications (pp. 1694-1711).

www.irma-international.org/chapter/efficiency-and-risk-management-models-for-cloud-based-solutions-in-supply-chain-management/140871

Computing the Spreading Power of a Business Portal to Propagate the Malicious Information in the Network

Hemraj Saini, Bimal Kumar Mishraand T. C. Panda (2013). Web Portal Design, Implementation, Integration, and Optimization (pp. 71-79).

www.irma-international.org/chapter/computing-spreading-power-business-portal/72955

Using Enhanced Lexicon-Based Approaches for the Determination of Aspect Categories and Their Polarities in Arabic Reviews

Mohammad Al Smadi, Islam Obaidat, Mahmoud Al-Ayyoub, Rami Mohaweshand Yaser Jararweh (2016). *International Journal of Information Technology and Web Engineering (pp. 15-31)*.

www.irma-international.org/article/using-enhanced-lexicon-based-approaches-for-the-determination-of-aspect-categories-and-their-polarities-in-arabic-reviews/164469

Tracing the Use of Communication Technologies in Higher Education

Fernando Ramos, Marta Pinto, Dalila Coelho, Rui Raposo, Lúcia Pombo, Luís Pedro, Pedro Almeida, João Batista, Nídia Morais, Francislê Souza, Ana Balula, Margarida Lucasand António Carrizo Moreira (2016). Web Design and Development: Concepts, Methodologies, Tools, and Applications (pp. 1035-1053).

www.irma-international.org/chapter/tracing-use-communication-technologies-higher/137386