



Bringing Semantic Services to Real-World Objects

Massimo Paolucci, DoCoMo Communications Laboratories Europe GmbH, Germany

Gregor Broll, Ludwig-Maximilians-Universität, Germany

John Hamard, DoCoMo Communications Laboratories Europe GmbH, Germany

Enrico Rukzio, Lancaster University, UK

Matthias Wagner, DoCoMo Communications Laboratories Europe GmbH, Germany

Albrecht Schmidt, University Duisburg-Essen, Germany

ABSTRACT

The last few years have seen the emergence of two parallel trends: the first of such trends is set by technologies such as Near Field Communication, 2D Bar codes and RFID that support the association of digital information with virtually every object. By using these technologies, ordinary objects such as coffee mugs or advertisement posters provide digital information that can be easily processed. The second trend is set by (semantic) Web services that provide a way to automatically invoke functionalities across the Internet lowering interoperability barriers. The PERCI system, discussed in the article, provides a bridge between these two technologies allowing the invocation of Web services using the information gathered from the tags to effectively transform every object in a service proxy.

Keywords: *human-machine systems; mobile technologies; semantic data model; Web technologies,*

INTRODUCTION

In recent years, tagging technologies, such as Near Field Communication (hereafter NFC) (ECMA 2006), Radio Frequency Identification (RFID) (EPC Global, 2006) and 2-dimensional bar codes, (Adams, 2007) have received a great deal of attention because of their ability to associate digital information to arbitrary objects. In principle, everything can be cheaply tagged, from coffee mugs to advertisement posters, and

applications can be invoked on the basis of the information that is gathered from the tags on the object.

Japan has seen initial commercial deployments of these technologies. There 2D tagging of advertisements, an example of which is shown by the banner in Figure 1, is quite common. By taking a picture of the banner, a mobile user would immediately gain access to an airline Web page and there buy tickets to fly anywhere in the

world. NFC tagging in combination with mobile phones is also widely used in Japan through iMode-FeliCa (Yoshinaga, 2003). Tagging technologies are also becoming increasingly common in Europe and the US. For example, the UK company Glue4 is delivering platform to associate NFC tags to advertisement posters (UsingRFID.com, 2007), while the German railroad operator uses 2D bar codes to store train tickets directly on the phone (Deutsche Bahn, 2007). Furthermore, tagging is widely used also in B2B solutions to monitor stock inventory, logistics and transport to track moving goods (Meloan, 2003). By tagging containers as well as single products, companies can easily manage their inventory, keep track of the goods that have been received and monitor their position during the delivery process (Tohamy, 2005; IDTechEx, 2007).

Whereas tagging is entering the computer science main stream, it also provides new challenges. The first one is that tags, by and large, do not have any processing abilities, rather they always passively return the same value. Even when active tags exists, as in the case of NFC and RFID, their cost is approximately 100 times higher of the corresponding passive tags making the broad use of active tags very costly. The second challenge is that tags have very limited memory storage, which ranges from a few bytes to a few Kbytes. The third challenge is that the range of the "network" to read a tag is also very limited, spanning from a few centimeters in the case of NFC tags, to a few meters in the case of RFID tags. The fourth challenge, which is important for this article, is that tags break the traditional structure of SOA-based applications which assumes that services are always available and discoverable through a registry.

In this article, we attempt to tackle these challenges by providing a general Web service infrastructure to support the user to interact with advertisement posters. Through the article, we will use the movie poster displayed in Figure 2 as our main example; the goal of the poster is to advertise movies that are playing in town, but the poster achieves more than that; the little

squares on the side of the poster specify additional information such as: the movie theaters where the movies are played (on the upper left side), the show times (on the upper left), and the number of tickets that the user may be able to buy (on the bottom right), public transport tickets to go to the theater (on the bottom left). Crucially, each one of the little boxes is associated with an NFC tag that can be read from any mobile phone with an appropriate reader. A mobile user swiping her phone on the tags should be able to purchase a ticket to a showing of the desired movie, and a public transport ticket to go to the movie. Ultimately, the poster becomes the user interface of the movie theater ticket selling service.

To exploit tagged objects such as the poster displayed in Figure 2, we introduce the

Figure 1. A banner with a 2D bar Code in Tokyo



13 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/article/bringing-semantic-services-real-world/2845

Related Content

CRUZAR: An Application of Semantic Matchmaking to e-Tourism

Iván Mínguez, Diego Berrueta and Luis Polo (2010). *Cases on Semantic Interoperability for Information Systems Integration: Practices and Applications* (pp. 255-271).
www.irma-international.org/chapter/cruzar-application-semantic-matchmaking-tourism/38047

Phishing Website Detection With Semantic Features Based on Machine Learning Classifiers: A Comparative Study

Ammar Almomani, Mohammad Alauthman, Mohd Taib Shatnawi, Mohammed Alweshah, Ayat Alrosan, Waleed Alomoush, Brij B. Gupta, Brij B. Gupta and Brij B. Gupta (2022). *International Journal on Semantic Web and Information Systems* (pp. 1-24).
www.irma-international.org/article/phishing-website-detection-with-semantic-features-based-on-machine-learning-classifiers/297032

A Distributed Patient Identification Protocol Based on Control Numbers with Semantic Annotation

Marco Eichelberg, Thomas Aden and Wilfried Thoben (2007). *Semantic Web-Based Information Systems: State-of-the-Art Applications* (pp. 234-253).
www.irma-international.org/chapter/distributed-patient-identification-protocol-based/28916

Probabilistic Models for the Semantic Web: A Survey

Livia Predoiu (2009). *The Semantic Web for Knowledge and Data Management* (pp. 74-105).
www.irma-international.org/chapter/probabilistic-models-semantic-web/30387

A Systematic Review of Citation Recommendation Over the Past Two Decades

Yicong Liang and Lap-Kei Lee (2023). *International Journal on Semantic Web and Information Systems* (pp. 1-22).
www.irma-international.org/article/a-systematic-review-of-citation-recommendation-over-the-past-two-decades/324071