

Chapter 11

Fabrication of Tailor–Made Metallic Structures for Lightweight Applications and Mechanical Behaviour

R. Ganesh Narayanan

*Department of Mechanical Engineering, Indian
Institute of Technology, Guwahati, India*

Perumalla Janaki Ramulu

*School of Mechanical, Chemical and Materials
Engineering, Adama Science and Technology
University, Adama, Ethiopia*

Satheeshkumar V.

*Department of Production Engineering, National
Institute of Technology Tiruchirappalli, India*

Arvind K. Agrawal

 <https://orcid.org/0000-0003-2151-6404>

*Madanapalle Institute of Technology and
Science, India*

Sumitesh Das

*Research and Development, Tata Steel Limited,
Jamshedpur, India*

Ajay Kumar P.

*Department of Mechanical Engineering, Indian
Institute of Technology Tirupati, India*

V. Vishnu Nambodiri

*National Institute of Construction Management
and Research, Hyderabad, India*

ABSTRACT

Tailor-made metallic structures are fabricated by welding, adhesive bonding, and mechanical joining methods. Here the aim is not only to fabricate lightweight structures, but also to develop novel methods of joining. Lightweight structures are advantageous in several ways including reduction of fuel consumption and vehicle emissions. Developing novel methods of joining is advantageous due to the possibility of joining of dissimilar materials, improved mechanical performance, and microstructures. In the chapter, initially, tailor-welded blanks (TWB) are introduced, and after that, fabrication of TWBs by laser welding, friction stir welding, and friction stir additive manufacturing are elaborately discussed. Some critical issues in modeling the deformation during fabrication of TWBs is also discussed. A brief account of mechanical behavior of adhesive bonded sheets and mechanical joining are presented in the later part.

DOI: 10.4018/978-1-7998-7864-3.ch011

INTRODUCTION TO TWB AND FABRICATION BY LASER WELDING

Introducing TWB

Tailor Welded Blank (TWB) consists of metallic sheets with similar or dissimilar thickness, materials, coatings etc. welded in a single plane before forming. TWBs are formed like un-welded blanks to manufacture automotive components. By using this technology, it is possible to produce parts with varying mechanical properties, leading to component optimization (Pallett & Lark, 2001). Among all the welding methods, laser welding is used predominantly to TWBs as the process is quick and produces smaller welds. The main catalyst behind the sudden growth of TWB is to maintain the market share of steel material in the face of competition generated by aluminium alloys towards weight reduction (Pallett & Lark, 2001).

Some of the advantages of using TWBs in the automotive sector are, (1) scrap materials from stamping industries can be reused to have new stamped products, (2) by distributing material thickness and properties, part consolidation is possible resulting in cost reduction and better quality, stiffness and tolerances, (3) provides greater flexibility for component designers, (4) weight reduction of the product can be achieved and hence fuel consumption is lowered, and (5) improved corrosion resistance and product quality. Research shows that a 1% reduction in vehicle weight can result in a reduction of fuel consumption to 0.6 – 1% (Pallett & Lark, 2001). With these advantages, the potential of TWBs was soon recognized by steel industries and a consortium called Ultra Light Steel Auto Body (ULSAB) concept was then developed (WorldAutoSteel, 2020)

Some of the applications of TWB include center pillar, bumper, front door inner, and rear door inner (Irving, 1995; Prange et al., 1994). Nevertheless, the applications are not restricted to automotive sector, as construction industries also show encouraging pathway in using TWB as part of buildings (Pallett & Lark, 2001). Some applications of laser-welded TWBs are listed in Table 2.1 (WorldAutoSteel, 2020). In the case of aluminium alloys, 5xxx for automotive inner body panels, and 6xxx for outer body panels are mainly used. Specifically, these include 6111-T4, 5754-O, 6061, 5182, 5052 and 5454. Some of the applications of aluminium TWBs made by laser welding, include deck lids, hoods, floor and door inner panels, side frame rails etc. (Das, 2000). Several applications in European and USA market, variety of welded sheets in the form of three piece blanks, non-linear weld lines, details on noise separation, and introduction of multi-piece blank lines can be noted (Rooks, 2001).

In laser welding, CO₂ and ND:YAG (Neodymium: Yttrium-Aluminum-Garnet) laser welding techniques are widely used to produce TWBs. A typical experimental setup is shown in Figure 1 (a) in which two steel sheets are clamped for CO₂ laser welding. Initially, a pointer is displaced at the interface of sheets to check the alignment of sheets with laser source. Figure 1 (b) shows the laser-welded TWB made of steel sheets. Edge quality is crucial and generally, machined edges are preferred for laser based TWB fabrication (Ono et al., 2004). Some of the problems encountered while welding Aluminium sheets are (i) excessive porosity and hot cracking of the fusion zone, (ii) poor coupling during laser welding because of high reflectivity of the metal, (iii) degradation of weld zone properties, and (iv) loss of alloying elements in fusion zone (Das, 2000). Of the two techniques, CO₂ based is accepted widely, safer and less expensive. However, it is subjected to high reflectivity of laser beam on the Al solid surface for a particular wavelength. ND:YAG laser welding has the advantage of uniform energy distribution than CO₂ laser beam over a wide area. It provides the ability to span over large gaps, while maintaining weld speed and quality.

44 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:
www.igi-global.com/chapter/fabrication-of-tailor-made-metallic-structures-for-lightweight-applications-and-mechanical-behaviour/290164

Related Content

Springback Prediction Using Finite Element Simulation Incorporated With Hardening Data Acquired From Cyclic Loading Tool

Jasri Mohamad and Mohd Zaidi Sidek (2019). *International Journal of Materials Forming and Machining Processes* (pp. 19-39).

www.irma-international.org/article/springback-prediction-using-finite-element-simulation-incorporated-with-hardening-data-acquired-from-cyclic-loading-tool/221323

The Evolution of Manufacturing Systems: From Craftsmanship to the Era of Customisation

Dimitris Mourtzis and Michael Doukas (2020). *Additive Manufacturing: Breakthroughs in Research and Practice* (pp. 446-477).

www.irma-international.org/chapter/the-evolution-of-manufacturing-systems/232942

A Study on the Parameters in Hard Turning of High Speed Steel

Krishnaraj Vijayan, N. Gouthaman and Tamilselvan Rathinam (2018). *International Journal of Materials Forming and Machining Processes* (pp. 1-12).

www.irma-international.org/article/a-study-on-the-parameters-in-hard-turning-of-high-speed-steel/209710

Effect of Microstructure on Chip Formation during Machining of Super Austenitic Stainless Steel

Mohanad Alabdullah, Ashwin Polishetty, Junior Noman and Guy Littlefair (2017). *International Journal of Materials Forming and Machining Processes* (pp. 1-18).

www.irma-international.org/article/effect-of-microstructure-on-chip-formation-during-machining-of-super-austenitic-stainless-steel/176058

Circularly Polarized Antennas: An Evident Advancement in Modern Wireless Communications

Utsab Banerjee, Anirban Karmakar and Anuradha Saha (2023). *Innovative Smart Materials Used in Wireless Communication Technology* (pp. 176-200).

www.irma-international.org/chapter/circularly-polarized-antennas/319926