

Chapter 6

Machine Learning Approaches Towards Medical Images

Gayathri S. P.

The Gandhigram Rural Institute (Deemed), India

Siva Shankar Ramasamy

*International College of Digital Innovation (ICDI), Chiang Mai University,
Thailand*

Vijayalakshmi S.

Department of Data Science, Christ University (Deemed), India

ABSTRACT

Clinical imaging relies heavily on the current medical services' framework to perform painless demonstrative therapy. It entails creating usable and instructive models of the human body's internal organs and structural systems for use in clinical evaluation. Its various varieties include signal-based techniques such as conventional X-ray, computed tomography (CT), magnetic resonance imaging (MRI), ultrasound (US) imaging, and mammography. Despite these clinical imaging techniques, clinical images are increasingly employed to identify various problems, particularly those that are upsetting the skin. Imaging and processing are the two distinct patterns of clinical imaging. To diagnose diseases, automatic segmentation using deep learning techniques in the field of clinical imaging is becoming vital for identifying evidence and measuring examples in clinical images. The fundamentals of deep learning techniques are discussed in this chapter along with an overview of successful implementations.

DOI: 10.4018/978-1-6684-6523-3.ch006

INTRODUCTION

The creation of biological image processing algorithms has significantly advanced as a result. This has made it possible to create automated algorithms for information extraction through image analysis or evaluation. Segmentation, which splits the image into visually distinct parts with semantic meaning for the given problem, is the fundamental stage in this automated analysis. Each area often has consistent features regarding its color, texture, or grey level. Precise segmentation and discernible sections are crucial for additional research that may require determining the homogeneity levels of texture or layer thickness. There may occasionally be several items of the same class in the image. Instance segmentation is the separation of regions containing items belonging to the same class while disregarding other courses, as opposed to semantic segmentation, in which objects belonging to the same type are not separated, but various categories are. Three categories can be used to categorize all image segmentation approaches manual segmentation (MS), semi-automatic segmentation, and fully automatic segmentation techniques. For MS methods to properly annotate each picture pixel, subject matter experts must first identify the region of interest (ROI) and then draw exact boundaries around the ROI. MS is essential for the advancement of semi-automatic and utterly automatic segmentation algorithms since it gives the tagged ground truth pictures. MS takes a lot of time and is only practical for tiny image datasets. When it comes to high-quality images, the high resolution could mean that the edges are no longer clearly defined. As a result, even little changes in the ROI boundary's pixel selection can cause significant errors. Another problem with manual segmentation is that it is subjective because it depends on the knowledge and experience of the expert, and as a result, there is frequently a lot of variation among and within experts.

A minimal amount of human intervention with automated algorithms is required for semi-automatic segmentation techniques to deliver appropriate segmentation results. The user's input may include choosing an estimated initial ROI that will be used to segment the entire image later on. To reduce segmentation errors, region borders may need to be manually checked and edited. One illustration of a semi-automatic segmentation procedure is the seeded region growing (SRG) calculation, which iteratively blends close-by pixels of a comparable force given a client giving the beginning seed point. Another model is the level-set-based dynamic form model, which begins with introductory limit shapes addressed by forms and iteratively modifies them through a contracting or development activity given the verifiable level of a capability. This strategy enjoys the benefit that it doesn't and 3) limited region-based dynamic form draws near, which enjoys the benefit of overseeing assorted surfaces and using area boundaries to describe the closer view and foundation of the picture utilizing little neighborhood districts.

20 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/machine-learning-approaches-towards-medical-images/318554

Related Content

Wave Propagation in Filamental Cellular Automata

Alan Gibbons and Martyn Amos (2010). *International Journal of Natural Computing Research* (pp. 56-69).

www.irma-international.org/article/wave-propagation-filamental-cellular-automata/41944

Some Words About Nature-Inspired Computing

Mohamed Arezki Mellal (2022). *Applications of Nature-Inspired Computing in Renewable Energy Systems* (pp. 1-9).

www.irma-international.org/chapter/some-words-about-nature-inspired-computing/294384

A General Rhythmic Pattern Generation Architecture for Legged Locomotion

Zhijun Yang and Felipe M.G. França (2009). *Advancing Artificial Intelligence through Biological Process Applications* (pp. 202-230).

www.irma-international.org/chapter/general-rhythmic-pattern-generation-architecture/4980

The Grid for Nature-Inspired Computing and Complex Simulations

R. Boero (2007). *Handbook of Research on Nature-Inspired Computing for Economics and Management* (pp. 171-182).

www.irma-international.org/chapter/grid-nature-inspired-computing-complex/21128

Local Search with P Systems: A Case Study

Miguel A. Gutiérrez-Naranjo and Mario J. Pérez-Jiménez (2011). *International Journal of Natural Computing Research* (pp. 47-55).

www.irma-international.org/article/local-search-systems/57970