

Chapter 1

Plasma Reactors: A Sustainable Solution for Carbon Dioxide Conversion

Erfan Nouri

 <https://orcid.org/0000-0002-6558-7848>

University of Guilan, Iran

Alireza Kardan

University of Guilan, Iran

Vahid Mottaghtalab

 <https://orcid.org/0000-0001-7211-3141>

University of Guilan, Iran

ABSTRACT

The chapter explores the potential of plasma reactors as a sustainable solution for carbon dioxide (CO₂) conversion. The diverse types of plasmas used in CO₂ conversion are discussed. Mechanisms of plasma-based CO₂ conversion are examined, with a specific focus on direct CO₂ dissociation assisted by plasma, plasma-catalytic processes, and electrochemical CO₂ reduction using plasma. In addition, the chapter delves into the various types of plasma reactors employed for CO₂ conversion and provides a comprehensive comparison of their designs. The analysis of different reactor designs aims to assist in selecting the most suitable plasma reactor for specific CO₂ conversion applications. Furthermore, the chapter delves into the future perspectives of plasma reactors for CO₂ conversion. The chapter concludes by summarizing the essential findings and highlighting the importance of plasma reactors as a sustainable solution for CO₂ conversion, emphasizing their potential impact on mitigating greenhouse gas emissions and contributing to a more environmentally friendly future.

DOI: 10.4018/979-8-3693-0904-9.ch001

1. INTRODUCTION

Global climate change is a pressing issue in our modern world. Human activities, primarily the emission of greenhouse gases, particularly CO₂, are the leading cause of this problem. In order to mitigate the impacts of climate change, it is essential to adopt a comprehensive approach that focuses on reducing carbon emissions and decreasing the existing excessive amount of CO₂ in the atmosphere. Undoubtedly, there is growing interest in exploring the potential of carbon capture and utilization (CCU) as a means of converting CO₂ into valuable fuels and chemicals (Norhasyima & Mahlia, 2018). The cradle-to-cradle principle emphasizes the reduction of reliance on fossil fuels by utilizing waste gas as a renewable feedstock, thereby facilitating technological advancement (Vertongen et al., 2022). Various alternative technologies are under development for industry electrification, such as plasma technology (Snoeckx & Bogaerts, 2017).

The composition of plasma is a collection of differently-formed entities, including but not limited to electrons, ions, excited species, radicals, and molecules. When an electric field is utilized to produce a plasma, such as in the case of gas breakdown, the application of electric power prioritizes the heating of electrons in the plasma over other particles. As a result, the gas molecules are stimulated through electron impact reactions. The division of energy towards favorable chemical processes, such as the splitting of CO₂ (Fridman, 2008), varies according to the discharge condition and parameters involved. Due to its easily adjustable on/off feature, a plasma reactor holds considerable promise in converting intermittent renewable energy into chemical storage. Additionally, it offers significant advantages such as independence from rare resources and the ability to scale up according to the energy market's demands (Fridman, 2008).

Various forms of plasma reactors have been studied in the context of CO₂ conversion (Fridman, 2008). The structure of dielectric barrier discharges (DBDs) is straightforward, allowing them to function effectively in normal atmospheric conditions. These discharges have the potential to achieve significant conversion rates, reaching up to 30%. However, their energy efficiency is relatively restricted, typically between 5% and 10% (Aerts et al., 2015; Uytendhouwen et al., 2018). Microwave (MW) plasmas achieve significantly greater energy efficiencies, primarily around 50%, occasionally reaching as high as 80-90%. However, these efficiencies are generally only observed when operating at lower pressures (Bongers et al., 2017). The drawbacks associated with gliding arc reactors can be effectively addressed. These reactors are capable of operating at atmospheric pressure, resulting in favorable energy efficiencies of approximately 30%. Nonetheless, the conversion rate of these reactors is confined to 8-9% due to the limitation in the fraction of gas that flows through the reactor (Ramakers et al., 2017; Trenchev et al., 2017). The utilization of atmospheric pressure glow discharges (APGD) is becoming increasingly popular for both fundamental research, such as the investigation of the transition from glow to arc (Boyle & Haworth, 1956; Bruggeman & Brandenburg, 2013), and practical applications like gas conversion (Wang et al., 1999; Wanten et al., 2022) and surface modification (Cernak et al., 1995; Shaw et al., 2016).

In summary, the book chapter explores the potential of plasma technology in addressing the challenge of CO₂ conversion. The chapter begins by discussing the types of plasmas used in CO₂ conversion, highlighting their properties and methods of generation. The mechanisms of plasma-based CO₂ conversion are then examined, with a focus on understanding the chemical reactions and physical processes involved. Subsequently, attention turns to plasma reactors for CO₂ conversion, where different reactor types and their operational parameters are explored. Furthermore, a comparison and analysis of these reactor designs is conducted, considering their respective advantages and disadvantages. Lastly, future

31 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/plasma-reactors/338039

Related Content

Investigation on Electrochemical Discharge Micro-Machining of Silicon Carbide

B.R. Sarkar, B. Doloian and B. Bhattacharyya (2017). *International Journal of Materials Forming and Machining Processes* (pp. 29-44).

www.irma-international.org/article/investigation-on-electrochemical-discharge-micro-machining-of-silicon-carbide/189061

Introduction to Bio-Inspired Hydrogel and Their Application: Hydrogels

John M. Melnychuk and Soubantika Palchoudhury (2016). *Emerging Research on Bioinspired Materials Engineering* (pp. 133-159).

www.irma-international.org/chapter/introduction-to-bio-inspired-hydrogel-and-their-application/146504

EDM Process Parameters Optimization for Al-TiO₂ Nano Composite

Arvind Kumar Dixit and Richa Awasthi (2015). *International Journal of Materials Forming and Machining Processes* (pp. 17-30).

www.irma-international.org/article/edm-process-parameters-optimization-for-al-tio2-nano-composite/130696

User Acceptance of Technologies in Their Infancy: The Case of 3D Printing Business Models

Timo Hartmann and Evelyne Vanpoucke (2020). *Additive Manufacturing: Breakthroughs in Research and Practice* (pp. 136-162).

www.irma-international.org/chapter/user-acceptance-of-technologies-in-their-infancy/232926

Directionally Solidified Ceramic Eutectics for High-Temperature Applications

Iurii Bogomol and Petro Loboda (2013). *MAX Phases and Ultra-High Temperature Ceramics for Extreme Environments* (pp. 303-322).

www.irma-international.org/chapter/directionally-solidified-ceramic-eutectics-for-high-temperature-applications/80036