## Chapter 7

# Design and Investigation of Line-Defected Photonic Crystal Antenna for Outstanding Data Transmission

#### Sathish Kumar Danasegaran

Sri Eshwar College of Engineering, India

Elizabeth Caroline Britto IFET College of Engineering, India

**S. Dhanasekaran** Sri Eshwar College of Engineering, India

**G. Rajalakshmi** Sathyabama Institute of Science and Technology, India S. Lalithakumari

Sathyabama Institute of Science and Technology, India

**A. Sivasangari** Sathyabama Institute of Science and Technology, India

**G. Sathish Kumar** Sri Eshwar College of Engineering, India

## ABSTRACT

Wireless technology now employs 5G (generation) communication, while 6G is the subject of increased research. Various G's have evolved due to the need to achieve high data transfer for reliable communication. A tremendous data transfer rate expressed in terabits per second (Tbps) is facilitated by the terahertz (THz) spectrum. The photonic crystal (PhC) patch antenna has been proposed in this chapter, and the consequences of a line defect were examined. The defect has been embedded in the perpendicular and parallel directions of the antenna substrates. The antenna's

DOI: 10.4018/979-8-3693-0916-2.ch007

#### Design and Investigation of Line-Defected Photonic Crystal Antenna

performance regarding return loss (RL), directivity, and voltage standing wave ratio (VSWR) is evaluated. The structure is simulated using CST, and the PhC structure results show excellent characteristics such as -48.02 dB RL, 1.007 VSWR, and 5.23 dB directivity at THz frequency.

### I. INTRODUCTION

A PhC's (Danasegaran et al., 2024; Povinelli et al., 2021) dielectric constant varies periodically in any direction. When the PhCs dielectric constant varies in just a single direction, it is referred to as one-dimensional (1D) PhC. Two-dimensional (2D) PhC structures are those in which the material arrangement is periodic in two directions. The identical is exact for (3D) PhC, whose dielectric constant values contrast in 3D and the categorization of various PhC is shown in figure 1.





2D PhC is the most commonly used in antenna design. The 2D PhC is available in two topologies: hole form and rod form. The hole form PhC is composed primarily of semiconductor material by a filling aspect greater than 50%. It has a structure of less indexed air-filled holes set on a back of highly indexed material. The highly indexed rods in rod type PhC are enclosed by less index surface material, and the filling factor is < 50%. Figures 2 (a) and (b) show the rod and hole category PhC structures.

16 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: <u>www.igi-</u> <u>global.com/chapter/design-and-investigation-of-line-defected-</u> <u>photonic-crystal-antenna-for-outstanding-data-</u> transmission/344442

**Related Content** 

#### Security Management in Mobile Ad Hoc Networks

Jhum Swain (2021). *Managing Resources for Futuristic Wireless Networks (pp. 251-265).* 

www.irma-international.org/chapter/security-management-in-mobile-ad-hoc-networks/262555

#### Trends in Managing Multimedia Semantics

Roberto Poli, Achilles Kameasand Lambrini Seremeti (2014). International Journal of Wireless Networks and Broadband Technologies (pp. 40-55).

www.irma-international.org/article/trends-in-managing-multimedia-semantics/115589

### Load-Balance Energy Aware Ad-Hoc On Demand Multipath Distance Vector Routing Protocol (LBEA-AOMDV) for WSN

Amany Sarhan, Nawal A. El-Fishawyand Mahmoud M. Shawara (2018). *International Journal of Wireless Networks and Broadband Technologies (pp. 38-58).* www.irma-international.org/article/load-balance-energy-aware-ad-hoc-on-demand-multipathdistance-vector-routing-protocol-lbea-aomdv-for-wsn/236065

## Enhanced PMF Model to Predict User Interest for Web API Recommendation

T. Ramathulasiand M. Rajasekhar Babu (2022). *Handbook of Research on Advances in Data Analytics and Complex Communication Networks (pp. 131-139).* www.irma-international.org/chapter/enhanced-pmf-model-to-predict-user-interest-for-web-api-recommendation/287233

#### Security Issues on IoT Environment In Wireless Network Communications

Gowthami K. (2019). International Journal of Wireless Networks and Broadband Technologies (pp. 31-46).

www.irma-international.org/article/security-issues-on-iot-environment-in-wireless-networkcommunications/243660