



701 E. Chocolate Avenue, Suite 200, Hershey PA 17033-1240, USA Tel: 717/533-8845; Fax 717/533-8661; URL-http://www.irm-press.com **ITB10092**

Chapter IX

Automatic 3D Face Model Adaptation with Two Complexity Modes for Visual Communication*

Markus Kampmann Ericsson Eurolab Deutschland GmbH, Germany

Liang Zhang Communications Research Centre, Canada

Abstract

This chapter introduces a complete framework for automatic adaptation of a 3D face model to a human face for visual communication applications like video conferencing or video telephony. First, facial features in a facial image are estimated. Then, the 3D face model is adapted using the estimated facial features. This framework is scalable with respect to complexity. Two complexity modes, a low complexity and a high complexity mode, are introduced. For the low complexity mode, only eye and mouth features are estimated and the low complexity face model Candide is adapted. For the

This chapter appears in the book, *3D Modeling and Animation: Synthesis and Analysis Techniques for the Human Body* edited by Nikos Sarris and Michael G. Strintzis. Copyright © 2005, IRM Press, an imprint of Idea Group Inc. Copying or distributing in print or electronic forms without written permission of Idea Group Inc. is prohibited.

high complexity mode, a more detailed face model is adapted, using eye and mouth features, eyebrow and nose features, and chin and cheek contours. Experimental results with natural videophone sequences show that with this framework automatic 3D face model adaptation with high accuracy is possible.

Introduction

In the last few years, virtual humans and especially animated virtual faces (also called talking heads) have achieved more and more attention and are used in various applications. In modern computer games, virtual humans act as football players or Kung Fu fighters. In movies, highly realistic animated virtual humans are replacing real actors (e.g., in the science fiction movie "Final Fantasy"). On the Internet, animated virtual faces are acting as news announcers or sales agents. In visual communication applications, like video telephony or video conferencing, the real faces of the participants are represented by virtual face clones of themselves. If we take a closer look at the technology behind these animated faces, the underlying shape of a virtual face is often built from a 3D wireframe consisting of vertices and triangles. This wireframe is textured using textures from a real person's facial image. Synthetic facial expressions are generated by animating the 3D wireframe. Usually, the face is animated by movement of the wireframe's vertices. In order to produce natural looking facial movements, an underlying animation structure (providing rules for animation) is needed, simulating the behavior of a real human face.

The creation of such an animated face requires generating a well-shaped and textured 3D wire-frame of a human face, as well as providing rules for animation of this specific 3D wireframe. There are different ways to create an animated face. One possibility is that an animated face is created manually by an experienced 3D modeler or animator. However, an automatic approach is less time consuming and is required for some applications. Dependent on the specific application and its requirements, different ways for the automatic creation of an animated face exist.

For 3D modeling of the shape of the head or face, i.e., for generation of the 3D wire-frame, techniques that are common for the 3D modeling of objects in general could be used. With a 3D scanner, a laser beam is sent out and reflected by the object's surface. Range data from the object can be obtained and used for 3D modeling. Other approaches use range data from multi-view images (Niem, 1994) obtained by multiple cameras for 3D modeling. All these techniques allow a very accurate 3D modeling of an object, i.e., a human head or face. However,

20 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: <u>www.igi-</u> <u>global.com/chapter/automatic-face-model-adaptation-</u>

two/4173

Related Content

Collaborative Spectra: Mille Feuille Design Workshop - Teaching Individuals Design through Group Work

Ammon Beyerleand Greg Missingham (2017). *Collaboration and Student Engagement in Design Education (pp. 257-282).* www.irma-international.org/chapter/collaborative-spectra/165685

A Study of Various Types of Natural Marble Towards Their Use in Cultural Applications

Nikolaos Andreas Kazakis, George I. Dallasand Nestor C. Tsirliganis (2020). International Journal of Art, Culture and Design Technologies (pp. 1-15). www.irma-international.org/article/a-study-of-various-types-of-natural-marble-towards-their-usein-cultural-applications/259876

CulturalNature Arga #2

Tiago Cruz, Fernando Faria Paulinoand Mirian Tavares (2014). *International Journal of Creative Interfaces and Computer Graphics (pp. 21-31).* www.irma-international.org/article/culturalnature-arga-2/113782

Detecting Bias on Aesthetic Image Datasets

Adrian Carballal, Luz Castro, Rebeca Perezand João Correia (2014). *International Journal of Creative Interfaces and Computer Graphics (pp. 62-74).* www.irma-international.org/article/detecting-bias-on-aesthetic-image-datasets/120642

A New Leaf

Liz Lee (2012). *Biologically-Inspired Computing for the Arts: Scientific Data through Graphics (pp. 278-288).* www.irma-international.org/chapter/new-leaf/65034