

Chapter 19

Online Remote Control of a Wireless Home Automation Network

John Wade

University of Ulster, Northern Ireland

Jose Santos

University of Ulster, Northern Ireland

Noel Evans

University of Ulster, Northern Ireland

ABSTRACT

Embedded systems within home appliances are not usually manufactured to operate in a networked environment; connecting supplementary hardware/software systems through a wireless, PC-controlled medium is necessary to enable full, efficient control of their functions from a remote location. Access to the home's central PC may be gained via a local web server, giving Internet-based control from almost anywhere in the world. The proposed system constitutes a significant improvement over those discussed in the literature to date, and reviewed here. It enables complex-appliance control in a secure and reliable portable-wireless environment, and was developed using ASP.Net. The system was assessed for Received Signal Strength (RSS) in an environment more radio-hostile than that found in a typical household. The minimum RF level found at a transfer rate of 9.6 kbps was 8 dB above the receiver's quoted sensitivity of -103 dBm; this fading margin will increase in a normal household environment.

INTRODUCTION

As the cost of electronics components and microprocessors decrease, they are embedded increasingly into every day household items,

e.g. microwave ovens, toasters, televisions and washing machines. Unfortunately it is still not possible to communicate with these appliances via a network, be that from within or outside the home. Although the appliances have embedded microprocessors to help control their onboard systems, they do not have the capability to com-

DOI: 10.4018/978-1-60960-549-0.ch019

municate with a network of any kind. This is because there are no communication devices pre-installed and as yet no clear leader exists in home automation network protocols. Until this happens, true home automation networks cannot be fully realised. This, however, does not limit the ability to remotely control appliances in the home. To do this, domestic appliances can be grouped as:

1. Appliances that can only be turned on and off (Group 1).
2. Appliances that can be controlled in a more functional manner, such as televisions, DVD players and HiFi equipment (Group 2).

There are many reasons why the ability to remotely control the home is an advantage. In modern times, security and time management have become important issues. Houses may give an impression of occupation through controlled lighting and have their alarm system monitored; kitchen tasks may be started remotely from a work location, saving time after the daily commute. A control network could also give the elderly and disabled a more independent way of life.

In section two, a background review of previous research into this topic is presented. Section three discusses the hardware design for the system investigated. Section four explores the software design for both the Internet interface and the firmware for the microprocessors. Section five discusses the testing protocol and results obtained from the system. Finally, section six presents conclusions and suggestions for future work.

Computer Controlled Home Automation

There have been several approaches to computer controlled home automation: what follows is a review of the most significant and recent contributions.

Al-Ali A.R. & Al-Rousan M. (2004) developed a system built from a Java based user interface

that was accessible through the World Wide Web. The system allowed the user to turn a cooker, light bulb or a fan on and off. This system used direct wiring from the computer to the appliances to exercise control over them: this approach is very costly due to the amount of cable needed to connect all the appliances found in a modern house. Also, appliances that fall into Group 2 could not be implemented in this system and introduction of new appliances into the household will result in further integration costs.

Sriskanathan N., (2002), proposed a system that controlled home appliances from a PC using Bluetooth as the communications technology. As before, there was no consideration for those appliances that fall into Group 2 and could not be controlled over the Internet. By using Bluetooth there is also a limit to the number of appliances that can be controlled. According to Stallings (2002), up to eight devices can communicate in a small network called a piconet, and up to ten piconets can coexist in the same coverage range of a Bluetooth radio. This permits up to 80 appliances to be connected. Although a significant number at present, in the future this may become a limitation on the system. Another disadvantage of Bluetooth is that it allows ad-hoc networking. This enables an appliance that is Bluetooth enabled to establish an instant connection with another Bluetooth enabled appliance in the network when it comes into range. The main implication of this statement is that as new appliances are introduced into the home, the PC software has to be able to identify the appliance and either accept it or reject it automatically.

Bigio P. & Cucos A. & Corcoran P & Chahil C & Lusted K. (1999) designed and implemented a non-standard means of wireless networking suitable for home automation. Their system consisted of a low-power RF network broadcasting on 433 MHz, which again is license-free as it falls in the Industrial Scientific & Medical (ISM) band according to the European Radio Commission Committee (2005).

9 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/online-remote-control-wireless-home/53339

Related Content

A Decision Support System for Classification of Normal and Medical Renal Disease Using Ultrasound Images: A Decision Support System for Medical Renal Diseases

Komal Sharma and Jitendra Virmani (2017). *International Journal of Ambient Computing and Intelligence* (pp. 52-69).

www.irma-international.org/article/a-decision-support-system-for-classification-of-normal-and-medical-renal-disease-using-ultrasound-images/179289

AmbiLearn: Multimodal Assisted Learning

Jennifer Hyndman, Tom Lunney and Paul Mc Kevitt (2011). *International Journal of Ambient Computing and Intelligence* (pp. 53-59).

www.irma-international.org/article/ambilearn-multimodal-assisted-learning/52041

negotiation behaviors in agent-based negotiation support systems

Manish Agrawal and Kaushal Chari (2011). *Intelligent, Adaptive and Reasoning Technologies: New Developments and Applications* (pp. 124-145).

www.irma-international.org/chapter/negotiation-behaviors-agent-based-negotiation/54428

Flexible and Hybrid Action Selection Process for the Control of Highly Dynamic Multi-Robot Systems

Lounis Adouane (2017). *Artificial Intelligence: Concepts, Methodologies, Tools, and Applications* (pp. 2431-2465).

www.irma-international.org/chapter/flexible-and-hybrid-action-selection-process-for-the-control-of-highly-dynamic-multi-robot-systems/173430

Fruit-Fly Optimization Algorithm for Disability-Specific Teaching Based on Interval Trapezoidal Type-2 Fuzzy Numbers

Deepak Aeloor (2020). *International Journal of Fuzzy System Applications* (pp. 35-63).

www.irma-international.org/article/fruit-fly-optimization-algorithm-for-disability-specific-teaching-based-on-interval-trapezoidal-type-2-fuzzy-numbers/245270