Chapter 3.7 DSOA: A Service Oriented Architecture for Ubiquitous Applications

Fabricio Nogueira Buzeto *Universidade de Brasília, Brazil*

Carlos Botelho de Paula Filho *Universidade de Brasília, Brazil*

Carla Denise Castanho *Universidade de Brasília, Brazil*

Ricardo Pezzuol Jacobi Universidade de Brasília, Brazil

ABSTRACT

Ubiquitous environments are composed by a wide variety of devices, each one with different characteristics like communication protocol, programming and hardware platforms. These devices range from powerful equipment, like PCs, to limited ones, like cell phones, sensors, and actuators. The services provided by a ubiquitous environment rely on the interaction among devices. In order to support the development of applications in this context, the heterogeneity of communication protocols must be abstracted and the functionalities dynamically provided by devices should be easily available to application developers. This paper proposes a Device Service Oriented Architecture (DSOA) as an abstraction layer to help organize devices and its resources in a ubiquitous environment, while hiding details about communication protocols from developers. Based on DSOA, a lightweight middleware (uOS) and a high level protocol (uP) were developed. A use case is presented to illustrate the application of these concepts.

1. INTRODUCTION

The presence of computer devices endowed with processing power and communication capabilities grows every day. Taking advantage of these capabilities in order to assist the user in its tasks demanding as minimum attention as possible is the basis of ubiquitous computing (Weiser & Brow, 1995). A smart space (Weiser, 1993) is an environment where the resources made available by the devices are organized and coordinated in order to provide intelligent services to the users.

DOI: 10.4018/978-1-61350-456-7.ch3.7

Such intelligence is implemented in the smart space through applications. In order to abstract and simplify the complexity for building these applications, it is common place the adoption of middlewares that facilitate the implementation of smart spaces. We can highlight some important requirements (Abowd, Atkeson, & Essa, 1998) that must be addressed by middlewares (Bernstein, 1996) for ubicomp.

- Limited devices are part of the smart space, so its limitations like CPU, memory, bandwidth and battery life must be considered. Such issues can be seen in middlewares like the MundoCore (Aitenbichler, Kangasharju, & Mühlhäuser, 2007).
- Interaction details on how applications and resources cooperate must be addressed. Not only synchronous but asynchronous communication must be taken into account. An example of a middleware in the literature that focus on these issues is MoCA (Sacramento et al., 2005). Communication can occur not only in small messages, but also can be streamlined as in the MediaBroker project (Modahl, Bagrak, Wolenetz, Hutto, & Ramachandran, 2004).
- Platform heterogeneity among devices. The hardware and software must be considered in order to allow the integration of as many devices as possible to the smart space. This type of concern is observed in projects like the Mundo-Core (Aitenbichler et al., 2007) and WSAMI (Issarny, Sacchetti, Chibout, Dalouche, & Musolesi, 2005) which provide solutions to multiple programming platforms.

Many middleware solutions, like the WSAMI project (Issarny et al., 2005) and the Home-SOA (The OSGi Alliance, 2009) utilize a SOA (MacKenzie, 2006) based solution. The use of SOA assists in the abstraction of the smart space functionalities in order to simplify the develop-

ment of smart applications. One problem with a pure SOA approach lies in the fact that it does not address some specific problems of ubicomp environments. For example, SOA does not define the way services are accessed, which is an important aspect in the ubicomp context.

This work proposes an extension of the SOA architecture, denominated DSOA (Device Service Oriented Architecture), to model a smart space taking into account the requirements outlined above. Founded on DSOA, we also developed a lightweight multi-platform communication interface, called uP, and the middle-ware uOS to support the development of smart applications. To illustrate some characteristics of the proposed model a use case, named Hydra Application, is also shown.

This paper is organized as follows. Some related works are presented in Section 2 while Section 3 describes the DSOA architecture. The protocol uP and the middleware uOS are presented in Sections 4 and 5 respectively. Section 6 brings into focus the Hydra Application. Some results and final considerations are addressed in Sections 7 and 8.

2. RELATED WORK

A ubicomp environment is permeated by applications that may run in a variety of devices, including static and mobile ones. In order to easy the development of this kind of software many initiatives can be found in the literature (Garlan, 2002; Cerqueira, 2001; Helal et al., 2005; Brumitt, Meyers, Krumm, Kern, & Shafer, 2000). Among these, we highlight four of them which achieve relevant contribution towards the three requisites presented on section 1.

2.1. MundoCore

The MundoCore (Aitenbichler et al., 2007) middleware focuses on the development of applica16 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/dsoa-service-oriented-architectureubiquitous/62467

Related Content

Digital Home: A Case Study Approach to Teaching Software Engineering Concepts

Salamah Salamah, Massood Towhidnejadand Thomas Hilburn (2018). *Computer Systems and Software Engineering: Concepts, Methodologies, Tools, and Applications (pp. 1284-1299).* www.irma-international.org/chapter/digital-home/192923

Identification of Genomic Islands by Pattern Discovery

Nita Parekh (2012). Computer Engineering: Concepts, Methodologies, Tools and Applications (pp. 742-758).

www.irma-international.org/chapter/identification-genomic-islands-pattern-discovery/62476

Investigating the Impacts of DEM Type, Resolution, and Noise on Extracted Hydro-Geomorphologic Parameters of Watersheds via GIS

Vahid Nourani, Safa Mokhtarian Asl, Maryam Khosravi Sorkhkolaee, Aida Hosseini Baghanamand Masoud Mehrvand (2018). *Emerging Trends in Open Source Geographic Information Systems (pp. 133-175).* www.irma-international.org/chapter/investigating-the-impacts-of-dem-type-resolution-and-noise-on-extracted-hydrogeomorphologic-parameters-of-watersheds-via-gis/205159

A Detailed Study on Single Electron Transistors in Nano Device Technologies

S. Darwin, E. Fantin Irudaya Raj, M. Appaduraiand M. Chithambara Thanu (2023). *Energy Systems Design for Low-Power Computing (pp. 67-99).*

www.irma-international.org/chapter/a-detailed-study-on-single-electron-transistors-in-nano-device-technologies/319990

Hybrid Control Systems: Integrating AI With Traditional Methods

Rituraj Jain, Kumar J. Parmar, Damodharan Palaniappanand T. Premavathi (2025). *Harnessing Al for Control Engineering (pp. 37-62).*

www.irma-international.org/chapter/hybrid-control-systems/377534