

# Chapter 3.19

## MMIR:

### An Advanced Content–Based Image Retrieval System Using a Hierarchical Learning Framework

**Min Chen**

*Florida International University, USA*

**Shu-Ching Chen**

*Florida International University, USA*

#### ABSTRACT

*This chapter introduces an advanced content-based image retrieval (CBIR) system, MMIR, where Markov model mediator (MMM) and multiple instance learning (MIL) techniques are integrated seamlessly and act coherently as a hierarchical learning engine to boost both the retrieval accuracy and efficiency. It is well-understood that the major bottleneck of CBIR systems is the large semantic gap between the low-level image features and the high-level semantic concepts. In addition, the perception subjectivity problem also challenges a CBIR system. To address these issues and challenges, the proposed MMIR system utilizes the MMM mechanism to direct the focus on the image level analysis together with the MIL technique (with the neural network technique as*

*its core) to real-time capture and learn the object-level semantic concepts with some help of the user feedbacks. In addition, from a long-term learning perspective, the user feedback logs are explored by MMM to speed up the learning process and to increase the retrieval accuracy for a query. The comparative studies on a large set of real-world images demonstrate the promising performance of our proposed MMIR system.*

#### INTRODUCTION

Content-based image retrieval (CBIR), which was proposed in the early 1990s, has attracted a broad range of research interests from many computer communities in the past decade. Generally speaking, in a CBIR system, each image is

first mapped to a point in a certain feature space, where the features can be categorized into color (Stehling, Nascimento, & Falcao, 2000), texture (Kaplan et al., 1998), shape (Zhang & Lu, 2002), and so forth. Next, given a query in terms of image examples, the system retrieves images with regard to their features (He, Li, Zhang, Tong, & Zhang, 2004). Though extensive research efforts have been directed into this area, it still remains a big challenge and an open issue in terms of retrieving the desired images from the large image repositories effectively and efficiently. In short, some of the major obstacles can be summarized as follows.

- First, it is widely accepted that the major bottleneck of CBIR systems is the large semantic gap between the low-level image features and high-level semantic concepts, which prevents the systems from being

applied to real applications (Hoi & Lyu, 2004).

- Second, the perception subjectivity problem poses additional challenges for CBIR systems. In other words, in viewing the same image (e.g., Figure 1a), different users might possess various interests in either a certain object (e.g., the house, the tree, etc.) or the entire image (e.g., a landscape during the autumn season). In this case, Figure 1b, Figure 1c, or Figure 1d, respectively, might be considered as the relevant image with regard to Figure 1a. In addition, even a same user can have different perceptions toward the same image at various situations and with different purposes.

To address the earlier-mentioned challenges and issues, a certain form of adaptive (i.e., data-driven) description is required to capture the

*Figure 1. Example images*




(a)



(b)



(c)



(d)

14 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:  
[www.igi-global.com/chapter/mmir-advanced-content-based-image/7965](http://www.igi-global.com/chapter/mmir-advanced-content-based-image/7965)

## Related Content

---

### Design of a Data Model for Social Networks Applications

Susanta Mitra, Aditya Bagchi and A. K. Bandyopadhyay (2009). *Advanced Principles for Improving Database Design, Systems Modeling, and Software Development* (pp. 360-385).

[www.irma-international.org/chapter/design-data-model-social-networks/4307](http://www.irma-international.org/chapter/design-data-model-social-networks/4307)

### Matching Attributes across Overlapping Heterogeneous Data Sources Using Mutual Information

Huimin Zhao (2012). *Cross-Disciplinary Models and Applications of Database Management: Advancing Approaches* (pp. 417-437).

[www.irma-international.org/chapter/matching-attributes-across-overlapping-heterogeneous/63676](http://www.irma-international.org/chapter/matching-attributes-across-overlapping-heterogeneous/63676)

### Economic Development: Government's Cutting Edge in IT

Gerald A. Merwin Jr., J. Scott McDonald and Levy C. Odera (2009). *Database Technologies: Concepts, Methodologies, Tools, and Applications* (pp. 1682-1722).

[www.irma-international.org/chapter/economic-development-government-cutting-edge/8000](http://www.irma-international.org/chapter/economic-development-government-cutting-edge/8000)

### The Need to Consider Hardware Selection when Designing Big Data Applications Supported by Metadata

Nathan Regola, David A. Cieslak and Nitesh V. Chawla (2014). *Big Data Management, Technologies, and Applications* (pp. 381-396).

[www.irma-international.org/chapter/the-need-to-consider-hardware-selection-when-designing-big-data-applications-supported-by-metadata/85464](http://www.irma-international.org/chapter/the-need-to-consider-hardware-selection-when-designing-big-data-applications-supported-by-metadata/85464)

### Dynamic Workflow Restructuring Framework for Long-Running Business Processes

Ling Liu, Calton Pu and Duncan Dubugras Ruiz (2005). *Advanced Topics in Database Research, Volume 4* (pp. 1-49).

[www.irma-international.org/chapter/dynamic-workflow-restructuring-framework-long/4367](http://www.irma-international.org/chapter/dynamic-workflow-restructuring-framework-long/4367)