Chapter 17 Intelligent Stereo Vision in Autonomous Robot Traversability Estimation

Lazaros Nalpantidis Royal Institute of Technology – KTH, Sweden

Ioannis Kostavelis Democritus University of Thrace, Greece

Antonios Gasteratos Democritus University of Thrace, Greece

ABSTRACT

Traversability estimation is the process of assessing whether a robot is able to move across a specific area. Autonomous robots need to have such an ability to automatically detect and avoid non-traversable areas and, thus, stereo vision is commonly used towards this end constituting a reliable solution under a variety of circumstances. This chapter discusses two different intelligent approaches to assess the traversability of the terrain in front of a stereo vision-equipped robot. First, an approach based on a fuzzy inference system is examined and then another approach is considered, which extracts geometrical descriptions of the scene depth distribution and uses a trained support vector machine (SVM) to assess the traversability. The two methods are presented and discussed in detail.

INTRODUCTION

Autonomous robots need to be able to operate in unknown, harsh environments and stereo vision can provide the means to cope with them in an efficient way. A basic but essential aspect of robots' autonomous operation is the assessment of terrain traversability, i.e. whether the robot is able to move towards a specific area or whether there are obstacles in front of it. Obstacle detection and traversability evaluation are important, as they provide crucial information for the safe navigation of mobile robots either for use in outdoor operations (Baudoin et al., 2009), or for use in space exploration, e.g. ESA's ExoMars rover (Kostavelis, Boukas, Nalpantidis, Gasteratos, &

DOI: 10.4018/978-1-4666-4607-0.ch017

Figure 1. Robots equipped with potential stereo vision traversability estimation abilities



Aviles Rodrigalvarez, 2011), shown in Figure 1. However, the actual methodology to extract this kind of information in a resource-efficient manner is still an active and interesting research topic.

There is a plethora of non-vision sensors that are used by autonomous robots. Yet, stereo vision tends to be a favorable solution due to its versatile nature and its inherent biomimetic origin that have been proven to be of great reliability under a variety of circumstances. As a result, autonomous robots often use stereo vision as their primary source of information about the structure of the world around them. The requirements placed by robotic applications are very strict and, in general, different from the requirements usually adopted by the computer vision community. As such, special care has to be attributed to the characteristics of the vision system. However, solid stereo perception constitutes only the first step towards more advanced operations. When it comes for autonomous robots, the next big issue is terrain traversability estimation, and as a consequence obstacle avoidance. In this chapter two alternative approaches are discussed, both suitable for stereo vision equipped autonomous robots. More specifically, the first approach (Nalpantidis & Gasteratos, 2011) detects obstacles in the scene and avoids them based on a fuzzy inference system (FIS). 3D vision information is used by the algorithm to analyze depth maps and deduce the most appropriate direction for the robot to avoid any existing obstacles. On the other hand, the second approach considered (Kostavelis, Nalpantidis, & Gasteratos, 2011) uses a machine learning method based on a support vector machine (SVM) for the traversability classification of the terrain. A v-disparity image calculation and processing step extracts suitable features about the scene's characteristics. The resulting data are used as input for the training of the SVM. This approach is able to classify the scenes either as traversable or nontraversable with high success rates. The two approaches are different in essence and each one mainly focuses on different aspects, as it will be discussed.

BACKGROUND

Depth Estimation Using Stereo Vision

Stereo vision is often used in vision-based robotics, instead of monocular sensors, due to the simpler calculations involved in the depth estimation. A correspondence search between the two stereo images can provide dense information about the depth of the depicted scene. In the case of stereo vision-based navigation, the accuracy and the refresh rate of the computed disparity maps are the cornerstones of its success (Schreer, 1998). Dense local stereo correspondence methods calculate depth for almost every pixel of the scene, taking into consideration only a small neighborhood of pixels each time (Scharstein & Szeliski, 2002). On the other hand, global methods are significantly more accurate but at the same time more computationally demanding, as they account for the whole image (Torra & Criminisi, 2004). However, since the most important constraint in autonomous robotics is the real-time operation, such applications usually utilize local algorithms. Muhlmann et al. in (Muhlmann, Maier, Hesser, & Manner, 2002) describe a local method that uses the sum of absolute differences (SAD) correlation measure for RGB color images. Applying a left to right consistency check, the uniqueness constraint and a median filter, it can achieve 20

14 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/intelligent-stereo-vision-in-autonomous-robottraversability-estimation/84902

Related Content

Segmentation of Leukemia Cells Using Clustering: A Comparative Study

Eman Mostafaand Heba A. Tag El-Dien (2019). *International Journal of Synthetic Emotions (pp. 39-48).* www.irma-international.org/article/segmentation-of-leukemia-cells-using-clustering/243685

The Semantic Dominance of Emotional Templates in Cognitive Structures

Tom Adi (2015). International Journal of Synthetic Emotions (pp. 1-13). www.irma-international.org/article/the-semantic-dominance-of-emotional-templates-in-cognitive-structures/160800

Application of the Principle of Rational Approximations for Measuring Dynamic Frequency Values Generated by an IMU

Fabian N. Murrieta-Rico, Vitalii Petranovskii, Juan de Dios Sanchez-Lopez, Juan Ivan Nieto-Hipolito, Mabel Vazquez-Briseño, Joel Antúnez-García, Rosario I. Yocupicio-Gaxiolaand Vera Tyrsa (2020). *Control and Signal Processing Applications for Mobile and Aerial Robotic Systems (pp. 26-51).* www.irma-international.org/chapter/application-of-the-principle-of-rational-approximations-for-measuring-dynamic-frequency-values-generated-by-an-imu/243763

Cloud Security Using 2-Factor Image Authentication Technique

Ratish Agarwal, Anjana Pandeyand Mahesh Pawar (2017). *Detecting and Mitigating Robotic Cyber Security Risks (pp. 135-147).*

www.irma-international.org/chapter/cloud-security-using-2-factor-image-authentication-technique/180066

Analysis of Direct Sensor-to-Embedded Systems Interfacing: A Comparison of Targets' Performance

Lars E. Bengtsson (2012). International Journal of Intelligent Mechatronics and Robotics (pp. 41-56). www.irma-international.org/article/analysis-direct-sensor-embedded-systems/64218