Fuzzy Graphs and Fuzzy Hypergraphs

Leonid S. Bershtein

Taganrog Technological Institute of Southern Federal University, Russia

Alexander V. Bozhenyuk

Taganrog Technological Institute of Southern Federal University, Russia

INTRODUCTION

Graph theory has numerous application to problems in systems analysis, operations research, economics, and transportation. However, in many cases, some aspects of a graph-theoretic problem may be uncertain. For example, the vehicle travel time or vehicle capacity on a road network may not be known exactly. In such cases, it is natural to deal with the uncertainty using the methods of fuzzy sets and fuzzy logic.

Hypergraphs (Berge, 1989) are the generalization of graphs in case of set of multiarity relations. It means the expansion of graph models for the modeling complex systems. In case of modelling systems with fuzzy binary and multiarity relations between objects, transition to fuzzy hypergraphs, which combine advantages both fuzzy and graph models, is more natural. It allows to realise formal optimisation and logical procedures.

However, using of the fuzzy graphs and hypergraphs as the models of various systems (social, economic systems, communication networks and others) leads to difficulties. The graph isomorphic transformations are reduced to redefinition of vertices and edges. This redefinition doesn't change properties the graph determined by an adjacent and an incidence of its vertices and edges.

Fuzzy independent set, domination fuzzy set, fuzzy chromatic set are invariants concerning the isomorphism transformations of the fuzzy graphs and fuzzy hypergraph and allow make theirs structural analysis.

BACKGROUND

The idea of fuzzy graphs has been introduced by Rosenfeld in a paper in (Zadeh, 1975), which has also been discussed in (Kaufmann, 1977).

The questions of using fuzzy graphs for cluster analysis were considered in (Matula, 1970, Matula, 1972). The questions of using fuzzy graphs in Database Theory were discussed in (Kiss, 1991). The tasks of allocations centers on fuzzy graphs were considered in (Moreno, Moreno & Verdegay, 2001, Kutangila-Mayoya & Verdegay, 2005, Rozenberg & Starostina, 2005). The analyses and research of flows and vitality in transportation nets were considered in (Bozhenyuk, Rozenberg & Starostina, 2006). The fuzzy hypergraph applications to portfolio management, managerial decision making, neural cell-assemblies were considered in (Monderson & Nair, 2000). The using of fuzzy hypergraphs for decision making in CAD-Systems were also considered in (Malyshev, Bershtein & Bozhenyuk, 1991).

MAIN DEFINITIONS OF FUZZY GRAPHS AND HYPERGRAPHS

This article presents the main notations of fuzzy graphs and fuzzy hypergraphs, invariants of fuzzy graphs and hypergraphs.

Fuzzy Graph

Let a fuzzy direct graph $\widetilde{G} = (X, \widetilde{U})$ is given, where X is a set of **vertices**, $\widetilde{U} = \{\mu_U(x_i, x_j) | (x_i, x_j) \in X^2\}$ is a fuzzy set of **edges** with the membership function μ_U : $X^2 \rightarrow [0,1]$ (Kaufmann, 1977).

Example 1. Let fuzzy graph \widetilde{G} has $X = \{x_1, x_2, x_3, x_4\}$, and $\widetilde{U} = \{<0.5/(x_1, x_2)>, <0.6/(x_2, x_3)>, <0.3/(x_3, x_4)>, <0.2/(x_4, x_1)>, <1/(x_4, x_2)>\}$. It is presented in figure 1.

The fuzzy graph \widetilde{G} may present a fuzzy dependence relation between objects x_1, x_2, x_3 , end x_4 . If the object x_1 fuzzy depends from the object x_1 , then there is direct edge (x_1, x_2) with membership function $\mu_{II}(x_1, x_2)$.

If a fuzzy relation, presented by fuzzy graph \widetilde{G} , is symmetrical, we have the fuzzy nondirect graph.

Figure 1.



A fuzzy graph $\tilde{G} = (X, \tilde{U})$ is convenient for representing as fuzzy **adjacent matrix** $\|r_{ij}\|_{n < u}$, where $r_{ij} = \mu_U(x_i, x_j)$. So, the fuzzy graph, presented in figure 1, may be consider by adjacent matrix:

	x_1	x_2	x_3	x_4
x_1	0	0,5	0	0
$R_X = x_2$	0	0	0,6	0
x_3	0	0	0	0.3
x_4	0,2	1	0	0

The fuzzy graph $\widetilde{H} = (X', \widetilde{U}')$ is called a fuzzy **subgraph** (Monderson & Nair, 2000) of $\widetilde{G} = (X, \widetilde{U})$ if $X' \subseteq X$ and $\widetilde{U}' \subseteq \widetilde{U}$.

Fuzzy directed **path** (Bershtein & Bozhenyuk, 2005) $\widetilde{L}(x_i, x_m)$ of graph $\widetilde{G} = (X, \widetilde{U})$ is called the sequence of fuzzy directed edges from vertex x_i to vertex x_m :

$$\begin{split} \widetilde{L}(x_i, x_m) = & \mu_U(x_i, x_j) / (x_i, x_j) >, < \mu_U(x_j, x_k) / (x_j, x_k) >, ... \\ ..., < & \mu_U(x_1, x_m) / (x_1, x_m) >. \end{split}$$

Conjunctive strength of path $\mu(\widetilde{L}(x_i,x_m))$ is defined as:

$$\mu\left(\widetilde{L}(x_{i},x_{m})\right) = \overset{}{\underset{< x_{\alpha},x_{\beta} > ?}{\&}} \overset{}{\underset{L(x_{i},x_{m})}{\mu_{U}}} \mu_{U} < x_{\alpha}, x_{\beta} >$$

Fuzzy directed path $L(x_i,x_m)$ is called simple path between vertices x_i and x_m if its part is not a path between the same vertices. If a number of vertices $n \ge 3$ and $x_i = x_m$, then the path is called a cycle.

Obviously, what is it definition coincides with the same definition for nonfuzzy graphs.

Vertex *y* is called fuzzy accessible from vertex *x* in the graph $\tilde{G} = (X, \tilde{U})$ if exists a fuzzy directed path from vertex *x* to vertex *y*.

The accessible degree of vertex y from vertex x, $(x\neq y)$ is defined by expression:

$$\chi(x,y) = \max_{\alpha} (\mu(\widetilde{L}_{\alpha}(x,y)), \alpha = 1,2,...,p)$$

where p - number of various simple directed paths from vertex x to vertex y.

A subset of vertices X' is called a fuzzy independent vertex set (Bershtein & Bozhenuk, 2001) with the degree of independence

$$\alpha(X') = 1 - \max_{\substack{? \, x_i, x_j \in X}} \{\mu_U(x_i, x_j)\}.$$

A subset of vertices $X' \subseteq X$ of graph \widetilde{G} is called a maximal fuzzy independent **vertex** set with the degree $\alpha(X')$, if the condition $\alpha(X'') < \alpha(X')$ is true for any $X' \subset X''$.

Let a set $\tau_k = \{X_{kl}, X_{k2}, ..., X_{kl}\}$ be given where X_{ki} is a fuzzy independent *k*-vertex set with the degree of independent α_{ki} . We define as

$$\alpha_{\mathbf{h}}^{\max} = \max\{\alpha_{X_{\mathbf{h}}^{1}}, \alpha_{X_{\mathbf{h}}^{2}}, \dots, \alpha_{X_{\mathbf{h}}^{1}}\}$$

The value α_{k}^{\max} means that fuzzy graph \widetilde{G} includes k-vertex subgraph with the degree of independent α_{k}^{\max} and doesn't include k-vertex subgraph with the degree of independence more than α_{k}^{\max} .

A fuzzy set

$$\Psi_{x} = \{ < \alpha_{1}^{\max} / 1 >, < \alpha_{2}^{\max} / 2 >, ..., < \alpha_{n}^{\max} / n > \}$$

is called a fuzzy **independent set** of fuzzy graph \widetilde{G} .

Fuzzy graph \tilde{G} , presented in figure 1, has seven maximum fuzzy independent vertex sets:

$$\Psi_1 = \{x_2\}, \ \Psi_2 = \{x_4\}, \ \Psi_3 = \{x_1, x_3\}$$

with the degree of independence 1; $\Psi_4 = \{x_1, x_4\}$ with the degree of independence 0,8; $\Psi_5 = \{x_1, x_3, x_4\}$ with 4 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-

global.com/chapter/fuzzy-graphs-fuzzy-hypergraphs/10322

Related Content

Load Balancing of Unbalanced Assignment Problem With Hungarian Method

Ranjan Kumar Mondal, Payel Ray, Enakshmi Nandi, Biswajit.Biswas, Manas Kumar Sanyaland Debabrata Sarddar (2019). *International Journal of Ambient Computing and Intelligence (pp. 46-60).* www.irma-international.org/article/load-balancing-of-unbalanced-assignment-problem-with-hungarian-method/216469

Applications of Drones in High-Tech Agriculture

Aamir Raza, Muhammad Safdar, Muhammad Adnan Shahid, Fahd Rasuland Rehan Mehmood Sabir (2023). Handbook of Research on Al-Equipped IoT Applications in High-Tech Agriculture (pp. 88-108). www.irma-international.org/chapter/applications-of-drones-in-high-tech-agriculture/327830

Speech-to-Speech Conversion: An Approach to Enhance the Speech Intelligibility of Dysarthric Speaker

Siddhanna Janai, Shreekanth T., Chandan M.and Ajish K. Abraham (2021). *International Journal of Ambient Computing and Intelligence (pp. 184-206).*

www.irma-international.org/article/speech-to-speech-conversion/272044

Assessing the Impact of Green Finance Investments on Sustainable Development

Shipra Shukla, Anshu Dixit, Jyoti Mishraand Zakir Hossen Shaikh (2024). *Issues of Sustainability in AI and New-Age Thematic Investing (pp. 202-215).*

www.irma-international.org/chapter/assessing-the-impact-of-green-finance-investments-on-sustainable-development/342450

Myth, Metaphor, and the Evolution of Self-Awareness

Terry Marks-Tarlow (2014). *International Journal of Signs and Semiotic Systems (pp. 46-60).* www.irma-international.org/article/myth-metaphor-and-the-evolution-of-self-awareness/104642