Chapter 10 Intelligent Detection of Heart Disorders

ABSTRACT

In this chapter, the first stage for detecting heart disorders (that is, noise removal) is explained. Two intelligent approaches based on Self Organizing Map (SOM) and Particle swarm Optimization (PSO) are used to train the feedforward neural network for noise removal. The trained ANNs are used to find the cutoff frequency. Then the found cutoff frequency is applied by a bandpass FIR filter for ECG noise removal.

1 INTRODUCTION

In this part, four heart disorders including bundle branch block, supraventricular tachycardia, anterior myocardial infarction (anterior MI) and inferior myocardial infarction (inferior MI), as well as normal ECG, will be classified using proposed intelligent method.

This chapter discusses the methodology to be employed in this research including the proposed method for classification as well as some related theory, with the implementation details given in the next chapter.

2 DATA COLLECTION

The biomedical research community uses the Physiobank archive of ECG signals (Physionet, 2012) for testing different studies. Since the collected signals are to be classified in the final stage of this project, having the correct classification of signals is necessary. Therefore, by consultation with heart specialist, 100 ECG signals were selected from three databases of Physiobank: the MIT-BIH Supraventricular Arrhythmia Database, the MIT-BIH Normal Sinus Rhythm Database, and the MIT-BIH Arrhythmia Database. The sampling frequency of the first two databases was 250 Hz, while the signals of the third database were sampled at 360 Hz.

The MIT-BIH Arrhythmia Database came into existence in 1980 for use in evaluating of detectors of arrhythmias, and it has become publicly available It was the first generally available collection of standard test signals and has become a worldwide standard Arrhythmia Database.

The Supraventricular Arrhythmia database includes the examples of supraventricular arrhythmias in the MIT-BIH Arrhythmia Database.

The normal Sinus Rhythm Database includes subjects referred to the Arrhythmia Laboratory at Boston's Beth Israel Hospital that were found to have had no significant arrhythmias; they include 5 men, aged 26 to 45, and 13 women, aged 20 to 50 (Physionet, 2012).

3 METHODOLOGY STAGES

A database of 100 lead II ECG signals was obtained from the Physiobank database. Figure 1 shows the simplified overall algorithm for the classification.

• **Preprocessing:** The noise from powerline interferences, as well as motion artifcats from the electrode and skin interface, affect the QRS complex, P and T waves of the ECG signals. In the preprocessing, two intelligent approaches based on Self Organizing Map (SOM) and PSO neural network (PSONN) for finding the cutoff frequency, are proposed and applied with one of the traditional models commonly used by many researchers (Losada, 2004; Orfanidis,



Figure 1. Flowchart of overall methodology for ECG classification

28 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: <u>www.igi-</u> <u>global.com/chapter/intelligent-detection-of-heart-</u> <u>disorders/111006</u>

Related Content

Big Data Analytics and Visualization for Food Health Status Determination Using Bigmart Data

Sumit Arun Hirveand Pradeep Reddy C. H. (2020). *Big Data Analytics for Sustainable Computing (pp. 179-205).*

www.irma-international.org/chapter/big-data-analytics-and-visualization-for-food-health-statusdetermination-using-bigmart-data/238612

Application of Multiple Regression and Artificial Neural Networks as Tools for Estimating Duration and Life Cycle Cost of Projects

Brian J. Galli (2022). *Research Anthology on Artificial Neural Network Applications* (pp. 509-540).

www.irma-international.org/chapter/application-of-multiple-regression-and-artificial-neuralnetworks-as-tools-for-estimating-duration-and-life-cycle-cost-of-projects/288973

Astrocytes and the Biological Neural Networks

Eduardo D. Martinand Alfonso Araque (2006). *Artificial Neural Networks in Real-Life Applications (pp. 22-46).*

www.irma-international.org/chapter/astrocytes-biological-neural-networks/5362

Higher Order Neural Network for Financial Modeling and Simulation

Partha Sarathi Mishraand Satchidananda Dehuri (2016). *Applied Artificial Higher Order Neural Networks for Control and Recognition (pp. 440-466).*

www.irma-international.org/chapter/higher-order-neural-network-for-financial-modeling-andsimulation/152115

Artificial Multi-Polynomial Higher Order Neural Network Models

Ming Zhang (2013). Artificial Higher Order Neural Networks for Modeling and Simulation (pp. 1-29).

www.irma-international.org/chapter/artificial-multi-polynomial-higher-order/71792