

Understanding RFID (Radio Frequency Identification)

Susan A. Vowels
Washington College, USA

INTRODUCTION

RFID, also known as radio frequency identification, is a form of Auto ID (automatic identification). Auto ID is defined as “the identification of an object with minimal human interaction” (Puckett, 1998). Auto ID has been in existence for some time; in fact, the bar code, the most ubiquitous form of Auto ID, celebrated its 30th year in commercial use in 2004 (Albright, 2004). Barcodes identify items through the encoding of data in various sized bars using a variety of symbologies, or coding methodologies. The most familiar type of barcode is the UPC, or universal product code, which provides manufacturer and product identification. While barcodes have proven to be very useful, and indeed, have become an accepted part of product usage and identity, there are limitations with the technology. Barcode scanners must have line of sight in order to read barcode labels. Label information can be easily compromised by dirt, dust, or rips. Barcodes take up a considerable footprint on product labels. Even the newer barcode symbologies, such as 2D, or two-dimensional, which can store a significant amount of data in a very small space (“Two dimensional...,” 2005) remain problematic. RFID proponents argue that limitations of barcodes are overcome through the use of RFID labeling to identify objects.

HISTORY OF RFID

Jeremy Landt (2001) wrote a history of RFID published by AIM, The Association for Automatic Identification and Data Capture Technologies, explaining that in the 20th century, the invention of radar took advantage of the electromagnetic energy that some postulate to have been present at the creation of the universe. By broadcasting and analyzing the reflection of radio waves, radar can identify two important characteristics about an object, its position and its velocity. This application of radio waves was a precursor to the use of radio waves in radio frequency identification.

During the 1950s, transponders were developed and improved, becoming increasingly more sophisticated and allowing for long-range determination of the identification of aircraft (Landt, 2001). Through the decades of the 1960s, 1970s, and 1980s, inventors, academicians, commercial enterprises, and governmental agencies explored a plethora of opportunities related to the use of early RFID devices, using radio transmissions, “short-range radio-telemetry,” microwave technology, and radar beams (Landt, 2001). Landt states that RFID was first used commercially in the 1960s by companies that developed security related devices called “electronic article surveillance (EAS) equipment.” Although EAS could only present the detection or absence of a tag, the tags were low cost

Figure 1. Barcode examples



Code 39 (Source:
<http://www.idautomation.com/fonts/free/word-example.gif>)



UPC-A (Source:
<http://www.idautomation.com/upceanfaq.html>)

and provided valuable deterrents to theft. EAS is still an important application of RFID today.

Work continued through the 1970s and in the 1980s, as companies began offering a variety of RFID related business solutions, primarily aimed at transportation, controlled access, and animal tracking applications (Landt, 2001). Of primary importance, in 1973 the United States government determined that there was no need for a national standard for electronic vehicle identification. This was serendipitous because it meant that individual firms, researchers, and others could have the freedom to develop new uses of RFID without being constrained by a governing body (Landt, 2001).

RFID TECHNOLOGY

Radio Frequency

Electromagnetic waves are comprised of a continuum of emanations, including visible light waves, and invisible frequencies such as television and radio waves, which are lower frequency than light, and x-rays and gamma rays, which are higher frequency than light. Frequencies are measured in Hertz (Hz), kilohertz (kHz), megahertz (MHz), or gigahertz (GHz), and represent the rate of oscillation of the waves. The portion of the electromagnetic spectrum used by radio frequency identification includes LF (low frequency), HF (high frequency), and UHF (ultra high frequency), which are all portions of the radio wave frequency bands, hence the term “radio frequency identification.” An advantage of radio waves over visible light is that radio waves can penetrate many substances that would block visible light. Radio waves range from 300 kHz to 3 GHz (Hodges et al, 2003). Specific frequencies use is controlled by governmental agencies.

Some of the concerns relating to RFID are inherent to the technology upon which it is based. For instance, the range over which devices using radio waves can consistently communicate is affected by the following factors:

1. The **power** contained in the wave transmitted
2. The **sensitivity** of the receiving equipment
3. The **environment** through which the wave travels
4. The presence of **interference** (Hodges et al., 2003)

Hardware Components

The radio frequency transmissions in RFID travel between the two primary components, the **RFID reader** and the **RFID tag**. The reader can be mobile or stationary and is the proactive component. It consists of an antenna and a transceiver, is supplied with power, and generates and transmits a signal from its antenna to the tag and then reads the information reflected from the tag (Hodges et al., 2003). The antenna is used to send and receive signals; the transceiver is used to control and interpret the signals sent and received (“What is...,” 2005). The tag, a transponder, is affixed to the object being identified, such as an automobile, a shipping pallet, or a tagged marine mammal. Thus, we can see a major benefit in using RFID since the data is exchanged using radio waves; it is not necessary to have line of sight between a reader and a tag, such as is required with barcodes. This permits a great deal more flexibility in the use of the RFID.

Although all readers have an external power source, tags may be completely without power or with some degree of power, and fall into three categories¹: (1) **Passive tags** are inert; they do not have any power source and must use energy from the radio wave that

Figure 2. The electromagnetic spectrum (Adapted from Hodges, 2003)

AM Radio		TV	Microwaves						
		FM Radio	FM Radar						
<u>LF</u>	MF	<u>HF</u>	VHF	<u>UHF</u>	Infrared	Visible Light	Ultraviolet	X-rays;	Gamma Rays
<i>Low frequency</i>							<i>High frequency</i>		
<i>Long wavelength</i>							<i>Short wavelength</i>		

7 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/understanding-rfid-radio-frequency-identification/13435

Related Content

Student Readiness and Perception of Tablet Learning in Higher Education in the Pacific- A Case Study of Fiji and Tuvalu: Tablet Learning at USP

Pritika Reddy, Bibhya Sharma and Shaneel Chandra (2020). *Journal of Cases on Information Technology* (pp. 52-69).

www.irma-international.org/article/student-readiness-and-perception-of-tablet-learning-in-higher-education-in-the-pacific-a-case-study-of-fiji-and-tuvalu/247996

Knowledge, Culture, and Cultural Impact on Knowledge Management: Some Lessons for Researchers and Practitioners

Deogratias Harorimana (2010). *Information Resources Management: Concepts, Methodologies, Tools and Applications* (pp. 1293-1304).

www.irma-international.org/chapter/knowledge-culture-cultural-impact-knowledge/54543

Towards a New Model for Knowledge Construction and Evolution

Antonio Cartelli (2009). *Encyclopedia of Information Communication Technology* (pp. 767-774).

www.irma-international.org/chapter/towards-new-model-knowledge-construction/13433

Relationship of Skill Expectation Gap Between IS Employees and Their Managers with User Satisfaction

James Jiang, Gary Klein and Eric T.G. Wang (2007). *Information Resources Management Journal* (pp. 63-75).

www.irma-international.org/article/relationship-skill-expectation-gap-between/1321

Information Management: Jurisdictional, Legal and Ethical Factors

Michael Losavio, Adel Elmaghraby and Deborah Keeling (2009). *Open Information Management: Applications of Interconnectivity and Collaboration* (pp. 406-420).

www.irma-international.org/chapter/information-management-jurisdictional-legal-ethical/27806