# Chapter 20 Sensitivity Analysis of Laser Cutting Based on Metamodeling Approach

**Toufik Al Khawli** RWTH Aachen University, Germany

**Urs Eppelt** *RWTH Aachen University, Germany* 

**Wolfgang Schulz** Fraunhofer Institute for Laser Technology, Germany

### ABSTRACT

In this work, the utility of a metamodel in gaining valuable information relating to the optimization of a laser cutting process using a CW laser source is analyzed. The simulation itself is characterized by a high dimensional input parameter set. Each parameter has its own range, and thus the complete parameter sets with their ranges form the full parameter domain space. The quality criteria are analyzed and used as objective function to optimize the process. Simulation results can only help in the build-up of process understanding, if they can be presented in their entirety and together with their origin in the parameter domain. For this purpose a metamodeling concept is presented, which takes the results from simulations and generates a process map that clearly indicates the process domains. For gaining insights, the Elementary Effect method is applied to screen the important parameters that exhibit the greater impact on the process.

#### INTRODUCTION

Nowadays, the global interest is strongly affected by economic, ecological, and social trends of the last decades such as globalization, global warming, shortage of energy resources, or even financial crises (Schmidt et al., 2011). Due to these trends, several complexities rise in production. For example, shorter product lifecycles, a higher global price competition, and faster changing market demands, put

DOI: 10.4018/978-1-4666-8823-0.ch020

#### Sensitivity Analysis of Laser Cutting Based on Metamodeling Approach

the production companies under pressure to make their workflows more efficient and more scalable, and to provide reliable and cost-effective responses to unpredictable changes that take place in a global market (Schuh et al., 2011).

Production planning and scheduling requires a large amount of human information processing and decision-making. Complex manufacturing systems and processes involve more demanding tasks for today's planners and schedulers (Heilala et al., 2010). Manufacturing, engineering and production management decisions involve the consideration of the effect of multidimensional parameters on preselected criteria onto the process. The relationship between interdependent parameters and criteria is first very difficult to achieve, and second very complex for the human mind to handle at a time. Recently, a modern approach to enhance the tasks of planners and schedulers to run production more efficiently has gained considerable importance (Gasser et al., 2011). It is based on using a simulation-based decision support system in the field of production technology (Mönch, 2007).

The simulation applications have positively influenced the research departments and production environments. In research departments, these applications are enabling a better understanding of the production processes, since they allow for decomposing those multi-physical interactions or complex material modeling and study their individual influence on the final processing result. However, in production environments, simulations are serving as a tool for planning and optimizing either a single production step, or even whole process chains (Otto et al. 2011).

The conventional approach in modeling and simulation of manufacturing processes so far is performing several sets of individual simulations. Pieces of information or rules are then extracted directly via data analysis of these single simulation results. The important goal of scientific data analysis is to understand and extract the behavior of the process based on a sample data set that contains the input parameters and the output criteria, and characterizes the system as a high-dimensional function (Fayyad et al., 1996). Each individual simulation is characterized by a set of parameters in a high-dimensional parameter space. If the following constraints exist: i) the time required for performing the simulation model increases; ii) the number of the parameter space dimensions rises; or iii) the complexity of the simulation model becomes highly nonlinear. The data analysis procedure will require a huge set of data that is, due to time constraints, difficult to achieve. Furthermore, when the simulation time increases, the conventional analysis tasks such as optimization, sensitivity analysis, or design space exploration will become impractical due to the high number of evaluation runs. Although the computational power available has been rapidly increasing over the years, it is still not feasible to run full numerical simulations of multi physics applications at a reasonable computational cost. For example, it takes Ford Motor Company about 36–160 hours to run one crash simulation, see (Gu, 2001). Thus, the total computation time required for optimizing such a task, by executing only 50 iterations, would be around 75 days – to 11 months, which is in practice unacceptable. Additionally, it is important to declare that the parametercriteria relationship approach is just revealed by a set of discrete data and thereby may already be indicated by taking advantage of appropriate scatter-diagrams mapping parameters on criteria. To overcome these difficulties, researchers are recently using approximation models that mimic the behavior of the expensive simulation up to a required accuracy. These models, also known as metamodels, are not only faster but also less expensive than physical simulation models that are questioned again and again when running an operation on the model. Once a fast predictive metamodel is achieved, a sensitivity analysis study or evolutionary multidimensional optimization can be easily performed by using the metamodel as an emulator or data generator.

20 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/sensitivity-analysis-of-laser-cutting-based-onmetamodeling-approach/137456

## **Related Content**

#### Multi-Agent Economically Motivated Decision-Making

Paulo Trigo (2014). Interdisciplinary Applications of Agent-Based Social Simulation and Modeling (pp. 165-183).

www.irma-international.org/chapter/multi-agent-economically-motivated-decision-making/106768

#### Industrial Augmented Reallity Applications

Holger Regenbrecht (2007). *Emerging Technologies of Augmented Reality: Interfaces and Design (pp. 283-304).* 

www.irma-international.org/chapter/industrial-augmented-reallity-applications/10169

#### Digital Twins in Healthcare: Addressing Concerns and Meeting Professional Needs

Christina Joseph Jyothula, Kishor Kumar Reddy C.and Thandiwe Sithole (2024). *Exploring the Advancements and Future Directions of Digital Twins in Healthcare 6.0 (pp. 48-68).* www.irma-international.org/chapter/digital-twins-in-healthcare/350996

# Multiobjective Optimization in Water and Environmental Systems Management- MODE Approach

Janga Reddy Manne (2016). Handbook of Research on Advanced Computational Techniques for Simulation-Based Engineering (pp. 120-136).

www.irma-international.org/chapter/multiobjective-optimization-in-water-and-environmental-systems-management--mode-approach/140387

#### Knowledge-Based Externalities and Geographical Clusters: An Agent-Based Simulation Study

Nunzia Carbonara (2014). Interdisciplinary Applications of Agent-Based Social Simulation and Modeling (pp. 269-286).

www.irma-international.org/chapter/knowledge-based-externalities-and-geographical-clusters/106775