Cognitive Learning Methodologies for Brain-Inspired Cognitive Robotics

Yingxu Wang, University of Calgary, Calgary, Alberta, Canada

ABSTRACT

Cognitive robots are brain-inspired robots that are capable of inference, perception, and learning mimicking the cognitive mechanisms of the brain. Cognitive learning theories and methodologies for knowledge and behavior acquisition are centric in cognitive robotics. This paper explores the cognitive foundations and denotational mathematical means of cognitive learning engines (CLE) and cognitive knowledge bases (CKB) for cognitive robots. The architectures and functions of CLE are formally presented. A content-addressed knowledge base access methodology for CKB is rigorously elaborated. The CLE and CKB methodologies are not only designed to explain the mechanisms of human knowledge acquisition and learning, but also applied in the development of cognitive robots, cognitive computers, and knowledge-based systems.

Keywords: Abstract Intelligence, Artificial Intelligence, Autonomous Learning, Brain Science, Cognitive Computing, Cognitive Informatics, Cognitive Knowledge Base, Cognitive Machine Learning, Cognitive Robotics, Cognitive Systems, Computational Intelligence, Denotational Mathematics, Intelligence Science, Neuroinformatics

1. INTRODUCTION

A cognitive robot is a brain-inspired robot system that is capable of inference, perception, and learning mimicking the cognitive mechanisms of humans. The fundamental theories and methodologies underpinning cognitive robotics are the cognitive learning engines (CLE) and cognitive knowledge bases (CKB) supported by a collection of contemporary mathematics known as *denotational mathematics* (Wang, 2003, 2007a,b, 2008c, 2009c, 2010a, 2012a,b,c, 2014a,b, 2015a,d,e; Wang & Berwick, 2012, 2013).

A Cognitive Knowledge Base (CKB) represents and manipulates knowledge as a dynamic concept network mimicking human knowledge processing. CKB is demanded in machine learning, knowledge-based systems, cognitive computers, and cognitive robots in general, as well as in the development of the Cognitive Learning Engine (CLE) for cognitive robots in particular. CKB is a central component for machine learning via autonomous knowledge acquisition and

DOI: 10.4018/IJCINI.2015040103

Copyright © 2015, IGI Global. Copying or distributing in print or electronic forms without written permission of IGI Global is prohibited.

manipulation, because the general form of learning is a knowledge acquisition and manipulation process according to the latest studies in cognitive science, brain science, and neuroinformatics (Debenham, 1989; Chang et al., 2006; Brewster et al., 2004; Wang, 2003, 2009a, 2010a, 2011a; Wang & Fariello, 2012).

Conventional knowledge bases are studied in three categories known as the *linguistic* knowledge bases (Crystal, 1987; Brewster et al., 2004; Fellbaum, 1998; Liddy, 2001; Pullman, 1997; Wang, 2014a, 2015c; Wang & Berwick, 2012, 2013), expert knowledge bases (Bender, 1996; Wang, 2007a; Wilson & Keil, 2001), and ontology (Gruber, 1993; Brewster et al., 2004; Leone et al., 2006; Tiberino, et al. 2005; Wang et al., 2011). Typical linguistic knowledge bases are generic lexical databases such as WordNet and ConceptNet (Fellbaum, 1998; Liu & Singh, 2004). Linguistic knowledge bases only provide general materials or dictionaries for applied knowledge bases of individuals and systems. Expert knowledge bases are elicitations of various domain knowledge represented by logical and fuzzy logical rules (Bender, 1996; Surmann, 2000; Zadeh, 1956, 2004; Wang, 2014c; Wang & Berwick, 2012, 2013). However, human knowledge representation and retrieval are more complicated and semantics-centric beyond logical rules. Ontology deals with small-scale knowledge in a certain domain as a hierarchical network of a set of natural words and their semantic relations (Brewster et al., 2004; Cocchiarella, 1996; Gruber, 1993; Sanchez, 2010; Tiberino, et al. 2005; Wang et al., 2011). Ontology represents small-scale acquired knowledge by a static and application-specific model, which cannot be applied as a general knowledge base for machine learning and real-time knowledge manipulations.

According to studies in cognitive science and neurophysiology (Leone et al., 2006; Pojman, 2003; Wang, 2009b, 2012b, 2013a; Wang & Wang, 2006; Wang et al., 2006), the foundations of human knowledge and long-term memory can be represented by an Object-Attribute-Relation (OAR) model based on the synaptic structure of human memory. The OAR model represents the hierarchical and dynamic neural clusters of knowledge retained in memory, which leads to the development of the logical model of cognitive knowledge bases.

Definition 1: The OAR model of knowledge as retained in long-term memory (LTM) is a triple, i.e.:

$OAR \land (O, A, R)$

where O is a finite set of objects identified by unique symbolic names, A is a finite set of attributes for characterizing each object, and R is a set of relations between objects and attributes.

(1)

The OAR model can be illustrated as shown in Figure 1 for formally modelling the structure of human knowledge and its representation in LTM and CKB.

This paper presents a novel cognitive learning engine (CLE) for cognitive robots powered by the cognitive knowledge base (CKB). The structure model of CKB is described in Section 2, which encompasses the formal concept model for itemized knowledge representation and the dynamic concept network model for the entire knowledge base composition. Knowledge manipulations in CKB are embodied by a set of knowledge acquisition and retrieval operations on the structural models of CKB. On the basis of CKB, the CLE architecture and methodologies are formally described in Section 4 for implementing autonomous learning of cognitive robots.

2. THE COGNITIVE KNOWLEDGE BASE FOR ROBOT LEARNING

It is recognized that the generic form of machine learning is a knowledge acquisition and manipulation process mimicking the brain. Therefore, knowledge representation as a dynamic

16 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: <u>www.igi-</u> <u>global.com/article/cognitive-learning-methodologies-for-brain-</u> inspired-cognitive-robotics/137751

Related Content

Constructivist Learning During Software Development

Václav Rajlichand Shaochun Xu (2007). *International Journal of Cognitive Informatics and Natural Intelligence (pp. 78-101).* www.irma-international.org/article/constructivist-learning-during-software-development/1542

IPML: Structuring Distributed Multimedia Presentations in Ambient Intelligent Environments

Jun Huand Loe Feijs (2009). *International Journal of Cognitive Informatics and Natural Intelligence (pp. 37-60).*

www.irma-international.org/article/ipml-structuring-distributed-multimedia-presentations/1586

Stratified Constraint Satissfaction Networks in Synergetic Multi-Agent Simulations of Language Evolution

Alexander Mehler (2007). *Artificial Cognition Systems (pp. 140-175).* www.irma-international.org/chapter/stratified-constraint-satissfaction-networks-synergetic/5247

Interior Design Based on Internet Thinking

Min Nie (2024). International Journal of Cognitive Informatics and Natural Intelligence (pp. 1-15).

www.irma-international.org/article/interior-design-based-on-internet-thinking/349971

A Data Processing Method for Human Motion Estimation to Reduce Network and Sensor Node Loads

Shintaro Imai, Mariko Miyamoto, Mingrui Cai, Yoshikazu Araiand Toshimitsu Inomata (2013). *International Journal of Cognitive Informatics and Natural Intelligence (pp. 58-74).*

www.irma-international.org/article/a-data-processing-method-for-human-motion-estimation-toreduce-network-and-sensor-node-loads/87176