

# Chapter 2

## Processing Technologies for Green Composites Production

**Deepak Verma**

*Graphic Era Hill University, India*

**Garvit Joshi**

*Graphic Era Hill University, India*

**Rajneesh Dabral**

*Graphic Era Hill University, India*

### **ABSTRACT**

*Green composites became a most important and adaptable theme of research. This area/theme not only harness the agricultural wastes such as bagasse fibres, banana fibres, etc. but also provides a new material manufactured from these wastes which are reduced weight, have low cost, and have high mechanical strength. Currently, there are various methods available for the processing or fabrication of green composites. Some of these methods are hand layup method, injection molding method, spray-up method, compression molding, Resin-Transfer Molding (RTM), etc. In this chapter, we are discussing about the fabrication method of green composite and their important parameters. Various properties and characterization of composite materials made by these methods have also been discussed and reported here.*

DOI: 10.4018/978-1-5225-0424-5.ch002

## **INTRODUCTION**

Green composites are a combination of bioplastics and natural fibers, which have arisen as propitious alternatives to conventional polyolefin/glass fiber composites because they offer a wide variety of advantages, such as less expensive, reduced weight, increased flexibility, renewable resource and sound insulation a certain required performance. Natural fibres are subdivided based on their origins, from plants, animals or minerals. All plant fibres are composed of cellulose while animal fibres consist of proteins. Plant fibres include bast (or stem or soft sclerenchyma) fibres found in phloem of dicotyledonous stems, leaf, seed, fruit, wood, and other grass fibres. The use of these fibers in composites has increased due to their relative cost, their ability to recycle and for the fact that they can compete well in terms of strength per weight with other material. Natural fibres can also be considered as naturally occurring composites consisting mainly of cellulose fibrils embedded in lignin matrix they are aligned along the length of the fibre, which render maximum tensile and flexural strengths, in addition to providing rigidity. The reinforcing efficiency of natural fibre is associated with the nature of cellulose and its crystallinity. The main components of natural fibres are cellulose, hemicellulose, pectins, lignin, and waxes. Currently due to increasing interest in eco-friendly, sustainability, eco-efficiency and industrial ecology materials, studies on natural fiber have been actively focused to the area of composite. In an appropriate way, it can be applied as very advantageous composite when an appropriate resin has been selected.

## **METHODS OF FABRICATION**

There are various methods for fabricating composite components to meet specific design or manufacturing challenges. The selection of appropriate method for a particular component, therefore, will depend on the part design, materials and application. Composite fabrication molding processes is used to shape the resin and reinforcement as per design. For an overview of methods used to make mold tools.

### **Open Molding**

Open mold processes include, hand lay-up and spray-up (chopping) (Verma, Deepak, et.al, 2015). In this process, a single-sided mold is used that acts as the form and cosmetic surface of the part. Gel coats is applied to the prepared mold surface and then reinforcements are applied either by hand and then wet-out with resin, or by the spray-up process where resin and chopped fiberglass are sprayed onto the gel coated surface. The additional laminate layer is added to build thickness and strength as

22 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: [www.igi-global.com/chapter/processing-technologies-for-green-composites-production/156901](http://www.igi-global.com/chapter/processing-technologies-for-green-composites-production/156901)

## Related Content

---

### Research Perspectives on Functional Micro and Nano Scale Coatings: New Advances in Nanocomposite Coatings for Severe Applications

Jaime Andrés Pérez Taborda and Elvis O. López (2016). *Research Perspectives on Functional Micro- and Nanoscale Coatings* (pp. 136-169).

[www.irma-international.org/chapter/research-perspectives-on-functional-micro-and-nano-scale-coatings/149758](http://www.irma-international.org/chapter/research-perspectives-on-functional-micro-and-nano-scale-coatings/149758)

### Effect of Process Parameters on MRR and Surface Roughness in ECM of EN 31 Tool Steel Using WPCA

Milan Kumar Das, Tapan Kumar Barman, Kaushik Kumar and Prasanta Sahoo (2017). *International Journal of Materials Forming and Machining Processes* (pp. 45-63).

[www.irma-international.org/article/effect-of-process-parameters-on-mrr-and-surface-roughness-in-ecm-of-en-31-tool-steel-using-wpca/189062](http://www.irma-international.org/article/effect-of-process-parameters-on-mrr-and-surface-roughness-in-ecm-of-en-31-tool-steel-using-wpca/189062)

### The Effect of Molybdenum on the Alloy Properties of the CoCrNiFeMnNb System

Svetlana Kvon, Vitaliy Kulikov, Olegas ernašjus and Yevgeniy Skvortsov (2026). *International Journal of Surface Engineering and Interdisciplinary Materials Science* (pp. 1-20).

[www.irma-international.org/article/the-effect-of-molybdenum-on-the-alloy-properties-of-the-cocrnifemnb-system/404001](http://www.irma-international.org/article/the-effect-of-molybdenum-on-the-alloy-properties-of-the-cocrnifemnb-system/404001)

### Quasi-SMILES for Nano-QSAR Prediction of Toxic Effect of Al<sub>2</sub>O<sub>3</sub> Nanoparticles

Alla P. Toropova, P. Ganga Raju Achary and Andrey A. Toropov (2017). *Materials Science and Engineering: Concepts, Methodologies, Tools, and Applications* (pp. 1624-1635).

[www.irma-international.org/chapter/quasi-smiles-for-nano-qsar-prediction-of-toxic-effect-of-al2o3-nanoparticles/175755](http://www.irma-international.org/chapter/quasi-smiles-for-nano-qsar-prediction-of-toxic-effect-of-al2o3-nanoparticles/175755)

## Enhancing Carbon Quantum Dots Properties: Surface Passivation, Functionalization, Doping, and Aggregation

K. S. Rajniand S Amala Devi (2026). *Carbon Quantum Dots With Tailored Heterogeneous Atoms* (pp. 89-126).

[www.irma-international.org/chapter/enhancing-carbon-quantum-dots-properties/395553](http://www.irma-international.org/chapter/enhancing-carbon-quantum-dots-properties/395553)