

Quantum Computing and Quantum Communication

T

Göran Pulkkis

Arcada University of Applied Sciences, Finland

Kaj J. Grahn

Arcada University of Applied Sciences, Finland

INTRODUCTION

Quantum computing and quantum communication are based on quantum physics. Information is represented by quantum states defined by energy levels of molecules, atoms, and photons. Quantum information technology includes quantum computers, other quantum information processing devices, quantum programming methodologies, and quantum communication applications such as quantum key distribution systems and quantum signatures. Error correction is a necessary quantum information technology property because of high error vulnerability caused by quantum physics characteristics. This article presents state-of-the-art and future perspectives of quantum computing and communication.

BACKGROUND

Feynman's (1982) observation, that a classical computer cannot efficiently simulate the stochastic parallelism of quantum states, started research on using quantum mechanical effects for efficient information processing. Operating principles and implementation possibilities of quantum computing were outlined in Oxford University (Deutsch, 1985).

Bennett and Brassard (1984) proposed a quantum protocol, BB84, for perfectly secret information transfer. Efficient quantum algorithms, for example integer factorization (Shor, 1994) and

unsorted search (Grover, 1996), were proposed. BB84 has been used for distribution of symmetric encryption/decryption keys (Quantum Key Distribution, QKD) in research networks (Elliot, Pearson, & Troxel, 2004; Quellet, 2004; Poppe, Momtchil, & Maurhart, 2008). Commercial QKD technology has been available over 10 years. Quantum digital signatures have been proposed and experimentally verified (Gottesman & Chuang, 2001; Lu & Feng, 2005; Clarke et al., 2012).

Small scale quantum circuit based computers have been built and successfully tested in research laboratories (Vandersypen et al., 2001; Monz et al., 2011). Since 2011 large scale commercial adiabatic quantum computers (Das & Chakrabarti, 2008) are available.

Achievements in quantum computing and quantum communication from 1970 till October 2015 are listed in (Timeline, 2015). Universities engaged in research and education on this topic are for example (qis.mit.edu, 2013; ...from Quantum, 2011; mathQI, 2015; Quantum, 2015a; Quantum, 2015b)

INFORMATION REPRESENTATION WITH QUANTUM STATES

Two quantum states, for which a state transition exists, can represent a bit called a quantum bit or qubit, if the energy level of both states is measurable. However, quantum states are probabilistic. A measured energy level is one of several possi-

DOI: 10.4018/978-1-5225-2255-3.ch671

bilities. Each possible outcome has a probability. The sum of all possible outcome probabilities is of course 1.

The *No Cloning* qubit property is the impossibility to clone an unknown quantum state. However, *Teleportation*, which changes the original qubit state, can transfer also an unknown quantum state.

Mathematical Treatment of Qubits

A qubit representation is a 2-dimensional vector. The orthogonal base vectors $(1,0)^T, (0,1)^T$ in *Dirac notation* $|0\rangle, |1\rangle$ represent binary values 0,1.

A qubit is a concurrent superposition of $|0\rangle, |1\rangle$. A measurement outcome is $|0\rangle$ or $|1\rangle$. In a qubit

$$|\psi\rangle = a \cdot |0\rangle + b \cdot |1\rangle. \quad (1)$$

a, b are complex numbers and

$$\langle \psi | \psi \rangle = (a^*, b^*) \cdot (a, b)^T = a^* \cdot a + b^* \cdot b = |a|^2 + |b|^2 = 1. \quad (2)$$

$\{a^*, b^*\}$ are complex conjugates of $\{a, b\}$. $\{|a|^2, |b|^2\}$ are measurement probabilities of $|0\rangle, |1\rangle$.

Multiple Qubits

A 2 qubit quantum state is a 2^2 component column vector. For

$$|\psi_1\rangle = a \cdot |0\rangle + b \cdot |1\rangle, |\psi_2\rangle = c \cdot |0\rangle + d \cdot |1\rangle \quad (3)$$

the state is

$$|\psi_1 \psi_2\rangle = |\psi_1\rangle \otimes |\psi_2\rangle = a \cdot c \cdot |00\rangle + a \cdot d \cdot |01\rangle + b \cdot c \cdot |10\rangle + b \cdot d \cdot |11\rangle. \quad (4)$$

\otimes is the *tensor product*. $|00\rangle = |0\rangle \otimes |0\rangle = (1, 0, 0, 0)^T$, $|01\rangle = |0\rangle \otimes |1\rangle = (0, 1, 0, 0)^T$, $|10\rangle = |1\rangle \otimes |0\rangle = (0, 0, 1, 0)^T$, and $|11\rangle = |1\rangle \otimes |1\rangle = (0, 0, 0, 1)^T$ are the *base vectors*.

A N qubit quantum state $|\psi_1 \psi_2 \dots \psi_N\rangle$ is a superposition of 2^N base vectors. For a 3 qubit state $|\psi_1 \psi_2 \psi_3\rangle$ the base vectors are $\{|000\rangle, |001\rangle, |010\rangle, |011\rangle, |100\rangle, |101\rangle, |110\rangle, |111\rangle\}$, where $|001\rangle = |0\rangle \otimes |0\rangle \otimes |1\rangle = (0, 1, 0, 0, 0, 0, 0, 0)^T$, etc.

The state $|\psi_1 \psi_2 \dots \psi_N\rangle$ is *entangled* if no $|\psi_1\rangle, |\psi_2\rangle, \dots, |\psi_N\rangle$ exist for which $|\psi_1 \psi_2 \dots \psi_N\rangle = |\psi_1\rangle \otimes |\psi_2\rangle \otimes \dots \otimes |\psi_N\rangle$.

Example: $(1 / \sqrt{2}) \cdot (|00\rangle + |11\rangle)$ is entangled.

Proof: $(a \cdot |0\rangle + b \cdot |1\rangle) \otimes (c \cdot |0\rangle + d \cdot |1\rangle) = a \cdot c \cdot |00\rangle + a \cdot d \cdot |01\rangle + b \cdot c \cdot |10\rangle + b \cdot d \cdot |11\rangle \neq (1 / \sqrt{2}) \cdot (|00\rangle + |11\rangle)$, since one of $\{a, d\}$ must be 0.

Physical Implementation of Qubits

Qubits have been implemented by photon states, ion traps, cavity quantum electrodynamics (QED), nuclear magnetic resonance (NMR), quantum dots, superconducting circuits, and in silicon (Nielsen & Chuang, 2002; Devoret & Schoelkopf, 2013; Veldhorst et al., 2015).

A physical qubit property is decoherence time, during which a qubit state is maintained before collaps caused by interaction with the physical environment.

A qubit implementation in quantum communication is a photon *polarization state* consisting of all propagation planes of the electromagnetic wave of the photon. A random polarization is a superposition of an orthogonal state pair. Orthogonal state pair examples:

- Horizontal and vertical polarization.
- $+45^\circ$ and -45° diagonal polarization.

A photon polarization state is thus a qubit

$$|\psi\rangle = a \cdot |horis\rangle + b \cdot |vert\rangle = c \cdot |+45^\circ\rangle + d \cdot |-45^\circ\rangle \quad (5)$$

a, b, c, d are complex numbers and $|a|^2 + |b|^2 = |c|^2 + |d|^2 = 1$. One state in a chosen pair must be interpreted as $|0\rangle$, the other as $|1\rangle$. Pho-

14 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/quantum-computing-and-quantum-communication/184467

Related Content

Comprehensive Survey on Metal Artifact Reduction Methods in Computed Tomography Images

Shrinivas D. Desai and Linganagouda Kulkarni (2015). *International Journal of Rough Sets and Data Analysis* (pp. 92-114).

www.irma-international.org/article/comprehensive-survey-on-metal-artifact-reduction-methods-in-computed-tomography-images/133535

Novel Methods to Design Low-Complexity Digital Finite Impulse Response (FIR) Filters

David Ernesto Troncoso Romero and Gordana Jovanovic Dolecek (2018). *Encyclopedia of Information Science and Technology, Fourth Edition* (pp. 6234-6244).

www.irma-international.org/chapter/novel-methods-to-design-low-complexity-digital-finite-impulse-response-fir-filters/184321

Securing Stored Biometric Template Using Cryptographic Algorithm

Manmohan Lakhera and Manmohan Singh Rauthan (2018). *International Journal of Rough Sets and Data Analysis* (pp. 48-60).

www.irma-international.org/article/securing-stored-biometric-template-using-cryptographic-algorithm/214968

The Systems View of Information Systems from Professor Steven Alter

David Paradise (2008). *International Journal of Information Technologies and Systems Approach* (pp. 91-98).

www.irma-international.org/article/systems-view-information-systems-professor/2541

Design and Implementation of Home Video Surveillance Systems Based on IoT Location Service

Wei Xu and Yujin Zhai (2023). *International Journal of Information Technologies and Systems Approach* (pp. 1-18).

www.irma-international.org/article/design-and-implementation-of-home-video-surveillance-systems-based-on-iot-location-service/318658