

Chapter 5

Hub Location Allocation Problems and Solution Algorithms

Peiman A. Sarvari

Istanbul Technical University, Turkey

Fatma Betül Yeni

Istanbul Technical University, Turkey

Emre Çevikcan

Istanbul Technical University, Turkey

ABSTRACT

The Hub Location-Allocation Problem is one of the most important topics in industrial engineering and operations research, which aims to find a form of distribution strategy for goods, services, and information. There are plenty of applications for hub location problem, such as Transportation Management, Urban Management, locating service centers, Instrumentation Engineering, design of sensor networks, Computer Engineering, design of computer networks, Communication Networks Design, Power Engineering, localization of repair centers, maintenance and monitoring power lines, and Design of Manufacturing Systems. In order to define the hub location problem, the present chapter offers two different metaheuristic algorithms, namely Particle Swarm Optimization or PSO and Differential Evolution. The presented algorithms, then, are applied to one of the hub location problems. Finally, the performances of the given algorithms are compared in term of benchmarking.

INTRODUCTION

In this chapter, we discuss some services, such as database transaction, movements of people, commodities, information or unfinished parts that take place between an origin-destination pair of nodes. Such pairs of nodes can be found in the domain of a manufacturing site or spread along continents, as each origin-destination pair needs a service different from the other pairs.

DOI: 10.4018/978-1-5225-2944-6.ch005

Hub location problem is one of the most important topics of location problems. The facility location problem, also known as location analysis or k-center problem is a branch of operations research and computational geometry. Facility location problems try to reduce the costs of operations considering some set of constraints and relevant demands with locating different ranges of facilities. Making decisions for facility location are critically challenging regarding strategic planning for all types of business entities. Property acquisition and establishment are naturally costly so that one can consider facility location and relocation operations as long-term investments. Decision makers are challenging with different geographical, demographical and trending factors for selecting profitable sites. Thus, selection of robust facility locations is an important task, as far as future events are uncertain and unpredictable.

Hub location problem is an extension of the classical facility location problems. Hubs are facilities that operate as consolidating, connecting, and switching points for flows between the stipulated origins and destinations (Farahani et al., 2013). Hubs are also defined as special facilities that serve as switching, transshipping and sorting points in many-to-many distribution systems. The hub location problem is concerned with locating hub facilities and allocating demand nodes to hubs in order to route the traffic between origin–destination pairs (Alumur & Kara, 2008). Many applications are available for the hub location problem, and this section is primarily dedicated to introducing this problem to readers.

In this chapter, we have tried to fit what moves between an origin-destination pair of nodes, like information, people and commodities into the concept of HLP. Basically, each different pair of origin-destination node has to be serviced exclusively. For instance, people traveling from i to j are not interchangeable with those traveling from j to i . In order to have a fully connected network (a network in which all nodes are connected) with N nodes, in which each node can be either an origin or a destination, the number of pairs (i - j pairs which are different from j - i pairs) should be $N(N-1)$. Fig.1 illustrates a network composed of nodes and connections.

Assuming that we have different traffic services in this network and that each vehicle can service five origin-destination pairs every day, with 18 vehicles, we will be able to service ten nodes every day. If we set one of the nodes as a hub node and connect it to all the other nodes, which are introduced as spokes, we will have $2(n-1)$ connections to service all origin-destination node pairs. This network is presented in Figure 2 (Daskin, 1995).

Assume, if there are different traffic services, and if each vehicle can provide service for origin-destination pairs every day, with 18 vehicles, we will be able to service 46 nodes every day. Thus, with fixed traffic resources, we can service more cities with a hub network than with a completely connected network. Multi-hub network is another type of hub and spoke network that is a formation of two or several hubs and spoke networks in which all hubs are fully connected to each other.

This chapter is organized as follows. Section two, presents a technical and comprehensive literature review. In section three, the taxonomy of HLP is given, and section four, introduces some of the basic and fundamental models developed for the hub problem. In section five, an application with two metaheuristic solution algorithms is suggested together with its application in terms of performance evaluation of the proposed metaheuristics, and finally, the conclusion of the study is given in section six.

LITERATURE REVIEW

The hub location problem has been studied for many years. With a glance at the related literature, one can find out the importance of the issue for the researchers. A panoramic view of its applications, research

28 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/hub-location-allocation-problems-and-solution-algorithms/191772

Related Content

Multi-Modal Assembly-Support System for Cellular Manufacturing

Feng Duan, Jeffrey Too Chuan Tan, Ryu Kato, Chi Zhuand Tamio Arai (2013). *Industrial Engineering: Concepts, Methodologies, Tools, and Applications* (pp. 559-576).

www.irma-international.org/chapter/multi-modal-assembly-support-system/69303

A Fuzzy Inventory Model for Weibull Deteriorating Items with Price-Dependent Demand and Shortages under Permissible Delay in Payment

Chandra K. Jaggi, Sarla Pareek, Anuj Sharmaand Nidhi (2012). *International Journal of Applied Industrial Engineering* (pp. 53-79).

www.irma-international.org/article/a-fuzzy-inventory-model-for-weibull-deteriorating-items-with-price-dependent-demand-and-shortages-under-permissible-delay-in-payment/93015

Rescheduling Activities in Face of Disruption in House Hold Goods Manufacturing Supply Chain

K. V.N.V.N. Raoand G. Ranga Janardhana (2016). *International Journal of Applied Industrial Engineering* (pp. 47-65).

www.irma-international.org/article/rescheduling-activities-in-face-of-disruption-in-house-hold-goods-manufacturing-supply-chain/168606

Justification of e-Governance in Education: A Multicriteria Decision Approach

Debendra Kumar Mahalik (2018). *International Journal of Applied Industrial Engineering* (pp. 30-40).

www.irma-international.org/article/justification-of-e-governance-in-education/209379

“Lex Lata” and “de lege Ferenda” for the R&D Law of Turkey

Serdar Türkeli (2013). *Industrial Dynamics, Innovation Policy, and Economic Growth through Technological Advancements* (pp. 307-331).

www.irma-international.org/chapter/lex-lata-lege-ferenda-law/68366