

Chapter 85

Enhanced Breast Cancer Diagnosis System Using Fuzzy Clustering Means Approach in Digital Mammography

Mohammed A. Osman
Helwan University, Egypt

Ayman E. Khedr
Helwan University, Egypt

Ashraf Darwish
Helwan University, Egypt

Atef Z. Ghalwash
Helwan University, Egypt

Aboul Ella Hassanien
Cairo University, Egypt

ABSTRACT

Breast cancer or malignant breast neoplasm is the most common type of cancer in women. Researchers are not sure of the exact cause of breast cancer. If the cancer can be detected early, the options of treatment and the chances of total recovery will increase. Computer Aided Diagnostic (CAD) systems can help the researchers and specialists in detecting the abnormalities early. The main goal of computerized breast cancer detection in digital mammography is to identify the presence of abnormalities such as mass lesions and Micro calcification Clusters (MCCs). Early detection and diagnosis of breast cancer represent the key for breast cancer control and can increase the success of treatment. This chapter investigates a new CAD system for the diagnosis process of benign and malignant breast tumors from digital mammography. X-ray mammograms are considered the most effective and reliable method in early detection of breast cancer. In this chapter, the breast tumor is segmented from medical image using Fuzzy Clustering Means (FCM) and the features for mammogram images are extracted. The results of this work showed that these features are used to train the classifier to classify tumors. The effectiveness and performance of this work is examined using classification accuracy, sensitivity and specificity and the practical part of the proposed system distinguishes tumors with high accuracy.

DOI: 10.4018/978-1-5225-5204-8.ch085

INTRODUCTION AND RELATED WORK

Breast cancer is one of the major causes of death among women, especially in developed countries. The early detection of this disease can reduce the rate of death in women. CAD can help the radiologist in detecting the abnormalities in an efficient way. The mammograms can be used in the detection of breast cancer according to the World Health Organization's International Agency for Research on Cancer (Gaber et al., 2015). Mammographic images are X-ray images of breast region (Verma & Zhang, 2007; Hassanien et al., 2003, Hassanien and Tai-hoon, 2012). Computer-assisted breast tumor classification which is based on the image analysis techniques provides more useful information. The conventional method for the breast tumor classification consists of three steps process. The first step involves the segmentation of breast tumor from the image. The second step is feature extraction and the third one is the classification process using a classifier. The goal of this study is to increase the diagnostic accuracy of image processing for optimum classification between benign and malignant abnormalities in digital mammograms.

Image enhancement module is a vital part as a preprocessing for any image processing technique. Image processing techniques like morphological operations and threshold techniques are applied in this study to enhance the mammogram images for the computerized detection of breast cancer.

Segmentation of medical images is an important step (Ali et al., 2015). This study employs a fuzzy segmentation algorithm for segmenting the mammogram images. Texture based features are extracted from the segmented images. These features are fed to the classifier for classification process. The binary classification accuracy of the developed system is measured using the Receiver Operating Characteristic (ROC) analysis with performance measures such as sensitivity, specificity and accuracy.

This chapter proposes a new technique based on fuzzy algorithm and ANN to diagnosis breast cancer from digital mammograms.

Research in areas of Computer-Aided Diagnostic (CAD) systems developed within a decade. In early studies investigators outlined many approaches and limitations of Computer-Aided Diagnosis (CAD) in mammography. Winsberg, Elkin, Macy, Brodaz, and Weymouth (1967) described a method that compares density between left and right breasts. An algorithm was developed by Kimme, O'Loughlin, and Sklansky (1975) to detect abnormal breast regions. They calculated seven features for breast images and compared them corresponding to regions of the left and right breasts. Smith, Wagner, Guenther, and Solmon (1977) introduced a measure to distinguish between malignant and benign cancer. Hand, Semmlow, Ackerman, and Alcorn (1979) constructed fourteen parameters of three basic textural features, intensity, roughness and directionality to detect malignant areas on xeromammograms. They achieved sensitivity of 87%. Now recent studies characterized by greater use of image processing, feature analysis and artificial intelligence methods. Varela, Tahoces, Mendez, Souto and Vidal (2007) applied iris filter and means of adaptive threshold to segment images and extract feature to train neural network classifier. System results sensitivity 88% and 94% at 1.02 false positives per image. Kumar and MONI (2010) applied Fuzzy Clustering Means (FCM) to extract tumor from Computed Tomography (CT), textural information obtained using curvelet transform. Consequently after classification 94.3% accuracy obtained. This chapter presents a new method for breast cancer early detection.

The remainder of this chapter is organized as follows. Section 2 presents the proposed model and its framework. In section 3, the research methodology and implementation of this chapter is presented and performance evaluation and analysis of the results are presented. Section 4 concludes this chapter and future work is presented.

15 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/enhanced-breast-cancer-diagnosis-system-using-fuzzy-clustering-means-approach-in-digital-mammography/197035

Related Content

Human Activity Recognition Using Gait Pattern

Jay Prakash Gupta, Nishant Singh, Pushkar Dixit, Vijay Bhaskar Semwal and Shiv Ram Dubey (2013). *International Journal of Computer Vision and Image Processing* (pp. 31-53).

www.irma-international.org/article/human-activity-recognition-using-gait-pattern/95969

A Context Based Tracking for Similar and Deformable Objects

Bhavana Kaushik, Manoj Kumar, Charul Bhatnagar and Anand Singh Jalal (2018). *International Journal of Computer Vision and Image Processing* (pp. 1-15).

www.irma-international.org/article/a-context-based-tracking-for-similar-and-deformable-objects/214070

A Survey on Local Textural Patterns for Facial Feature Extraction

Uma Maheswari V, Golla Vara Prasad and S Viswanadha Raju (2018). *International Journal of Computer Vision and Image Processing* (pp. 1-26).

www.irma-international.org/article/a-survey-on-local-textural-patterns-for-facial-feature-extraction/208175

Content Based Image Retrieval Using Active-Nets

David García Pérez, Antonio Mosquera, Stefano Berretti and Alberto Del Bimbo (2009). *Artificial Intelligence for Maximizing Content Based Image Retrieval* (pp. 85-114).

www.irma-international.org/chapter/content-based-image-retrieval-using/4153

Biologically Inspired Components in Embedded Vision Systems

Li-Minn Ang, Kah Phooi Seng and Christopher Wing Hong Ngau (2018). *Computer Vision: Concepts, Methodologies, Tools, and Applications* (pp. 458-493).

www.irma-international.org/chapter/biologically-inspired-components-in-embedded-vision-systems/196966