Chapter 88 Distributed Methods for Multi–Sink Wireless Sensor Networks Formation

Miriam A. Carlos-Mancilla CINVESTAV Unidad Guadalajara, Mexico

Ernesto Lopez-Mellado CINVESTAV Unidad Guadalajara, Mexico

Mario Siller CINVESTAV Unidad Guadalajara, Mexico

ABSTRACT

Recent application development in the wireless sensor networks (WSNs) area makes arise problems, regarding data aggregation and effective methods to collect data. For addressing these problems, effective procedures are required. A multi-sink sensor network application has been characterized by many-to-many communication, where multiple sources report their data to multiple sinks. This chapter presents recent techniques for distributed multi-sink environments. The reviewed proposals are classified according to the purpose of the application, such as routing, monitoring of a specific target, data aggregation applications, and others. Finally, the authors present a discussion on the analyzed works.

INTRODUCTION

A Wireless Sensor Network (WSN) is composed of a set of hundreds of devices deployed in a common area, which are connected among them. Each device has the same capabilities; it is able to collect information from the surrounding environment through one or more sensors, process this information in a local manner. Data collection is usually made by a sink node or base station. A WSN can be used to control multiple tasks in one environment; the sensors require of data sensed from multiple sources by delivering information to multiple sinks at the same time.

DOI: 10.4018/978-1-5225-7598-6.ch088

Distributed Methods for Multi-Sink Wireless Sensor Networks Formation

There are a wide variety of current research problems in this area, such as tracking, surveillance, military applications, building automation, disaster management, and agriculture, among others. The applications are designed to obtain precise information from the environment regardless of the human presence. Radio communication, processing, transmission/reception generally are the main cause of power consumption. A multi-sink approach is becoming an efficient scheme to reduce the energy consumption in the whole network, either in a centralized or distributed application. In this paper, distributed techniques are presented and analysed.

The analysis is focused on the used strategies in a multiple sink environment, whether the nodes are static or mobile and how applications can be improved by mixing more than one strategy; the objective of the application such as event detection, following a target, finding the best route, collecting and data aggregation, among others. The survey covers recent and traditional works and presents a discussion of their advantages and drawbacks. A simple and operational distributed algorithm that performs network formation and data collection using a multi-sink environment is presented.

This article is organized as follows: the next section presents the generalities and features of WSNs. The third section presents a classification of distributed approaches based on multi-sink environments; the fourth section describes the classification of the related works and discusses their proposals. The fifth section focuses on the simple and operational proposal of a distributed and multi-sink protocol for a WSN; finally, the last section presents the concluding remarks, which drive further research in the area.

BACKGROUND

Wireless Sensor Networks

Wireless Sensor networks with a single sink node have constraints; one of them is presented during the data collection, where bottleneck (Hochbaum & Shmoys, 1986) and hotspot problems (Sungjin & Kim, 2006) can arise. Another limiting factor emerges when the purpose of the application is finding a target and the sink is far away from it; in this case, the routing can require great expenses of energy. Another drawbacks are presented when the sink require of responses in a short period of time and the routing is not efficient, when the sink node is not available, or there is a high demand for transmissions and one sink is not enough.

Multi-sink platforms have arisen as response to this kind of problems; a multi-sink platform provides redundancy, avoids problems in the data collections and increases the efficiency of the application. A set of sinks can be strategically or randomly distributed in the coverage area to collect and process the information from the environment. The sink or sinks can be static or mobile according to the available resources of the application.

Once the topology strategy is specified, the information can be collected following a distributed o centralized policy via multi-hop mode. In this article, we focus on the distributed strategies. *Distributed techniques* allow to the nodes take their own decisions in a locally way and dispense the information to a limited set of neighbours nodes within a scope area, which provide energy savings and spreading the information in a uniform manner to avoid the overhearing or hot spot problems. The flexibility of distributed systems enables targeting random environments without complications during the information collection.

14 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: <u>www.igi-global.com/chapter/distributed-methods-for-multi-sink-wireless-</u> <u>sensor-networks-formation/214693</u>

Related Content

Personalization and Customer Satisfaction in Mobile Commerce

HY Sonya Hsuand Songpol Kulviwat (2009). *Mobile Computing: Concepts, Methodologies, Tools, and Applications (pp. 1886-1892).*

www.irma-international.org/chapter/personalization-customer-satisfaction-mobile-commerce/26634

Trust Modeling and Computational Trust: Digitalizing Trust

(2014). *Trust Management in Mobile Environments: Autonomic and Usable Models (pp. 13-30).* www.irma-international.org/chapter/trust-modeling-and-computational-trust/86916

An Overview of the Capabilities and Limitations of Smartphone Sensors

Avi Klausner, Ari Trachtenberg, David Starobinskiand Mark Horenstein (2013). International Journal of Handheld Computing Research (pp. 69-80).

www.irma-international.org/article/an-overview-of-the-capabilities-and-limitations-of-smartphone-sensors/79960

An Immune Systems Approach for Classifying Mobile Phone Usage

Hanny Yulius Limanto, Tay Joc Cingand Andrew Watkins (2009). *Mobile Computing: Concepts, Methodologies, Tools, and Applications (pp. 2896-2907).* www.irma-international.org/chapter/immune-systems-approach-classifying-mobile/26700

A Framework for the Quality Evaluation of B2C M-Commerce Services

John Garofalakis, Antonia Stefaniand Vassilios Stefanis (2011). *International Journal of Handheld Computing Research (pp. 73-91).*

www.irma-international.org/article/framework-quality-evaluation-b2c-commerce/55892