

## Chapter 3.11

# Device Localization in Ubiquitous Computing Environments

**Rui Huang**

*University of Texas at Arlington, USA*

**Gergely V. Záruba**

*University of Texas at Arlington, USA*

**Sajal Das**

*University of Texas at Arlington, USA*

### ABSTRACT

In this chapter, we will study the localization problem in ubiquitous computing environments. In general, localization refers to the problem of obtaining (semi-) accurate physical location of the devices in a dynamic environment in which only a small subset of the devices know their exact location. Using localization techniques, other devices can indirectly derive their own location by means of some measurement data such as distance and angle to their neighbors. Localization is now regarded as an enabling technology for ubiquitous computing environments because it can substantially increase the performance of other fundamental tasks such as routing, energy

conservation, and network security. Localization is also a difficult problem because it is computationally intractable. Furthermore, it has to be implemented in a highly dynamic and distributed environment in which measurement data is often subject to noise. In this chapter, we will give an overview of localization in terms of its common applications, its hardware capacities, its algorithms, and its computational complexity.

### INTRODUCTION

In a ubiquitous computing environment, devices are often connected to one another on the fly to form an infrastructure-less network that is fre-

quently referred to as a mobile ad hoc network (MANET). Since MANET serves as an abstract model that can be seen as a superset of diverse sub-areas such as sensor networks, mesh networks or an enabler for pervasive computing, it has attracted significant research interests in the past several years. A major advantage of MANETs over regular wired or wireless networks is their infrastructure-less nature, as MANETs can potentially be deployed more rapidly and less expensively than infrastructure-based networks. However, the lack of an underlying explicit infrastructure also becomes a major disadvantage in adapting MANETs to a wider array of applications, since existing network algorithms and protocols are often not “plug-in” solutions for such dynamic networks. New algorithms need to be designed for fundamental network tasks such as addressing, topology discovery, and routing.

Location discovery is emerging as one of the more important tasks as it has been observed that (semi-) accurate location information can greatly improve the performance of other MANET tasks such as routing, energy conservation, or maintaining network security. For instance, algorithms such as location aided routing (LAR) (Ko, 2000), GRID (Liao, 2001), and GOAFR+ (Kuhn, 2003) rely on location information to provide more stable routes during unicast route discovery. The availability of location information is also required for geocast (multicast based on geographic information (Jiang, 2002)) algorithms such as location-based multicast (LBM) (Ko, 1999), GeoGRID (Liao, 2000) and position-based multicast (PBM) (Mauve, 2003). To minimize power consumption, the geographical adaptive fidelity (GAF) algorithm (Xu, 2001) uses location information to effectively modify the network density by turning off certain nodes at particular instances. Furthermore, in (Hu, 2003), the authors have shown that wormhole attacks can be effectively prevented when location information is available. As more algorithms are being proposed to exploit location information of devices in

ubiquitous networks, it is clear that obtaining such information efficiently and accurately becomes of great importance.

A direct way of obtaining location information is to install global positioning system (GPS) receivers on devices. However, this is currently impractical as GPS receivers are still relatively expensive, power-hungry, and require clear line of sight (i.e., making indoor usage impossible) to several earth-bound satellites. In ubiquitous environments (e.g., sensor networks), devices are imagined as small as possible and operating on a very restricted power source, thus, it may not be feasible to install GPS receivers onto all sensor nodes. *Localization* in MANET refers to the problem of finding the locations of those non-GPS enabled nodes based on limited information such as the locations of some known *beacons* (also referred to as *anchors*) and measurements such as *ranges* or *angles* among the neighbors. In this chapter, we will study why localization is important and how it can be accomplished within the ubiquitous computing environment.

## BACKGROUND

The localization problem is hard for a number of reasons:

- 1 **Geometric limitations:** To pinpoint its exact location in 2-D, a node needs to know the locations and its distances to at least three beacons. Alternatively, nodes could calculate their own location based on a distance and an (absolute) angle measurement from one beacon. However, even if obtaining such measurements were possible and the measurements were exact, guaranteeing that the right number of beacons surround each node is often impossible since MANETs may be randomly deployed and that in general only a small percentage of nodes are indeed beacons. Thus, localization algorithms often

25 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

[www.igi-global.com/chapter/device-localization-ubiquitous-computing-environments/22308](http://www.igi-global.com/chapter/device-localization-ubiquitous-computing-environments/22308)

## Related Content

---

### The Impact of Information and Communication Technology Factors on the User Intention to Participate in the Sharing Economy

Pinghao Ye, Liqiong Liu and Joseph Tan (2022). *International Journal of Technology and Human Interaction* (pp. 1-24).

[www.irma-international.org/article/the-impact-of-information-and-communication-technology-factors-on-the-user-intention-to-participate-in-the-sharing-economy/299076](http://www.irma-international.org/article/the-impact-of-information-and-communication-technology-factors-on-the-user-intention-to-participate-in-the-sharing-economy/299076)

### Users' Acceptance of Artificial Intelligence-Based Chatbots: An Empirical Study

Mahendar Goli, Anoop Kumar Sahu, Surajit Bag and Pavitra Dhamija (2023). *International Journal of Technology and Human Interaction* (pp. 1-18).

[www.irma-international.org/article/users-acceptance-of-artificial-intelligence-based-chatbots/318481](http://www.irma-international.org/article/users-acceptance-of-artificial-intelligence-based-chatbots/318481)

### A Risk Based View of Influential Factors in IT Outsourcing Relationship for Large Multinational Companies: A Service Buyer Perspective

Georg Hodosi, Lazar Rusu and Seungho Choo (2012). *International Journal of Social and Organizational Dynamics in IT* (pp. 29-47).

[www.irma-international.org/article/risk-based-view-influential-factors/72888](http://www.irma-international.org/article/risk-based-view-influential-factors/72888)

### Revisiting Our Quantum World: Applications to Education, Health, and Security

Lester Ingber (2021). *Technological Breakthroughs and Future Business Opportunities in Education, Health, and Outer Space* (pp. 96-111).

[www.irma-international.org/chapter/revisiting-our-quantum-world/276255](http://www.irma-international.org/chapter/revisiting-our-quantum-world/276255)

### Cyberterrorism and Its Impact on Contemporary Conflicts and Society

Emilia Alaverdov, Sopo Chkopoia and Zurabi Tchabashvili (2023). *Analyzing New Forms of Social Disorders in Modern Virtual Environments* (pp. 170-192).

[www.irma-international.org/chapter/cyberterrorism-and-its-impact-on-contemporary-conflicts-and-society/328109](http://www.irma-international.org/chapter/cyberterrorism-and-its-impact-on-contemporary-conflicts-and-society/328109)