

Chapter 45

Novel Cryptography Technique via Chaos Synchronization of Fractional- Order Derivative Systems

Alain Giresse Tene

University of Dschang, Cameroon

Timoleon Crépin Kofane

University of Yaounde I, Cameroon

ABSTRACT

Synchronization of fractional-order-derivative systems for cryptography purpose is still exploratory and despite an increase in cryptography research, several challenges remain in designing a powerful cryptosystem. This chapter addresses the problem of synchronization of fractional-order-derivative chaotic systems using random numbers generator for a novel technique to key distribution in cryptography. However, there is evidence that researchers have approached the problem using integer order derivative chaotic systems. Consequently, the aim of the chapter lies in coding and decoding a text via chaos synchronization of fractional-order derivative, the performance analysis and the key establishment scheme following an application on a text encryption using the chaotic Mathieu-Van Der Pol fractional system. In order to improve the level of the key security, the Fibonacci Q-matrix is used in the key generation process and the initial condition; the order of the derivative of the responder system secretly shared between the responder and the receiver are also involved. It followed from this study that compared to the existing cryptography techniques, this proposed method is found to be very efficient due to the fact that, it improves the key security.

DOI: 10.4018/978-1-7998-5351-0.ch045

INTRODUCTION

Nowadays, developing new strategies to protect sensitive information from eavesdropping has attracted significant attention in the worldwide communication networks. That is, wide investigations have been made to implement an effective cryptosystem to ensure information encryption and decryption. These include the algorithmic key based encryption systems which usually consider a digital stream and convolute it with a given binary pattern using as the key. This encryption method can be denoted as the Vernam Cipher method (Bloisi and Iocchi 2007). In this method, the message is transformed to a binary string (a sequence of 0 and 1), and the key is a randomly generated sequence of 0 and 1 having the same length as the message. The encryption is done by adding the key to the message modulo 2 bit by bit, this includes the symmetric key encryption such as the Data Encryption Standard (DES) cryptosystem (Standard 1977), the Advanced Encryption Standard (AES) (Standard 2001) cryptosystems, etc. Even though this encryption method has been used for long times and is still used today, it presents some lacks in the key security and the key distribution. The drawback of this encryption technique comes from the fact that, it is easily breakable even if the key can be used only one time (one time-pad key). However, this drawback has been avoided by developing other software cryptosystems that use asymmetric algorithms key distribution which is called a public key cryptography such as the Rivest Shamir Adleman (RSA), the Elliptic Curve Cryptography (ECC) cryptosystems just to name a few (Bleichenbacher 1998, Habib 2009). Such cryptosystems usually use several computational resources and compare them with their counterparts but they are not generally used to encrypt bulk data stream and are computationally hard. Although this encryption technique is not yet broken, further investigations have been made to develop another encryption method that is based on chaos. Chaos theory has simulated increasing attentions of scientists since the work of Lorenz (1963). Due to their random-like behavior, their unpredictability character and their high degree of nonlinearity, chaotic signals have been proven to be very efficient for information security then, in the recent few decades, chaos based cryptosystems which consists of masking an information to be transmitted through a chaotic signal have received a great deal of interest. Here one denotes the chaos masking (CMA) which consists of masking the plaintext through a chaotic signal, the chaos shift keying (CSK), the chaos modulation (CMO), etc (Annovazzi-Lodi *et al.* 2005, Dedieu *et al.* 1993, Tang *et al.* 2002). However, particular attentions have been given to the encryption technique based on chaos synchronization between distant elements in large networks in order to improve the effectiveness of information security. This encryption technique has been developed by several authors (Alvarez 2006) and has even been implemented in the real experiment. These authors demonstrated that a cryptosystem based on this encryption is highly efficient, although it is difficult to synchronize two chaotic systems. Therefore, this method consists of generating an encryption key by synchronizing two chaotic signals (driver and responder systems). Thus, the aim of this chapter is to develop new strategy of key encryption based on chaos synchronization of two chaotic systems with fractional order derivative in order to improve the information security.

The main motivation behind such an idea includes the fact that, the fractional order derivative chaotic system is geometrically complex and its high nonlinearity degree makes such a system an efficient tool to encrypt message. Furthermore, the order of the derivative might be used as the secret key as well as other parameters of the system enhancing the effectiveness of the encryption method. In addition, it was shown by Tene & Kofane (2017) that the fractional order of the derivative can induce quick synchronization of chaotic systems which can highly improve the encryption and decryption speed. Such encryption

32 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/novel-cryptography-technique-via-chaos-synchronization-of-fractional-order-derivative-systems/268634

Related Content

Empirical Study on the Impact of Select Green HRM Dimensions on Green Innovation Culture

Vasuki Boominathan, J. Tamil Selvi, C. Dhilipan, M. Tamil Arasu, B. Elamuruganand Palanivel Rathinasabapathi Velmurugan (2024). *Data-Driven Intelligent Business Sustainability* (pp. 405-417). www.irma-international.org/chapter/empirical-study-on-the-impact-of-select-green-hrm-dimensions-on-green-innovation-culture/334757

Attacks and Countermeasures

Mukta Sharma (2021). *Research Anthology on Blockchain Technology in Business, Healthcare, Education, and Government* (pp. 1446-1467). www.irma-international.org/chapter/attacks-and-countermeasures/268670

A Dynamic Approach to Estimate Receiving Bandwidth for WebRTC

Razib Iqbal, Shervin Shirmohammadiand Rasha Atwah (2016). *International Journal of Multimedia Data Engineering and Management* (pp. 17-33). www.irma-international.org/article/a-dynamic-approach-to-estimate-receiving-bandwidth-for-webrtc/158109

Charity Management Using Blockchain Technology

R. Parkavi, S. Vigneshwaran, N. Sambathand P. Sanjai (2023). *Handbook of Research on Data Science and Cybersecurity Innovations in Industry 4.0 Technologies* (pp. 291-314). www.irma-international.org/chapter/charity-management-using-blockchain-technology/331016

Human Research Protections Basics for New Investigators

Rochelle Siapno, Laura Smithand Robin Throne (2025). *IRB, Human Research Protections, and Data Ethics for Researchers* (pp. 1-20). www.irma-international.org/chapter/human-research-protections-basics-for-new-investigators/362817