

IDEA GROUP PUBLISHING

701 E. Chocolate Avenue, Suite 200, Hershey PA 17033-1240, USA **ITB10414** Tel: 717/533-8845; Fax 717/533-8661; URL-http://www.idea-group.com

Chapter III

Generalized Extremal Optimization: A New Meta-Heuristic Inspired by a Model of Natural Evolution

Fabiano Luis de Sousa, INPE, Brazil

Fernando Manuel Ramos, INPE, Brazil

Roberto Luiz Galski, INPE, Brazil

Issamu Muraoka, INPE, Brazil

ABSTRACT

In this chapter a recently proposed meta-heuristic devised to be used in complex optimization problems is presented. Called Generalized Extremal Optimization (GEO), it was inspired by a simple co-evolutionary model, developed to show the emergence of self-organized criticality in ecosystems. The algorithm is of easy implementation, does not make use of derivatives and can be applied to unconstrained or constrained problems, non-convex or even disjoint design spaces, with any combination of continuous, discrete or integer variables. It is a global search meta-heuristic, like the Genetic Algorithm (GA) and the Simulated Annealing (SA), but with the advantage of having only one free parameter to adjust. The GEO has been shown to be competitive to the GA and the SA in tackling complex design spaces and a useful tool in real design problems. Here the algorithm is described, including a step-by-step implementation to a simple numerical example, its main characteristics highlighted, and its efficacy as a design tool illustrated with an application to satellite thermal design.

This chapter appears in the book, *Recent Developments in Biologically Inspired Computing*, edited by Leandro N. de Castro and Fernando J. Von Zuben. Copyright © 2005, Idea Group Inc. Copying or distributing in print or electronic forms without written permission of Idea Group Inc. is prohibited.

INTRODUCTION

Many numeric techniques have been developed to address optimization problems in science and engineering (Glover & Kochenberg, 2003; Pardalos & Romeijn, 2002; Vanderplaats, 1998). The existence of many types of optimization methods is the consequence of a practical and theoretic observation: The efficiency of a given optimization algorithm is dependent on the kind of problem that is being tackled. In fact, it can be said that there is not a technique that is better than all others for all problems, but that there exists those that are more appropriate for a given class of problems (Vanderplaats, 1998; Wolpert & Macready, 1995). Traditionally, the most used methods are based on local search algorithms, frequently using the gradient of the objective function as a "guide" to the search of the optimum in the design space.

Gradient-based methods are very efficient when applied to problems where the design space is convex, with continuous design variables and when there are no severe non-linearities in the objective function or its constraints. However, many engineering problems have complex design spaces, which may be non-convex, disjoint, have severe non-linearities in the objective function and its constraints or contain a mix of continuous, discrete and integer design variables (Eldred, 1998). These characteristics may decrease considerably the efficiency of the gradient-based methods, making them converge to sub-optimal designs.

A common feature of a complex design space is the existence of multiple local optima (Eldred, 1998). In such case, a gradient-based method would converge to the nearest local minimum from where the search was started. Hence, in a practical case where the design space is not known *a priori*, if a gradient-based or any other local search algorithm is used, global search strategies must be implemented so that the probability of being trapped in a local minimum is diminished. A more general approach is to use a global search algorithm. Global optimization algorithms try to identify the global optima in the design space, using either a deterministic or a heuristic approach. Theoretically, the deterministic approach would guarantee that at least one global optimum can be found, but it has usually prohibitive computational costs for large problems or complex design spaces. On the other hand, heuristic strategies that use a stochastic component to perform the global search can yield a high probability of reaching the global solution, or solutions, with acceptable computational costs for problems considered too hard to address with global deterministic strategies (Pintér, 2002).

One class of global optimization algorithms that has been receiving great attention lately is the algorithms based on natural phenomena. The motivation behind this approach may be the observation that natural processes are frequently self-optimized. Whether to save energy, reduce waste or produce fitter organisms, nature developed robust, self-regulating mechanisms that tend to produce simple and efficient solutions. Algorithms based on the evolution of species (Davis et al., 1999), on the annealing of metals (Kirkpatrick et al., 1983), on the functioning of the brain (Freeman & Skapura, 1991), on the immune system (Castro & Timmis, 2002) and even on the social behavior of ants (Bonabeau et al., 2000) have been proposed and used in science and engineering to address many kinds of problems. Of these, maybe the most commonly used are Simulated Annealing (SA) (Kirkpatrick et al., 1983), Genetic Algorithms (GAs) (Goldberg, 1989) or variations of them.

Copyright © 2005, Idea Group Inc. Copying or distributing in print or electronic forms without written permission of Idea Group Inc. is prohibited.

18 more pages are available in the full version of this document, which may be purchased using the "Add to Cart"

button on the publisher's webpage: www.igi-

global.com/chapter/generalized-external-optimization/28323

Related Content

Swarm Intelligence for Biometric Feature Optimization

Santosh Kumar, Deepanwita Dattaand Sanjay Kumar Singh (2017). *Nature-Inspired Computing: Concepts, Methodologies, Tools, and Applications (pp. 830-863).* www.irma-international.org/chapter/swarm-intelligence-for-biometric-feature-optimization/161053

Recognition of Human Silhouette Based on Global Features

Milene Arantesand Adilson Gonzaga (2010). *International Journal of Natural Computing Research (pp. 47-55).* www.irma-international.org/article/recognition-human-silhouette-based-global/52615

Mapping with Monocular Vision in Two Dimensions

Nicolau Leal Werneckand Anna Helena Reali Costa (2010). *International Journal of Natural Computing Research (pp. 56-65).* www.irma-international.org/article/mapping-monocular-vision-two-dimensions/52616

A Flexible Bio-Signal Based HMI for Hands-Free Control of an Electric Powered Wheelchair

Ericka Janet Rechy-Ramirezand Huosheng Hu (2014). *International Journal of Artificial Life Research (pp. 59-76).*

www.irma-international.org/article/a-flexible-bio-signal-based-hmi-for-hands-free-control-of-anelectric-powered-wheelchair/103856

Multimodal Genetic Algorithms for Craniofacial Superimposition

Óscar Ibáñez, Oscar Cordón, Sergio Damasand José Santamaría (2010). *Nature-Inspired Informatics for Intelligent Applications and Knowledge Discovery: Implications in Business, Science, and Engineering (pp. 119-143).* www.irma-international.org/chapter/multimodal-genetic-algorithms-craniofacialsuperimposition/36313