Chapter 14 The Role of Neural Networks and Metaheuristics in Agile Software Development Effort Estimation

Anupama Kaushik

Maharaja Surajmal Institute of Technology, Delhi, India; Indira Gandhi Delhi Technical University for Women, Delhi, India

Devendra Kumar Tayal

Indira Gandhi Delhi Technical University for Women, Delhi, India

Kalpana Yadav

Indira Gandhi Delhi Technical University for Women, Delhi, India

ABSTRACT

In any software development, accurate estimation of resources is one of the crucial tasks that leads to a successful project development. A lot of work has been done in estimation of effort in traditional software development. But, work on estimation of effort for agile software development is very scant. This paper provides an effort estimation technique for agile software development using artificial neural networks (ANN) and a metaheuristic technique. The artificial neural networks used are radial basis function neural network (RBFN) and functional link artificial neural network (FLANN). The metaheuristic technique. The proposed techniques FLANN-WOA and RBFN-WOA are evaluated on three agile datasets, and it is found that these neural network models performed extremely well with the metaheuristic technique used. This is further empirically validated using non-parametric statistical tests.

DOI: 10.4018/978-1-6684-2408-7.ch014

INTRODUCTION

In software development firms, two development approaches are present, the traditional software development approach and agile software development approach. In traditional software development approach requirements are well understood and there are predefined stages of development. This type of development is driven by process and tool. The requirements once decided is difficult to change and the customer's involvement is limited in this development. Here, the iterations are longer and the working software is not quickly available.

In agile software development approach customers can do modifications until late in project's life. They are people and collaboration driven. So, there is a continuous involvement of customers'. This development approach is more user friendly and follows incremental and iterative development. The iterations are shorter here and working software is available quickly. Now-a-days, software development firms are moving towards adopting agile methodologies (Dingsøyr, Nerur, Balijepally, & BredeMoe, 2012; Papadopoulos, 2015).

The success of a software project mainly depends upon the accuracy of estimation of its resources like effort, schedule etc. There are many effort estimation studies for traditional software development present in literature (Nguyen, Boehm &LiGuo, 2019; Venkataiah, Mohanty, Pahariya & Nagaratna, 2017; Kaushik, Verma, Singh & Chabbra, 2017; Kaushik, Tayal, Yadav & Kaur, 2016). These studies are based on algorithmic and non-algorithmic approach. The COCOMO model (Boehm, 1994) commonly used for effort estimation in traditional software development uses algorithmic approach. The non-algorithmic approach uses various soft computing techniques like fuzzy logic, neural network, genetic algorithms etc.

In agile software development approach, not much of work has been done in estimation of resources for the projects but a lot of work is going on for developing agile methodologies (Curiel, Jacobo, Alfaro, Zepeda & Delgado, 2018; Tolfo, Wazlawick, Ferreira & Forcellini, 2018; Perkusich, Gorgônio, Almeida, & Perkusich, 2017). This work is dedicated towards estimation of effort for agile projects using story point approach which finds the effort of a project in terms of story points. In the past, few researchers have applied various machine learning techniques for effort estimation using story point approach (Satapathy, Panda & Rath, 2014; Panda, Satapathy & Rath, 2015; Satapathy & Rath, 2017).

The current work integrates artificial neural networks (ANN) with a metaheuristic technique for effort estimation of projects following agile methodologies. The ANN used are RBFN and FLANN and, the metaheuristic technique used is whale optimization algorithm (WOA).

The ANN models incorporated have no relationship with each other and they are evaluated independently. These models are used as they have their own advantages. The major advantages of FLANN are: it has less computational complexity, faster convergence and handles the non-linear data (Mishra & Dehuri, 2007); and the major advantages of RBFN are: its easy design, good generalization, strong tolerance to input noise and has faster online learning ability (Yu, Xie, Paszczyński & Wilamowski, 2011). These models are also chosen as no earlier study exists based on these models for agile environment.

Now-a-days metaheuristic techniques have come up. These are the optimization techniques which mimics the biological or physical phenomenon to solve various engineering problems. They can even find the solutions for the problems with very less and incomplete information. Many new metaheuristic algorithms are developed and many researchers (Kaushik, Tayal, Yadav, & Kaur, 2016; Kaushik, Verma, Singh, & Chhabra, 2017; Benala & Mall, 2018) have used these techniques in estimations for traditional software development environment, but according to the best of our knowledge these techniques have not been explored for resource estimations in agile software development. So the current work is an attempt

21 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/the-role-of-neural-networks-and-metaheuristics-

in-agile-software-development-effort-estimation/288962

Related Content

Netlab Training

(2014). *Medical Diagnosis Using Artificial Neural Networks (pp. 213-232).* www.irma-international.org/chapter/netlab-training/111012

Artificial Neural Network (ANN) in Network Reconfiguration for Improvement of Voltage Stability

Dipu Sarkarand Joyanta Kumar Roy (2020). Deep Learning and Neural Networks: Concepts, Methodologies, Tools, and Applications (pp. 174-198). www.irma-international.org/chapter/artificial-neural-network-ann-in-network-reconfiguration-for-improvement-of-voltagestability/237872

High Level Transformation Techniques for Designing Reliable and Secure DSP Architectures

Jyotirmoy Pathak, Abhishek Kumarand Suman Lata Tripathi (2020). *AI Techniques for Reliability Prediction for Electronic Components (pp. 164-174).*

www.irma-international.org/chapter/high-level-transformation-techniques-for-designing-reliable-and-secure-dsparchitectures/240496

40-GHz Inductor Less VCO

Abhishek Kumar (2020). AI Techniques for Reliability Prediction for Electronic Components (pp. 288-298). www.irma-international.org/chapter/40-ghz-inductor-less-vco/240503

Global Stability Analysis for Complex-Valued Recurrent Neural Networks and Its Application to Convex Optimization Problems

Mitsuo Yoshidaand Takehiro Mori (2009). Complex-Valued Neural Networks: Utilizing High-Dimensional Parameters (pp. 104-122).

www.irma-international.org/chapter/global-stability-analysis-complex-valued/6766