

Chapter 3

Perceiving the World With Sound: An Overview to Robot Audition

Usama Saqib

 <https://orcid.org/0000-0001-9783-1887>

GN Audio, Denmark

Robin Kerstens

 <https://orcid.org/0000-0002-5127-4947>

University of Antwerp, Belgium

ABSTRACT

Robot perception is the ability of a robotic platform to perceive its environment by the means of sensor inputs, e.g., laser, IMU, motor encoders, and so on. Much like humans, robots are not limited to perceiving their environment through vision-based sensors, e.g., cameras. Robot perception, through the scope of this chapter, encompasses acoustic signal processing techniques to locate the presence of a sound source, e.g., human speaker, within an environment for human-robot interaction (HRI), that has gained great interest within scientific community. This chapter will serve as an introduction to acoustic signal processing within robotics, starting with passive acoustic localization and building up to contemporary active sensing methods, such as the usage of neural networks and spatial map generation. The origins of active acoustic localization, which finds its roots in biomimetics, are also discussed.

INTRODUCTION

The detection and localization of acoustic reflectors such as walls, objects or people within an environment is a popular topic within the area of robotics. Traditionally, camera and laser-based technologies are used to detect the presence of these landmarks to generate a spatial map of a 3D space and aid these robotic platforms in navigating within their environment. However, these light-based sensing modalities often face challenges such as a lack of light, overexposure (glare), the inability of detecting transparent

DOI: 10.4018/978-1-6684-5381-0.ch003

Perceiving the World With Sound

surfaces such as windows, false reflections, or their sensitivity to occlusion. These issues can be addressed when incorporating sound-based sensing modalities. Research in animal auditory system has inspired researchers to develop technologies to locate the presence of sound sources within an environment.

This chapter will serve as an introduction to robot audition, starting with the subdomains of robot audition and building up to more contemporary active sensing methods, such as the usage of Artificial Intelligence (AI) on recorded data to detect and track acoustic sources and for spatial map generation. The origins of active acoustic sensing, which finds its roots in biomimetics, are also discussed. This chapter is written as a reference for people working on robot perception using sound and wants to contribute to future works by bringing new challenges to the field of robot perception. The chapter will begin with an introduction to biomimicry in robotics, which aims to mimic an animal's auditory system to localize the position of sound sources in the nearby environment. Biomimicry facilitates intelligent designs in robots to achieve high performance and robustness when navigating between and localizing acoustic sources in a dynamic environment. Designers of such robots make use of new materials, sensors and actuators to provide high capabilities that allow robots to mimic biological processes such as hearing.

Furthermore, this chapter will review techniques in scientific literature associated with passive acoustic localization and active acoustic localization, which are the two important sub-domains of robot audition for SSL. Passive acoustic localization involves detecting sound generated by objects present in an environment while active acoustic localization techniques probe an environment with a known sound to detect the position of objects within an environment. Both sub-domains have their fair share of advantages and disadvantages. For example, active acoustic localization is useful in a quiet environment. This is normally the case when a robot explores an underground environment, such as caves, tunnels, and sewers. Bats, rats and even some aquatic mammals are known to use these techniques to navigate and hunt in complete darkness. These animals probe the environment with a unique sound, or call, and use acoustic echoes to distinguish flora and fauna, different types of animals/prey, and everything needed for their survival. Therefore, a discussion on the different types of probe signals that can be used in robotics to acquire spatial information from the environment is also an important highlight of this chapter. More specifically, analysis of additive white Gaussian noise (AWGN), coded emissions, and chirp signals will be discussed in detail. The application of spatial mapping using echolocation is also an important highlight of this chapter, which incorporate spatial filtering techniques, such as, beamforming techniques.

Finally, the chapter will review data-driven approaches to using contemporary methods such as neural networks for perceiving the environment in an artificially intelligent way. This is relatively a newer approach that combines physics-based model of sound with machine learning to teach robotic platforms to learn to classify and predict their surroundings.

BACKGROUND

Biomimicry in Robotics

The goal of robotics is to design an autonomous machine that behaves, reacts, and interacts with its surroundings much like a human does. That is, a robot should mimic the behavior and, in some cases, the physical appearance of humans. To fulfil this dream, researchers started studying humans and animal senses in an attempt to replicate the sensory organs, so that they can be used by robots. The five senses (seeing, hearing, touching, tasting, and smelling) have been a popular area of research and a source of

28 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/perceiving-the-world-with-sound/314692

Related Content

Awareness-Based Recommendation toward a New Preference: Evaluation of the Awareness Effect

Tomohiro Yamaguchi, Takuma Nishimura and Keiki Takadama (2015). *Handbook of Research on Advancements in Robotics and Mechatronics* (pp. 219-241).

www.irma-international.org/chapter/awareness-based-recommendation-toward-a-new-preference/126018

Hybrid Graph-Based Methods

(2013). *Intelligent Planning for Mobile Robotics: Algorithmic Approaches* (pp. 154-190).

www.irma-international.org/chapter/hybrid-graph-based-methods/69695

Parallel Architecture Manipulators for Use in Masticatory Studies

Madusudanan Sathia Narayanan, Srikanth Kannan, Xiaobo Zhou, Frank Mendeland Venkat Krovi (2011). *International Journal of Intelligent Mechatronics and Robotics* (pp. 100-122).

www.irma-international.org/article/parallel-architecture-manipulators-use-masticatory/61159

Robotic Assistive System: Development of a Model based on Artificial Intelligent Technique

Ku Nurhanim Ku Abdul Rahim, I. Elamvazuthi, P. Vasant and T. Ganesan (2020). *Robotic Systems: Concepts, Methodologies, Tools, and Applications* (pp. 1688-1720).

www.irma-international.org/chapter/robotic-assistive-system/244080

EEG-Analysis for the Detection of True Emotion or Pretension

Reshma Kar, Amit Konar and Aruna Chakraborty (2015). *Handbook of Research on Synthesizing Human Emotion in Intelligent Systems and Robotics* (pp. 283-298).

www.irma-international.org/chapter/eeg-analysis-for-the-detection-of-true-emotion-or-pretension/127568