Chapter 1 MIMO Hybrid Beamforming: Performance Assessment in Macrocells and HetNets

Mostafa Hefnawi Royal Military College of Canada, Canada

Jamal Zbitou

(D) https://orcid.org/0000-0002-3118-8929 LABTIC ENSA of Tangier, University of Abdelmalek Essaadi Tetouan, Morocco

ABSTRACT

In mmWave massive MIMO, the required number of radio frequency (RF) chains becomes impractical due to the expensive and power-hungry components such as variable gain power amplifiers, filters, mixers, and analog-to-digital/digital-to-analog converters (ADCs/DACs). A promising solution to this problem is reducing the number of radiofrequency (RF) chains by partitioning beamforming operations between the digital and RF domains, known as hybrid beamforming (HBF), while still achieving the nearoptimal performance of the fully digital beamforming systems with much-reduced hardware complexity. This chapter reviews different HBF techniques for massive MIMO in 5G and radar systems. The basic HBF structures and their algorithm design is presented in the context of a point-to-point MIMO hybrid beamforming system. Then, some recently proposed HBF techniques for 5G and beyond networks are investigated, followed by a discussion about the benefit of HBF in MIMO radar systems.

INTRODUCTION

Recently, millimeter-wave (mmWave) massive multiple-input multiple-output (MIMO) systems have emerged as a promising solution to enhance the network capacity and coverage of the new generation cellular networks (Marzetta, October 2010; Rusek, 2013; Hoydis, 2013; Busari, 2018). On the one hand, the mmWave can provide a considerable bandwidth; on the other hand, the significant gain of the massive arrays can compensate for the attenuation of the mmWave channel. Traditional MIMO-beamforming systems require a dedicated radio frequency (RF) chain for each antenna element to achieve optimal

DOI: 10.4018/978-1-6684-5955-3.ch001

beamforming performance. However, in mmWave massive MIMO, the required number of radio frequency (RF) chains becomes impractical due to the expensive and power-hungry components such as variable gain power amplifiers, filters, mixers, and analog-to-digital/digital-to-analog converters (ADCs/ DACs). A promising solution to this problem is reducing the number of radiofrequency (RF) chains by partitioning beamforming operations between the digital and RF domains, known as hybrid beamforming (HBF), while still achieving the near-optimal performance of the fully-digital beamforming systems with much-reduced hardware complexity (Sohrabi, F., Yu, W., 2016; El Ayach, O., 2014; Alkhateeb, A., 2014, 2015; Liang, L.,2014; Ni, W., 2017; Hefnawi, M., 2019; Kebede, T., 2022). In HBF, the RF analog beamformer is typically limited to applying phase shifters only to each array element, while digital beamforming with complex weighting vectors can be applied on each RF chain. Figure 1 shows a general hybrid configuration that connects N_a antenna elements to N_d RF chains, where $N_d < N_a$, using an analog RF beamforming matrix built from only phase shifters.





Figure 2. Architectures of analog beamformers: (a) Fully-connected; (b) partially-connected



26 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/mimo-hybrid-beamforming/317783

Related Content

Not Just Playing Around: The MoLeNET Experience of Using Games Technologies to Support Teaching and Learning

Rebecca Petley, Jill Attewelland Carol Savill-Smith (2012). *Wireless Technologies: Concepts, Methodologies, Tools and Applications (pp. 1429-1442).*

www.irma-international.org/chapter/not-just-playing-around/58850

Converged Fi-Wi Passive Optical Networks and Their Designing Using the HPON Network Configurator

Rastislav Róka (2019). Paving the Way for 5G Through the Convergence of Wireless Systems (pp. 150-184).

www.irma-international.org/chapter/converged-fi-wi-passive-optical-networks-and-their-designing-using-the-hponnetwork-configurator/219143

Overload Detection and Energy Conserving Routing Protocol for Underwater Acoustic Communication

Manel Baba Ahmed (2022). International Journal of Wireless Networks and Broadband Technologies (pp. 1-24).

www.irma-international.org/article/overload-detection-and-energy-conserving-routing-protocol-for-underwater-acousticcommunication/304386

Lifetime Maximization in Wireless Sensor Networks

Vivek Katiyar, Narottam Chandand Surender Soni (2011). *International Journal of Wireless Networks and Broadband Technologies (pp. 16-29).*

www.irma-international.org/article/lifetime-maximization-wireless-sensor-networks/55879

An Overview of Wireless Sensor Networks: Towards the Realization of Cooperative Healthcare and Environmental Monitoring

Thomas D. Lagkasand George Eleftherakis (2014). *Handbook of Research on Progressive Trends in Wireless Communications and Networking (pp. 317-339).*

www.irma-international.org/chapter/an-overview-of-wireless-sensor-networks/97850