

Chapter 12

Methods and Applications of Graph Neural Networks for Fake News Detection Using AI-Inspired Algorithms

Arpit Jain

*Koneru Lakshmaiah Education Foundation,
India*

Ishta Rani

Chandigarh University, India

Tarun Singhal

Chandigarh Engineering College, India

Parveen Kumar

Chandigarh University, India

Vinay Bhatia

Chandigarh Engineering College, India

Ankur Singhal

Chandigarh Engineering College, India

ABSTRACT

Graph data, which often includes a richness of relational information, are used in a vast variety of instructional puzzles these days. Modelling physics systems, detecting fake news on social media, gaining an understanding of molecular fingerprints, predicting protein interfaces, and categorising illnesses all need graph input models. Reasoning on extracted structures, such as phrase dependency trees and picture scene graphs, is essential research that is necessary for other domains, such as learning from non-structural data such as texts and photos. These types of structures include phrase dependency trees and image scene graphs. Graph reasoning models are used for this kind of investigation. GNNs have the ability to express the dependence of a graph via the use of message forwarding between graph nodes. Graph convolutional networks (GCN), graph attention networks (GAT), and graph recurrent networks (GRN) have all shown improved performance in response to a range of deep learning challenges over the course of the last few years.

DOI: 10.4018/978-1-6684-6903-3.ch012

INTRODUCTION

Another possible explanation is graph representation learning, which involves the process of understanding how to represent graph nodes, edges, and subgraphs via the use of low-dimensional vectors (Goyal & Ferrara, 2018; Cui et al., 2018a; Hamilton et al., 2017; Zhang et al., 2018a; Cai et al., 2018; Goyal & Ferrara, 2018). Because they depend on hand-engineered features, conventional graph analysis and machine learning approaches are inflexible, time-consuming, and expensive. The SkipGram model is applied to the random walks generated by DeepWalk (Perozzi et al., 2014), which is the first way to graph embedding based on representation learning. DeepWalk was developed by Perozzi and his colleagues. Additionally, substantial progress was achieved in Node2vec, LINE, and TADW. According to Hamilton et al. (2017b), these techniques have two fundamental limitations. First, the encoder does not share any parameters with its offspring nodes. Consequently, the total number of parameters rises proportionately to the total number of nodes, making computation inefficient. Second, direct embedding methods cannot be generalised and cannot handle dynamic graphs.

When creating graph neural networks (GNNs), also known as graph structure data gatherers, CNNs and graph embedding are part of the process. Because of this, they can simulate input and output behaviours that are element-dependent.

The effectiveness of graph neural networks may be evaluated in various ways. In the essay that they published in 2017, Bronstein and his colleagues discuss the problems, prospective solutions, applications, and the future of deep geometric learning. Zhang et al. (2019a) provide a further in-depth analysis and discussion of graph convolutional networks. They explore graph convolution operators, whereas we concentrate on skip connections and pooling operators in GNNs.

The research publications on GNN models carried out by Zhang et al. (2018b), and Chami et al. (2020) are the most current survey studies to be published. Under the findings of Chami et al. (2020), GNNs may be classified as recurrent, convolutional, graph autoencoders or spatial-temporal networks. While Zhang et al. (2018b) provide a comprehensive analysis of graph deep learning approaches, Chami et al. (2020) provide a Graph Encoder-Decoder Model to blend network embedding and graph neural network models. This model was developed in order to improve the accuracy of graph deep learning. This research may be accessed on the web pages maintained by their authors. Our article precisely categorises them and focuses mainly on the more conventional GNN models. In addition, we cover variants of GNN that may be applied to various graphs and their applications in a wide range of business sectors.

In addition, polls were conducted, with the primary emphasis being on learning how to read graphs. An attack on graph data that uses adversarial learning methods and a defence against such an assault. Review of graph attention models. Yang et al. (2020) present learning from a heterogeneous network, which includes multi-type nodes and edges. Huang et al.'s (2020) define the dynamic graph GNN models. Peng et al. (2020) have written combinatorial optimisation graph embeddings are addressed. In Sections 4.2, 4.3, and 8.1.6, the discussion of GNNs for heterogeneous, dynamic, and combinatorial optimisation is ended. The fundamental components of a graph are called nodes and edges. Because of the expressive capability of graphs, they may be used to designate a broad range of systems in the disciplines of social science (social networks; Wu et al., 2020), natural science (physical systems; Sanchez et al., 2018; Battaglia et al., 2016), and knowledge graphs (Yamaguchi et al., 2017). Clustering, link prediction, and node classification are the three critical areas of focus in graph analysis, a non-Euclidean data structure used for machine learning. GNNs are a term used to refer to the deep learning algorithms that work in the graph domain. As a result of the remarkable results it consistently produces, GNN has emerged as

14 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/methods-and-applications-of-graph-neural-networks-for-fake-news-detection-using-ai-inspired-algorithms/323829

Related Content

Self-Adapting Intelligent Neural Systems Using Evolutionary Techniques

Daniel Manrique, Juan Riosand Alfonso Rodriguez-Paton (2006). *Artificial Neural Networks in Real-Life Applications* (pp. 94-115).

www.irma-international.org/chapter/self-adapting-intelligent-neural-systems/5365

Biological Neural Circuits as Applications in Business and Engineering as a New Approach in Artificial Intelligence

Rinat Galiautdinov (2021). *Artificial Neural Network Applications in Business and Engineering* (pp. 49-74).

www.irma-international.org/chapter/biological-neural-circuits-as-applications-in-business-and-engineering-as-a-new-approach-in-artificial-intelligence/269581

A Prescriptive Stock Market Investment Strategy for the Restaurant Industry using an Artificial Neural Network Methodology

Gary R. Weckman, Ronald W. Dravenstott, William A. Young II, Ehsan Ardjmand, David F. Millieand Andy P. Snow (2020). *Deep Learning and Neural Networks: Concepts, Methodologies, Tools, and Applications* (pp. 217-237).

www.irma-international.org/chapter/a-prescriptive-stock-market-investment-strategy-for-the-restaurant-industry-using-an-artificial-neural-network-methodology/237874

Cognitive Deep Learning: Future Direction in Intelligent Retrieval

Chiranji Lal Chowdhary, Ashraf Darwishand Aboul Ella Hassanien (2019). *Handbook of Research on Deep Learning Innovations and Trends* (pp. 220-231).

www.irma-international.org/chapter/cognitive-deep-learning/227854

Multi-Sensor Motion Fusion Using Deep Neural Network Learning

Xinyao Sun, Anup Basuand Irene Cheng (2020). *Deep Learning and Neural Networks: Concepts, Methodologies, Tools, and Applications* (pp. 568-586).

www.irma-international.org/chapter/multi-sensor-motion-fusion-using-deep-neural-network-learning/237893