


Chapter 8

Modelling and Performance Analysis of Battery Thermal Management System for Electric Vehicles on MATLAB/Simulink

Gaurav Raj Pandey


 <https://orcid.org/0000-0002-0100-9248>

Independent Researcher, India

Kheelraj Pandey

Amity University, Lucknow, India

Ashwani Sharma

 <https://orcid.org/0000-0003-2749-1666>

Amity University, Lucknow, India

ABSTRACT

The battery pack in an electric car plays a vital role in converting direct current (DC) from the battery into alternating current (AC) to power the induction motor. It is a complex arrangement of batteries connected in series and parallel to meet the power requirements of electric vehicles. A Battery Management System (BMS) is employed to ensure safe and efficient operation. The BMS oversees and regulates the battery's performance by monitoring and managing voltage, current, temperature, and state of charge. This prevents any parameters from exceeding safe levels,

DOI: 10.4018/979-8-3693-4314-2.ch008

ensuring the longevity and safety of the battery. The Battery Thermal Management System (BTMS) involves monitoring the temperature of the battery packs and initiating the cooling process when the temperature rises. This prevents excessive heat that could lead to component failure. MATLAB/Simulink is used to develop BTMS that analyze and compare temperature and state of charge parameters with and without the integration of a cooling system connected to the battery pack, aiming to improve battery pack performance.

MODELLING AND PERFORMANCE ANALYSIS OF BATTERY THERMAL MANAGEMENT SYSTEM FOR ELECTRIC VEHICLES ON MATLAB/SIMULINK

The electric car's battery pack converts direct current (DC) from the battery into alternating current (AC) to power the induction motor through power electronic components, making it a vital component of the vehicle. The battery pack in electric vehicles is a sophisticated system comprised of multiple batteries that are interconnected both in series and parallel configurations. This setup is designed to meet the high-power demands of electric cars, necessitating careful monitoring and control to ensure the safe and optimal functioning of the battery pack. To ensure the safe and effective functioning of the batteries, a Battery Management System (BMS) is employed. The BMS oversees and regulates the battery's performance to guarantee safe and efficient operation. It is responsible for monitoring and managing voltage, current, temperature, and state of charge to prevent any parameters from exceeding safe levels, ensuring the battery's longevity and safety. The correct positioning and effective use of the Battery Management System (BMS) play a vital role in ensuring the peak performance and safety of the battery within an electric vehicle. It is imperative to place the BMS in a strategic location within the vehicle to monitor and regulate the battery's functions efficiently. Additionally, the proper utilization of the BMS is essential in managing the charging and discharging processes of the battery to maximize its lifespan and overall performance. The thermal management of BMS involves monitoring the temperature of battery packs. When the temperature rises, a control signal is sent to the coolant circuit, initiating the cooling process to regulate the temperature. This is crucial in preventing excessive heat that could lead to component failure. The temperature of the battery pack is measured during charging, discharging, and while the electric vehicle is in operation. To improve battery pack performance, MATLAB/Simulink is used to develop battery thermal management systems that analyze and compare temperature and state of charge (SoC) parameters with and without the integration of a cooling system connected to the battery pack.

34 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/modelling-and-performance-analysis-of-battery-thermal-management-system-for-electric-vehicles-on-matlab-simulink/353325

Related Content

Surface Charge Property of SiR/SiC Composites with Field-Dependent Conductivity

(2020). *Electrical Insulation Breakdown and Its Theory, Process, and Prevention: Emerging Research and Opportunities* (pp. 219-254).

www.irma-international.org/chapter/surface-charge-property-of-sirsic-composites-with-field-dependent-conductivity/243863

Increasing the Energy Efficiency of Photovoltaic Systems Operating Under Conditions of Uneven Illumination

Leonid Yuferev and Pavel Nikolaevich Kuznetsov (2019). *Renewable Energy and Power Supply Challenges for Rural Regions* (pp. 88-114).

www.irma-international.org/chapter/increasing-the-energy-efficiency-of-photovoltaic-systems-operating-under-conditions-of-uneven-illumination/223848

Modern Optimization Algorithms and Applications in Solar Photovoltaic Engineering

Igor Tyukhov, Hegazy Rezk and Pandian Vasant (2016). *Sustaining Power Resources through Energy Optimization and Engineering* (pp. 390-445).

www.irma-international.org/chapter/modern-optimization-algorithms-and-applications-in-solar-photovoltaic-engineering/143791

Load Research

(2012). *Power System Planning Technologies and Applications: Concepts, Solutions and Management* (pp. 47-60).

www.irma-international.org/chapter/load-research/63929

Energy Storage Systems: From Classic to Hydrogen

Ana-Maria Nasture, Maria Simona Raboaca, Laurentiu Patularu and Ciprian Lupu (2021). *Hydrogen Fuel Cell Technology for Stationary Applications* (pp. 105-138).

www.irma-international.org/chapter/energy-storage-systems/276553