

# Chapter 1.5

## RFID Technologies and Applications

**Christian Kaspar**

*Georg-August-Universität Göttingen, Germany*

**Adam Melski**

*Georg-August-Universität Göttingen, Germany*

**Britta Lietke**

*Georg-August-Universität Göttingen, Germany*

**Madlen Boslau**

*Georg-August-Universität Göttingen, Germany*

**Svenja Hagenhoff**

*Georg-August-Universität Göttingen, Germany*

### INTRODUCTION

Radio frequency identification (RFID) is a radio-supported identification technology that typically operates by saving a serial number on a radio transponder that contains a microchip for data storage. Via radio waves, the coded information is communicated to a reading device (Jones et al., 2005). RFID does not represent a new development; it was devised by the American military in the 1940s. Since the technology's clearance

for civil use in 1977, RFID has been successfully used for the identification of productive livestock, for electronic immobilizer systems in vehicles, or for the surveillance of building entrances (Srivastava, 2005). Due to decreasing unit costs (especially for passive transponders), RFID technologies now seem increasingly applicable for the labeling of goods and semi-finished products. By this, manual or semi-automatic data entry, for instance through the use of barcodes, can be avoided. This closes the technical gap

between the real world (characterized by the lack of distribution transparency of its objects) and the digital world (characterized by logically and physically unambiguous and therefore distribution-transparent objects). In addition, RFID facilitates fully automated simultaneous recognition of more than one transponder without direct line of sight between reader and transponders.

**CONFIGURATION OF RFID SYSTEMS**


A typical RFID system consists of three basic components (Jones et al., 2005): (1) a computer, (2) a reader, and (3) a transponder, as depicted in Figure 1.

1. The computer runs an application that requires real world data (for instance enterprise resource planning [ERP], manufacturing

execution system [MES], supply chain management [SCM], or e-commerce applications). The processor sends commands to the reader and receives its replies.

2. The reader is connected to the processor through either a serial interface or a network connection. It contains a so-called “coupling unit,” which allows the reader to modulate coded commands onto a magnetic or electromagnetic alternating field. The size and form of this coupling unit may vary, and its dimension determines the design of the reader.
3. The transponder has to be attached to the object to be identified. It is the actual information carrier. All transponders in the reader’s field receive commands and send back their response data. A transponder usually consists of a microchip and a coupling unit. There are various transponder designs; most common, however, are small spools attached to adhesive film.

*Figure 1. Logical RFID system architecture (Bitkom, 2005; Thiesse, 2005)*



8 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

[www.igi-global.com/chapter/rfid-technologies-applications/37776](http://www.igi-global.com/chapter/rfid-technologies-applications/37776)

## Related Content

---

### Ontologies for Scalable Services-Based Ubiquitous Computing

Daniel Oberle, Christof Bornhovdand Michael Althenhofen (2008). *Handbook of Research on Ubiquitous Computing Technology for Real Time Enterprises* (pp. 88-106).

[www.irma-international.org/chapter/ontologies-scalable-services-based-ubiquitous/21764](http://www.irma-international.org/chapter/ontologies-scalable-services-based-ubiquitous/21764)

### Analysis of Big Data Using Two Mapper Files in Hadoop

Jyotsna Malhotra, Jasleen Kaur Sethiand Mamta Mittal (2021). *International Journal of Security and Privacy in Pervasive Computing* (pp. 69-77).

[www.irma-international.org/article/analysis-of-big-data-using-two-mapper-files-in-hadoop/269506](http://www.irma-international.org/article/analysis-of-big-data-using-two-mapper-files-in-hadoop/269506)

### A QoS aware Framework to support Minimum Energy Data Aggregation and Routing in Wireless Sensor Networks

Neeraj Kumarand R.B. Patel (2009). *International Journal of Advanced Pervasive and Ubiquitous Computing* (pp. 91-106).

[www.irma-international.org/article/qos-aware-framework-support-minimum/41706](http://www.irma-international.org/article/qos-aware-framework-support-minimum/41706)

### Service Discovery

Gerhard Austaller (2008). *Handbook of Research on Ubiquitous Computing Technology for Real Time Enterprises* (pp. 107-127).

[www.irma-international.org/chapter/service-discovery/21765](http://www.irma-international.org/chapter/service-discovery/21765)

### Consumer Attitudes toward RFID Usage

Madlen Boslauand Britta Lietke (2010). *Ubiquitous and Pervasive Computing: Concepts, Methodologies, Tools, and Applications* (pp. 1098-1105).

[www.irma-international.org/chapter/consumer-attitudes-toward-rfid-usage/37839](http://www.irma-international.org/chapter/consumer-attitudes-toward-rfid-usage/37839)