

## Chapter 4.14

# Neural Network–Based Process Analysis in Sport

**Juergen Perl**

*University of Mainz, Germany*

### INTRODUCTION

Processes in sport like motions or games are influenced by communication, interaction, adaptation, and spontaneous decisions. Therefore, on the one hand, those processes are often fuzzy and unpredictable and so have not extensively been dealt with, yet. On the other hand, most of those processes structurally are roughly determined by intention, rules, and context conditions and so can be classified by means of information patterns deduced from data models of the processes.

Self organizing neural networks of type Kohonen Feature Map (KFM) help for classifying information patterns – either by mapping whole processes to corresponding neurons (see Perl &

Lames, 2000; McGarry & Perl, 2004) or by mapping process steps to neurons, which then can be connected by trajectories that can be taken as process patterns for further analyses (see examples below). In any case, the dimension of the original data (i.e. the number of contained attributes) is reduced to the dimension of the representing neuron (normally 2 or 3), which makes it much easier to deal with.

Additionally, extensions of the KFM-approach are introduced, which are able to flexibly adjust the net to dynamically changing training situations. Moreover, those extensions allow for simulating adaptation processes like learning or tactical behaviour.

Finally, a current project is introduced, where tactical processes in soccer are analysed under the aspect of simulation-based optimization.

DOI: 10.4018/978-1-60960-195-9.ch414

## **BACKGROUND**

A major problem in analysing complex processes in sport like motions or games often is the reduction of available data to useful information. Two examples shall make plain what the particular problems in sport are:

In Motor Analysis, a lot of data regarding positions, angles, speed, or acceleration of articulations can be recorded automatically by means of markers and high speed digital cameras. The problem is that those recorded data show a high degree of redundancy and inherent correlation: A leg consisting of thigh, lower leg, foot, and the articulations hip joint, knee, and ankle obviously has only a comparably small range of possible movements due to natural restrictions. Therefore the quota of characteristic motion data is comparably small as well. Classification can help for deducing that relevant information from recorded data by mapping them to representative types or patterns.

In Game Analysis, during the last about 5 years an increasing number of approaches have been developed which enable for automatic recording of position data. Based on the video time precision of 25 frames per second, 9.315.000 x-y-z-coordinate data from 22 players and the ball can be taken from a 90-minutes soccer game. Obviously, the amount of data has to be reduced and to be focused to the major tactical patterns of the teams. Similar to what coaches are doing, the collection of players' positions can be reduced to constellations of tactical groups which interact like super-players and therefore enable for a computer-aided game analysis based on pattern analysis.

As is demonstrated in the following, neural network-based pattern analysis can support the handling of those problems.

## **MAIN FOCUS OF THE CHAPTER**

### **Artificial Neural Networks**

Current developments in the fields of Soft Computing and/or Computational Intelligence demonstrate how information patterns can be taken from data collections by means of fuzziness, similarity and learning, which the approach of Artificial Neural Networks gives an impressive example for. In particular self organizing neural networks of type KFM (Kohonen Feature Map) play an important role in aggregating input data to clusters or types by means of a self organized similarity analysis (Kohonen, 1995).

### **Net-Based Process Analysis**

Processes can be mapped to attribute vectors – in a game, for example, by recording the positions of the players – which then can be learned by neurons. There is, of course, a certain loss of precision if replacing an attribute vector by a representing neuron, the entry of which is similar but normally not identical to that attribute vector. Nevertheless, there are two major advantages of the way a KFM maps input data to corresponding neurons:

1. The number of objects is dramatically reduced if using the representing neurons instead of the original attribute vectors: a 2-dimensional  $20 \times 20$ -neuron-matrix contains 400 neurons, while a 10-dimensional vector space with only 10 different values per attribute already contains  $10^{10} = 10.000.000.000$  vectors.
2. The dimension of input data is reduced to the dimension of the network (i.e. normally 2 or at most 3). This for example enables for mapping time-series of high-dimensional attribute vectors to trajectories of neurons that can easily be presented graphically.

7 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:  
[www.igi-global.com/chapter/neural-network-based-process-analysis/49439](http://www.igi-global.com/chapter/neural-network-based-process-analysis/49439)

## Related Content

---

### PIR: A Domain Specific Language for Multimedia Information Retrieval

Xiaobing Huang, Tian Zhao and Yu Cao (2014). *International Journal of Multimedia Data Engineering and Management* (pp. 1-27).

[www.irma-international.org/article/pir/117891](http://www.irma-international.org/article/pir/117891)

### KTRICT A KAZE Feature Extraction: Tree and Random Projection Indexing-Based CBIR Technique

Badal Soni, Angana Borah, Pidugu Naga Lakshmi Sowgandhi, Pramod Sarma and Ermyas Fekadu Shiferaw (2020). *International Journal of Multimedia Data Engineering and Management* (pp. 49-65).

[www.irma-international.org/article/ktrict-a-kaze-feature-extraction/260964](http://www.irma-international.org/article/ktrict-a-kaze-feature-extraction/260964)

### HTSPN: An Experience in Formal Modeling of Multimedia Applications Coded in MHEG or Java

Willrich Roberto, Pierre de Saqui-Sannes, Patrick Senac and Michel Diaz (2001). *Design and Management of Multimedia Information Systems: Opportunities and Challenges* (pp. 380-411).

[www.irma-international.org/chapter/htspn-experience-formal-modeling-multimedia/8125](http://www.irma-international.org/chapter/htspn-experience-formal-modeling-multimedia/8125)

### Enhancing Rating Prediction by Discovering and Incorporating Hidden User Associations and Behaviors

Ligaj Pradhan (2019). *International Journal of Multimedia Data Engineering and Management* (pp. 40-59).

[www.irma-international.org/article/enhancing-rating-prediction-by-discovering-and-incorporating-hidden-user-associations-and-behaviors/232181](http://www.irma-international.org/article/enhancing-rating-prediction-by-discovering-and-incorporating-hidden-user-associations-and-behaviors/232181)

### iASSIST: An iPhone-Based Multimedia Information System for Indoor Assistive Navigation

Zhigang Zhu, Jin Chen, Lei Zhang, Yaohua Chang, Tyler Franklin, Hao Tang and Arber Ruci (2020). *International Journal of Multimedia Data Engineering and Management* (pp. 38-59).

[www.irma-international.org/article/iassist/267766](http://www.irma-international.org/article/iassist/267766)