

The Development of a Parallel Ray Launching Algorithm for Wireless Network Planning

Zhihua Lai, University of Bedfordshire, UK

Nik Bessis, University of Bedfordshire, UK

Guillaume De La Roche, University of Applied Science of Western Switzerland, Switzerland

Pierre Kuonen, University of Applied Science of Western Switzerland, Switzerland

Jie Zhang, University of Bedfordshire, UK

Gordon Clapworthy, University of Bedfordshire, UK

ABSTRACT

Propagation modeling has attracted much interest because it plays an important role in wireless network planning and optimization. Deterministic approaches such as ray tracing and ray launching have been investigated, however, due to the running time constraint, these approaches are still not widely used. In previous work, an intelligent ray launching algorithm, namely IRLA, has been proposed. The IRLA has proven to be a fast and accurate algorithm and adapts to wireless network planning well. This article focuses on the development of a parallel ray launching algorithm based on the IRLA. Simulations are implemented, and evaluated performance shows that the parallelization greatly shortens the running time. The COST231 Munich scenario is adopted to verify algorithm behavior in real world environments, and observed results show a 5 times increased speedup upon a 16-processor cluster. In addition, the parallelization algorithm can be easily extended to larger scenarios with sufficient physical resources.

Keywords: Intelligent Ray Launching, Network Planning, Parallelization, Propagation Prediction, Simulation

INTRODUCTION

Propagation modeling serves as a fundamental input in the wireless network planning and optimization process. Especially, in order to determine the interferences for an indoor fem-

tocell base station with the outdoor macrocell, accurate coverage predictions have to be obtained via propagation modeling (Zhang & De La Roche, 2010). Planning and optimization of a wireless network usually requires simulation of hundreds of User Equipments (UE) and the path loss between these UEs and base stations

DOI: 10.4018/jdst.2011040101

are obligatory to investigate the best servers and handovers etc.

Current propagation models can be divided into three categories: empirical models, semi-deterministic and deterministic models. Empirical models are the simplest models; which are usually based on simple factors such as the carrier frequency and distance. They are extremely fast because of statistical model environmental factors. The semi-deterministic models are enhanced by introducing relevant deterministic factors in the computation. Such models provide higher accuracy than empirical models, thus running time of semi-deterministic models is usually realistically acceptable upon conventional computing power, such as PCs.

The deterministic models consider environmental factors, e.g., buildings and walls, which are time-consuming compared to empirical and semi-deterministic models. However, the deterministic models provide the highest accuracy out of these categories.

Ray-based methods belong to deterministic models and they are based on geometry path finding algorithms (Haslett, 2008). Ray-based methods in general are divided into two subcategories: ray tracing and ray launching. Ray tracing adopts a backward path search technique, which guarantees that exact paths between transmitters and receivers can be computed (Glassner, 1989). Ray tracing offers high accuracy but it is extremely time consuming. The complexity grows exponentially with the number of objects and the maximum ray iterations (Nagy, Dady, & Farkasvolgyi, 2009). Ray tracing is used for precise point-to-point predictions. Several acceleration techniques such as pre-processing (Wofle, Gschwendtner, & Landstorfer, 1997) or the use of a General Purpose Graphic Processing Unit (GPGPU) (Rick & Mathar, 2007) have been proposed. The performance of ray tracing is usually limited by the inherent complex ray-object intersection tests and many techniques have been proposed over the past years to speed up computation (Degli-Esposti, Fuschini, Vitucci, & Falcia-secca, 2009). Ray launching emits the rays from sources; which are separated by a small angle.

This method is efficient in an area prediction because the rays are actively followed. However, this approach leads to two inherent problems. The first problem is angular dispersion of ray launching. The distant pixels are less likely to be visited by rays because rays disperse as they are propagated. For example, a distant small object may be missed by rays because a fixed angle is used to separate rays. Secondly, the ray double counting arises when a sample pixel is marked twice by the same rays, which should be avoided because it reduces the accuracy of ray launching. Ray launching is usually faster than ray tracing with less accuracy. The complexity of ray launching grows linearly with the number of objects and maximum ray iteration (Nagy et al., 2009).

In (Lai, Bessis, De La Roche, Song, Zhang, & Clapworthy, 2009), a new model based on discrete ray launching, namely the Intelligent Ray Launching Algorithm (IRLA), has been proposed to obtain fast propagation prediction (path loss and multipath components) within a realistic time scale. In (Lai et al., 2010), the authors extended this model to indoor prediction, which accurately predicts the multipath propagation in indoor environment. The IRLA model has been validated with measurement campaigns (Lai et al., 2010), which has led to the effective development for network applications. In (Lai et al., 2009), the authors proposed an efficient method to improve the accuracy of IRLA by solving angular dispersion problem of ray launching. This method has effectively improved the accuracy and avoids ray double counting. In (Lai et al., 2009), a parallel algorithm of IRLA is implemented based on a toolkit named Parallel Object-oriented Programming in C++ (POP-C++). Preliminary promising results have been presented, which show that parallel IRLA has improved the performance. This article is an extension of this work: issues related to performance and accuracy will be further addressed in this work. This article contributes to present a parallel propagation algorithm that accelerates the time-consuming prediction. The components of the IRLA model are analyzed so that the most time-consuming

17 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/article/development-parallel-ray-launching-algorithm/53849

Related Content

Optimal Scheduling of Parallel Jobs With Unknown Service Requirements

Benjamin Bergand Mor Harchol-Balter (2021). *Handbook of Research on Methodologies and Applications of Supercomputing* (pp. 18-40).

www.irma-international.org/chapter/optimal-scheduling-of-parallel-jobs-with-unknown-service-requirements/273393

Improvement of JXTA-Overlay P2P Platform: Evaluation for Medical Application and Reliability

Yi Liu, Shinji Sakamoto, Keita Matsuo, Makoto Ikeda, Leonard Barolliand Fatos Xhafa (2015). *International Journal of Distributed Systems and Technologies* (pp. 45-62).

www.irma-international.org/article/improvement-of-jxta-overlay-p2p-platform/126177

A Security Prioritized Computational Grid Scheduling Model: An Analysis

Rekha Kashyapand Deo Prakash Vidyarthi (2009). *International Journal of Grid and High Performance Computing* (pp. 73-84).

www.irma-international.org/article/security-prioritized-computational-grid-scheduling/3971

Dynamic Dependent Tasks Assignment for Grid Computing

Meriem Meddeberand Belabbas Yagoubi (2013). *Applications and Developments in Grid, Cloud, and High Performance Computing* (pp. 58-73).

www.irma-international.org/chapter/dynamic-dependent-tasks-assignment-grid/69027

Semaphore Based Data Aggregation and Similarity Findings for Underwater Wireless Sensor Networks

Ruby Dand Jeyachidra J (2019). *International Journal of Grid and High Performance Computing* (pp. 59-76).

www.irma-international.org/article/semaphore-based-data-aggregation-and-similarity-findings-for-underwater-wireless-sensor-networks/232213