

Chapter 1.4

Survey of Cross-Layer Optimization Techniques for Wireless Networks

Han-Chieh Chao

National Ilan University, Taiwan

Chi-Yuan Chang

National Dong Hwa University, Taiwan

Chi-Yuan Chen

National Dong Hwa University, Taiwan

Kai-Di Chang

National Dong Hwa University, Taiwan

ABSTRACT

The explosive development of Internet and wireless communication has made personal communication more convenient. People can use a handy wireless device to transfer different kinds of data such as voice data, text data, and multimedia data. Multimedia streaming, video conferencing, and on-line interactive 3D games are expected to attract an increasing number of users in the future. The bandwidth requirement would be high and the heterogeneous terminals would generally provide limited resource, such as low processing power, low battery life and limited data rate capabilities. These applications would be the major challenge for wireless networks. Although the traditional layered protocol stacks have been used for many years, they are not suitable for the next generation wireless networks and the mobile systems. Due to the time varying transmission of the wireless channel and the dynamic resource requirements of different application, the traditional layered approach to the mobile multimedia communication is full of challenges to meet the user requirement on performance and efficiency. Cross-layer design is an interesting research topic that actively exploits the dependence between different protocol layers to obtain performance gains. The authors performed a survey and introduced the cross-layer design principles and issues for different research topics, including QoS, mobility, security, application, and the next generation wireless communication.

DOI: 10.4018/978-1-61350-101-6.ch104

CURRENT PRINCIPLES FOR CROSS-LAYER DESIGN

The traditional Open System Interconnection (OSI) seven layer protocol stacks have been used for many years. The function of each layer is defined clearly. All those protocol layers are coordinated to complete the network communication. The OSI model could reduce the complex of network implementation and increase the flexibility. However, for the next generation wireless networks and mobile systems, the traditional approach to network design can not satisfy the user requirement on performance and efficiency. Because of the time varying transmission of the wireless channel and the dynamic resource requirements of different application, the mobile multimedia communication is very challenging. Based on limited frequency allocations and channel considerations, Shakkottai et al (2003) depicted the special properties of wireless networks that distinguish them from conventional wire-line networks.

In the layered OSI architecture model, the protocol at each layer is designed independently for the different layers. The layered architecture doesn't allow direct communication between nonadjacent layers. Communication between adjacent layers must follow the pre-defined interfaces through procedure calls and responses.

Cross-layer design is a new research topic that actively exploits the dependence and interaction between different protocol layers to obtain performance gains. Srivastava and Motani made a detail survey on cross-layer design and depicted that there are three main reasons to motivate designers to violate the layered architectures, which are the special problems under the wireless environment, the possibility of opportunistic communication on wireless links, and the new communication models offered by the wireless medium (Srivastava & Motani, 2005; Qusay, 2007).

An important cross-layer design aspect is the management of cross-layer interaction that can

guarantee the system operation. Such cross-layer entities may reside within the protocol stack, in which case it is considered as an internal cross-layer entity or an external network node (Foukalas, Gazis, & Alonistioti, 2008). Figure 1 shows that the internal entity may be either an interlayer entity that coordinates the operation of all protocol stack layers or an intralayer entity that is located within a protocol layer. The external cases are illustrated in Figure 2. The external entities may be centralized by a specific network node or distributed over several network nodes.

Kawadia and Kumar (2005) examined holistically the issues of cross-layer design and its architectural categories. They emphasized the importance of well constructed architecture. Modularity in system could provide the abstractions of system and makes designers easy to understand the overall system. It can also accelerate development of both design and implementation. Designers can focus their effort on a particular subsystem and assure that the entire system will operate correctly. A good architectural design can make system easy to maintain and lead to longer life cycle.

Based on the electronic transfer of information, Kawadia and Kumar (2005) depicted that operating a wireless network based on a layered stack is a natural way to implement the multi-hop decode and forward strategy. A layered architecture can achieve optimal performance, within a constant, with regard to network capacity. They also claimed that all cross-layer design can only improve throughput by at most a constant factor, but cannot result in any unbounded improvements.

In evaluating the cross-layer design proposals, the trade-off between performance and architecture needs to be fundamentally considered. Performance is considered to be more short-term and architecture is longer-term. Thus, a particular cross-layer suggestion may get an improvement in throughput or performance but the longer-term consideration is lack. However, it is very difficult

15 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/survey-cross-layer-optimization-techniques/58782

Related Content

Adaptive Aperture Aided Antenna Design for SISO-MIMO Systems using Fuzzy C-Mean Clustering

Parismita A. Kashyap and Kandarpa Kumar Sarma (2015). *International Journal of Wireless Networks and Broadband Technologies* (pp. 33-47).

www.irma-international.org/article/adaptive-aperture-aided-antenna-design-for-siso-mimo-systems-using-fuzzy-c-mean-clustering/154480

Trends in Managing Multimedia Semantics

Roberto Poli, Achilles Kameas and Lambrini Seremeti (2014). *International Journal of Wireless Networks and Broadband Technologies* (pp. 40-55).

www.irma-international.org/article/trends-in-managing-multimedia-semantics/115589

Augmented Reality (AR) Applications in Agriculture

Róbert Szilágyi and Miklós Herdon (2016). *Mobile Computing and Wireless Networks: Concepts, Methodologies, Tools, and Applications* (pp. 1290-1305).

www.irma-international.org/chapter/augmented-reality-ar-applications-in-agriculture/138331

The Next Generation CDMA Technology for Futuristic Wireless Communications: Why Complementary Codes?

Hsiao-Hwa Chen (2010). *Fourth-Generation Wireless Networks: Applications and Innovations* (pp. 596-621).

www.irma-international.org/chapter/next-generation-cdma-technology-futuristic/40719

Strategy for Reducing Delays and Energy Consumption in Cloudlet-Based Mobile Cloud Computing: Problems on Mobile Devices, Problem Solution, Selection of Cloudlets According to User Requirements

Rashid Alakbarov (2021). *International Journal of Wireless Networks and Broadband Technologies* (pp. 32-44).

www.irma-international.org/article/strategy-for-reducing-delays-and-energy-consumption-in-cloudlet-based-mobile-cloud-computing/272050