

Chapter 4.5

Data Gathering in Correlated Wireless Sensor Networks with Cooperative Transmission

Laxminarayana S. Pillutla

The University of British Columbia, Canada

Vikram Krishnamurthy

The University of British Columbia, Canada

ABSTRACT

This chapter considers the problem of data gathering in correlated wireless sensor networks with distributed source coding (DSC), and virtual multiple input and multiple output (MIMO) based cooperative transmission. Using the concepts of super and sub modularity on a lattice, we analytically quantify as how the optimal constellation size, and optimal number of cooperating nodes, vary with respect to the correlation coefficient. In particular, we show that the optimal constellation size is an increasing function of the correlation coefficient. For the virtual MIMO transmission case, the optimal number of cooperating nodes is a decreasing function of the correlation coefficient. We also prove that in a virtual MIMO based transmission scheme, the optimal constellation size adopted by each cooperating node is a decreasing function of number of cooperating nodes. Also it is shown that, the optimal number of cooperating nodes is a decreasing function of the constellation size adopted by each cooperating node. We also study numerically that for short distance ranges, SISO transmission achieves better energy-mutual information (MI) tradeoff. However, for medium and large distance ranges, the virtual MIMO transmission achieves better energy-MI tradeoff.

DOI: 10.4018/978-1-61350-101-6.ch405

INTRODUCTION

A wireless sensor network (WSN) consists of large number of spatially distributed devices called *nodes*, which cooperate to accomplish various high level tasks. These nodes find applications in a wide range of remote sensing and environmental applications. Each of these nodes are equipped with a sensor and wireless transceiver, to perform sensing and communication tasks respectively. Typically the nodes are equipped with small batteries, and therefore are subject to severe energy constraints. Consequently, the main objective of sensor network research is to design energy-efficient devices and algorithms to support various aspects of network operation. The μ AMP project at MIT (Chandrakasan, Min, Bharadwaj, Cho & Wang, 2002), and the PicoRadio project at Berkeley (Rabaey, Ammer, dasilva, Patel & Roundy, 2000) are efforts in this direction. Another unique feature of WSNs is, the high degree of spatial correlation in the data sensed by the nodes, owing to their close proximity. We refer the readers to (Akyildiz, Su, Sankarasubramaniam & Cayirci, 2002), for a detailed discussion on WSNs and their applications.

Typically in a WSN, the nodes cooperate to accomplish a common task (unlike a conventional wireless network), therefore the idea of cooperation is central to the design of a WSN. The cooperation among WSNs can be of two types: *implicit* and *explicit*. In implicit cooperation, the nodes of a WSN cooperate implicitly based on the information obtained a priori. The concept of distributed source coding (DSC) where the sensor nodes determine their encoding rates, based on the prior information obtained on spatial correlation, is an instance of implicit cooperation. On the other hand, in the explicit cooperation, the nodes cooperate explicitly by sharing information. The concept of virtual multiple input and multiple output (MIMO) (or cooperative) transmission, where the sensor nodes share information and transmit

cooperatively, is an instance of explicit cooperation. In this chapter, we consider an architecture based on implicit and explicit cooperation for WSNs. Specifically, we consider an architecture that employs, virtual MIMO to reduce the energy consumption of each sensor node and DSC to exploit the spatial correlation.

The concept of virtual MIMO aims to exploit the benefits of popular MIMO antenna techniques for WSNs. Direct application of the popular MIMO techniques to WSNs is not possible, owing to the relatively small size of the sensor nodes. However, by allowing the nodes to exchange their information, one can create a virtual MIMO system. We focus on *orthogonal* space-time block codes (STBC) (Tarokh, Jafarkhani & Calderbank, 1999) as a way to implement virtual MIMO in WSNs. The orthogonal STBCs are attractive because they facilitate simple decoding at the receiver. However, the orthogonal STBCs are bandwidth inefficient, especially if the number of cooperating nodes is greater than two. The reason for this bandwidth inefficiency can be attributed to the fact that, it may not be possible to design orthogonal STBCs with spatial rate equal to one, if the number of sensor nodes is greater than two (Liang, 2003). Thus it is of interest to know the effect of using an STBC with spatial rate less than one, on the energy efficiency of a WSN. To this end, we formulate the problem of minimum energy data gathering in correlated WSNs. We also study the tradeoff between energy-Mutual Information (MI) and energy-mean square error (MSE), for single input and single output (SISO) and virtual MIMO based transmission schemes in correlated WSNs.

An important aspect of our work is, we analytically study the effect of data correlation on physical layer design variables such as, constellation size and number of cooperating nodes, which was not considered before. In general, the energy expended by a sensor node is a function of constellation size. *Constellation size* represents the number of bits that can be transmitted in a given modulation symbol. Further in cases where the nodes cooper-

21 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:
www.igi-global.com/chapter/data-gathering-correlated-wireless-sensor/58825

Related Content

Navigation Based on Sensors in Smartphones

Guenther Retscher and Allison Kealy (2018). *Positioning and Navigation in Complex Environments* (pp. 368-396).

www.irma-international.org/chapter/navigation-based-on-sensors-in-smartphones/195720

Co-Operative Load Balancing in Vehicular Ad Hoc Networks (VANETs)

G. G. Md. Nawaz Ali and Edward Chan (2011). *International Journal of Wireless Networks and Broadband Technologies* (pp. 1-21).

www.irma-international.org/article/operative-load-balancing-vehicular-hoc/64624

Cooperation Among Members of Online Communities: Profitable Mechanisms to Better Distribute Near-Real-Time Services

M. L. Merani, M. Capetta and D. Saladino (2011). *International Journal of Wireless Networks and Broadband Technologies* (pp. 1-14).

www.irma-international.org/article/cooperation-among-members-online-communities/62084

A Demonstration of Practical DNS Attacks and their Mitigation Using DNSSEC

Israr Khan, William Farrelly and Kevin Curran (2020). *International Journal of Wireless Networks and Broadband Technologies* (pp. 56-78).

www.irma-international.org/article/a-demonstration-of-practical-dns-attacks-and-their-mitigation-using-dnssec/249154

Energy Efficient Clustering using Modified Multi-Hop Clustering

Vimala M. and Rajeev Ranjan (2019). *International Journal of Wireless Networks and Broadband Technologies* (pp. 18-30).

www.irma-international.org/article/energy-efficient-clustering-using-modified-multi-hop-clustering/243659