



Chapter VIII

Discriminant DCT Feature Extraction

ABSTRACT

This chapter provides a feature extraction approach that combines the discrete cosine transform (DCT) with LDA. The DCT-based frequency-domain analysis technique is introduced first. Then, we describe the presented discriminant DCT approach and analyze its theoretical properties. Finally, we offer detailed experimental results and a chapter summary.

INTRODUCTION

Frequency-domain analysis is a commonly used image processing and recognition technique. During the past years, some work has been done to extract the frequency-domain features for image recognition. Li, Zhang, and Xu (2002) extract Fourier range and angle features to identify the palmprint image. Lai, Yuen, and Feng (2001) use holistic Fourier invariant features to recognize the facial image. Another spectral feature generated from SVD is used by some researchers (Chellappa, 1995). However, Tian, Tan, Wang and Fang (2003) indicate that this feature does not contain adequate information for face

recognition. In Hafed and Levine (2001), they extract DCT feature for face recognition. They point out that DCT obtains the near-optimal performance of K-L transform in facial information compression. And the performance of DCT is superior to those of discrete Fourier transform (FT) and other conventional transforms. By manually selecting the frequency bands of DCT, their recognition method achieves similar recognition effect as the eigenface method (Turk & Pentland, 1991) which is based on K-L transform. Nevertheless, their method cannot provide a rational band selection rule or strategy. And it cannot outperform the classical eigenface method.

To enhance the image classification information and improve the recognition effect, we propose a new image recognition approach in this section (Jing & Zhang, 2004), which combines DCT with the linear discrimination technique. It first uses a 2D separability judgment that can facilitate the selection of useful DCT frequency bands for image recognition, because not all the bands are useful in classification. It will then extract the linear discriminative features by an improved fisherface method and perform the classification by the nearest-neighbor classifier. We will perform the detailed analysis of the theoretical advantages of our approach. The rest of this section is organized as follows: First, we provide the description of our approach. Then, we show its theoretical analysis. Next, the experimental results on different image data and some conclusions are given.

APPROACH DEFINITION AND DESCRIPTION

In this section, we present a 2D separability judgment and introduce the whole recognition procedure of our approach.

Select DCT Frequency Bands by Using a 2D Separability Judgment

Suppose that image training and test sample sets are X_1 and X_2 , respectively; each gray image matrix is sized $M \times N$ and expressed by $f(x, y)$, where $1 \leq x \leq M$, $1 \leq y \leq N$ and $M \geq N$. Assume there are c known pattern classes (w_1, w_2, \dots, w_c) in X , where $P_i (i = 1, 2, \dots, c)$ denotes the a priori probability of class w_i . Perform a 2DDCT on each image (Hafed & Leveine, 2001) by:

$$F(u, v) = \frac{1}{\sqrt{MN}} \alpha(u) \alpha(v) \sum_{x=1}^M \sum_{y=1}^N f(x, y) \cos \left[\frac{(2x+1)u\pi}{2M} \right] \cos \left[\frac{(2y+1)v\pi}{2N} \right] \quad (8.1)$$

where $F(u, v)$ is sized $M \times N$, and $\alpha(\bullet)$ is defined as follows:

$$\alpha(w) = \begin{cases} \frac{1}{\sqrt{2}}, & w = 1 \\ 1, & \text{otherwise} \end{cases} \quad (8.2)$$

15 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/discriminant-dct-feature-extraction/5924

Related Content

Tracking Systems for Multiple Smart Home Residents

Aaron S. Crandall and Diane J. Cook (2013). *Human Behavior Recognition Technologies: Intelligent Applications for Monitoring and Security* (pp. 111-129). www.irma-international.org/chapter/tracking-systems-multiple-smart-home/75288

Improving System Reliability of Secondary Distribution Networks Through Smart Monitoring

Aderonke Oluseun Akinwumi (2022). *International Journal of Smart Security Technologies* (pp. 1-11). www.irma-international.org/article/improving-system-reliability-of-secondary-distribution-networks-through-smart-monitoring/309404

Information Processing for Generating Recommendations Ahead of Time in an IoT-Based Environment

Alexandros Bousdekis, Nikos Papageorgiou, Babis Magoutas, Dimitris Apostolou and Gregoris Mentzas (2017). *International Journal of Monitoring and Surveillance Technologies Research* (pp. 38-62). www.irma-international.org/article/information-processing-for-generating-recommendations-ahead-of-time-in-an-iot-based-environment/204944

From Streams of Observations to Knowledge-Level Productive Predictions

Mark Wernsdorfer and Ute Schmid (2013). *Human Behavior Recognition Technologies: Intelligent Applications for Monitoring and Security* (pp. 268-281). www.irma-international.org/chapter/streams-observations-knowledge-level-productive/75295

Probabilistic Methods for Face Registration and Recognition

Peng Li, Peng Li, Simon J. D. Prince and Simon J. D. Prince (2011). *Advances in Face Image Analysis: Techniques and Technologies* (pp. 178-197). www.irma-international.org/chapter/probabilistic-methods-face-registration-recognition/43827