



Chapter XVII

Design Wind Speeds using Fast Fourier Transform: A Case Study

Z. Ismail, N.H. Ramli and Z. Ibrahim,
Universiti Malaya, Malaysia

T.A. Majid and G. Sundaraj
Universiti Sains Malaysia, Malaysia

W.H.W. Badaruzzaman
Universiti Kebangsaan Malaysia, Malaysia

ABSTRACT

In this chapter, a study on the effects of transforming wind speed data, from a time series domain into a frequency domain via Fast Fourier Transform (FFT), is presented. The wind data is first transformed into a stationary pattern from a non-stationary pattern of time series data using statistical software. This set of time series is then transformed using FFT for the main purpose of the chapter. The analysis is done through MATLAB software, which provides a very useful function in FFT algorithm. Parameters of engineering significance such as hidden periodicities, frequency components, absolute magnitude and phase of the transformed data, power spectral density and cross spectral density can be obtained. Results obtained using data from case studies involving thirty-one weather stations in Malaysia show great potential for application in verifying the current criteria used for design practices.

INTRODUCTION

In the design of civil engineering structures, the effects of the natural environment on these structures have to be taken into consideration. Some examples of these are the effects of wind, current and waves on offshore structures; and the effects of wind and seismic activities on buildings. This chapter focuses mainly on the effects of wind on buildings. The parameter of interest in the design and construction of a structure is the design wind speed. This can be obtained from fundamental principles backed by verification through field studies of the dynamic characteristics of the structure. In many cases involving large structures, the input force cannot be created at will or be controlled. This shortcoming is overcome through ambient vibration testing and the use of Fast Fourier Transform (FFT) to convert the raw wind data into wind loads.

The chapter starts with a review of the general effects of wind on structures and the inhabitants. The parameters used in the design of structures including buildings are discussed. It is shown here that Fast Fourier Transform (FFT) which include Power Spectral Density (PSD), Cross Spectral Density (CSD) and Turbulence Intensities (TI) can be applied to derive the design parameters and subsequently, improve a wind code for structures. Examples of early studies on wind loads are given, and the limits of tolerance for civil engineering structures and the inhabitants therein are mentioned. It is noted that the criteria for design are more concerned with the human tolerance rather than the structural tolerance. In the design of structures, there is a need for a full understanding of the effects of wind at each stage of construction since the tolerance for the final structure could vary appreciably with the tolerance at each intermediate stage of the structure during construction. Vibration effects due to wind on structures are given, and examples of vibration effects on mechanical structures are also given as a comparison.

Methods of structural analysis and structural monitoring including vibration analysis and modal analysis are mentioned. Field tests including forced vibration methods as well as ambient vibration methods are described. Factors affecting the design of structures as well as the incentives to better understand the complex effects of wind on structures result in the approach to simplify these effects into components. These components can then be utilized in defining design wind speed and deriving design wind load, which can be used to develop the local design wind code for civil engineering structures such as buildings.

The analysis using FFT in this chapter can be taken one step further through frequency response function (FRF). FRF is the ratio of the output response to the input excitation force. This measurement is typically acquired using a dedicated instrument such as an FFT analyzer or a data acquisition system with software that performs the FFT. The input data in this case would be the measured wind speed using several anemometers, which can be converted into dynamic pressure

18 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/design-wind-speeds-using-fast/6844

Related Content

Safe-Platoon: A Formal Model for Safety Evaluation

Mohamed Garoui (2019). *International Journal of Software Science and Computational Intelligence* (pp. 26-37).

www.irma-international.org/article/safe-platoon/233521

EEG Analysis to Decode Tactile Sensory Perception Using Neural Techniques

Anuradha Saha and Amit Konar (2018). *Applied Computational Intelligence and Soft Computing in Engineering* (pp. 178-203).

www.irma-international.org/chapter/eeg-analysis-to-decode-tactile-sensory-perception-using-neural-techniques/189321

Analysis of Protein Structure for Drug Repurposing Using Computational Intelligence and ML Algorithm

Deepak Srivastava, Kwok Tai Chui, Varsha Arya, Francisco José García Peñalvo, Pramod Kumar and Anuj Kumar Singh (2022). *International Journal of Software Science and Computational Intelligence* (pp. 1-11).

www.irma-international.org/article/analysis-of-protein-structure-for-drug-repurposing-using-computational-intelligence-and-ml-algorithm/312562

Agent-Based Software Engineering, Paradigm Shift, or Research Program Evolution

Yves Wautelet, Christophe Schinckus and Manuel Kolp (2018). *Handbook of Research on Investigations in Artificial Life Research and Development* (pp. 284-296).

www.irma-international.org/chapter/agent-based-software-engineering-paradigm-shift-or-research-program-evolution/207208

Positive and Negative Innovations in Software Engineering

Capers Jones (2009). *International Journal of Software Science and Computational Intelligence* (pp. 20-30).

www.irma-international.org/article/positive-negative-innovations-software-engineering/2791