

Chapter 7

Chaos-Enhanced Firefly Algorithm with Automatic Parameter Tuning

Xin-She Yang
National Physical Lab, UK

ABSTRACT

Many metaheuristic algorithms are nature-inspired, and most are population-based. Particle swarm optimization is a good example as an efficient metaheuristic algorithm. Inspired by PSO, many new algorithms have been developed in recent years. For example, firefly algorithm was inspired by the flashing behaviour of fireflies. In this paper, the author extends the standard firefly algorithm further to introduce chaos-enhanced firefly algorithm with automatic parameter tuning, which results in two more variants of FA. The author first compares the performance of these algorithms, and then uses them to solve a benchmark design problem in engineering. Results obtained by other methods will be compared and analyzed.

1. INTRODUCTION

Search for optimality in many optimization applications is a challenging task, and search efficiency is one of the most important measures for an optimization algorithm. In addition, an efficient algorithm does not necessarily guarantee the global optimality is reachable. In fact, many optimization algorithms are only efficient in finding local optima. For example, classic hill-climbing or steepest descent method is very

efficient for local optimization. Global optimization typically involves objective functions which can be multimodal and highly nonlinear. Thus, it is often very challenging to find global optimality, especially for large-scale optimization problems. Recent studies suggest that metaheuristic algorithms such as particle swarm optimization are promising in solving these tough optimization problems (Kennedy & Eberhart, 1995; Kennedy et al., 2001; Shi & Eberhart, 1998; Eberhart & Shi, 2000; Yang, 2008).

DOI: 10.4018/978-1-4666-2479-5.ch007

Most metaheuristic algorithms are nature-inspired, from simulated annealing (Kirkpatrick et al., 1983) to firefly algorithm (Yang, 2008, 2010a), and from particle swarm optimization (Kennedy & Eberhart, 1995; Kennedy et al., 2001) to cuckoo search (Yang & Deb, 2010). These algorithms have been applied to almost all areas of optimization, design, scheduling and planning, data mining, machine intelligence, and many others (Gandomi et al., in press; Talbi, 2009; Yang, 2010a). On the other hand, chaotic tunneling is an important phenomenon in complex systems (Tomsovic, 1994; Podolskiy & Narmanov, 2003; Kohler et al., 1998; Delande & Zakrzewski, 2003; Shudo & Ikeda, 1998; Shudo et al., 2009). Traditional wisdom in optimization is to avoid numerical instability and chaos. Contemporary studies suggest that chaos can assist some algorithms such as genetic algorithms (Yang & Chen, 2002). For example, metaheuristic algorithms often use randomization techniques to increase the diversity of the solutions generated during search iterations (Talbi, 2009; Yang, 2010a). The most common randomization techniques are probably local random walks and Lévy flights (Gutowski, 2001; Pavlyukevich, 2007; Yang 2010b).

The key challenge for global optimization is that nonlinearity leads to multimodality, which in turns will cause problems to almost all optimization algorithms because the search process may be trapped in any local valley, and thus may cause tremendous difficulty to the search process towards global optimality. Even with most well-established stochastic search algorithms such as simulated annealing (Kirkpatrick et al., 1983), care must be taken to ensure it can escape the local modes/optimality. Premature convergence may occur in many algorithms including simulated annealing and genetic algorithms. The key ability of an efficient global search algorithm is to escape local optima, to visit all modes and to converge subsequently at the global optimality.

In this paper, we will first analyze the recently developed firefly algorithm (FA) (Yang, 2008,

2010b). Under the right conditions, FA can have chaotic behaviour, which can be used as an advantage to enhance the search efficiency, because chaos allow fireflies to sample search space more efficiently. In fact, a chaotic tunnelling feature can be observed in FA simulations when a firefly can tunnel through multimodes and jump from one mode to another modes. This enables the algorithm more versatile in escaping the local optima, and thus can guarantee to find the global optimality. Chaotic tunneling is an important phenomenon in complex systems, but this is the first time that a chaotic tunneling is observed in an optimization algorithm. Through analysis and numerical simulations, we will highlight that intrinsic chaotic characteristics in the FA can enhance the search efficiency. Then, we will introduce automatic parameter tuning to the chaotic firefly algorithm and compare its performance against a set of diverse test functions. Finally, we will apply the FA with automatic parameter tuning to solve a design benchmark whose solutions will be compared with other results in the literature.

2. FIREFLY ALGORITHM

Firefly Algorithm (FA) was developed by Yang (2008, 2010b), which was based on the flashing patterns and behaviours of fireflies. In essence, each firefly will be attracted to brighter ones, while at the same time, it explores and searches for prey randomly. In addition, the brightness of a firefly is determined by the landscape of the objective function.

The movement of a firefly i is attracted to another more attractive (brighter) firefly j is determined by

$$x_i^{t+1} = x_i^t + \beta e^{-\gamma r_{ij}^2} (x_j^t - x_i^t) + \alpha \varepsilon_i^t, \quad (1)$$

10 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/chaos-enhanced-firefly-algorithm-automatic/70644

Related Content

A Review of Recent Contribution in Agent-Based Health Care Modeling

Simerjit Gilland Raman Paranjape (2010). *Multi-Agent Systems for Healthcare Simulation and Modeling: Applications for System Improvement* (pp. 26-43).

www.irma-international.org/chapter/review-recent-contribution-agent-based/37009

A Multiagent Approach to Teaching Complex Systems Development

Simon C. Lynchand Keerthi Rajendran (2011). *Multi-Agent Systems for Education and Interactive Entertainment: Design, Use and Experience* (pp. 70-87).

www.irma-international.org/chapter/multiagent-approach-teaching-complex-systems/50395

Hybrid Model for Named Entity Recognition

Nikhil Chaturvediand Jigyasu Dubey (2022). *International Journal of Distributed Artificial Intelligence* (pp. 1-12).

www.irma-international.org/article/hybrid-model-for-named-entity-recognition/311063

An Agent-Based Model of the Spread of Devil Facial Tumor Disease in an Isolated Population of Tasmanian Devils

Charles E. Knadler (2012). *International Journal of Agent Technologies and Systems* (pp. 1-16).

www.irma-international.org/article/agent-based-model-spread-devil/75446

Multi-Agent Negotiation Paradigm for Agent Selection in B2C E-Commerce

Bireshwar Dass Mazumdar, Swati Basakand Neelam Modanwal (2011). *International Journal of Agent Technologies and Systems* (pp. 33-52).

www.irma-international.org/article/multi-agent-negotiation-paradigm-agent/55228