Chapter 4 The Kolmogorov Spline Network for Image Processing

Pierre-Emmanuel Leni University of Burgundy, France

Yohan D. Fougerolle University of Burgundy, France

Frédéric Truchetet University of Burgundy, France

ABSTRACT

In 1900, Hilbert stated that high order equations cannot be solved by sums and compositions of bivariate functions. In 1957, Kolmogorov proved this hypothesis wrong and presented his superposition theorem (KST) that allowed for writing every multivariate functions as sums and compositions of univariate functions. Sprecher has proposed in (Sprecher, 1996) and (Sprecher, 1997) an algorithm for exact univariate function reconstruction. Sprecher explicitly describes construction methods for univariate functions and introduces fundamental notions for the theorem comprehension (such as tilage). Köppen has presented applications of this algorithm to image processing in (Köppen, 2002) and (Köppen & Yoshida, 2005). The lack of flexibility of this scheme has been pointed out and another solution which approximates the univariate functions has been considered. More specifically, it has led us to consider Igelnik and Parikh's approach, known as the KSN which offers several perspectives of modification of the univariate functions as well as their construction. This chapter will focus on the presentation of Igelnik and Parikh's Kolmogorov Spline Network (KSN) for image processing and detail two applications: image compression and progressive transmission. Precisely, the developments presented in this chapter include: (1)Compression: the authors study the reconstruction quality using univariate functions containing only a fraction of the original image pixels. To improve the reconstruction quality, they apply this decomposition on images of details obtained by wavelet decomposition. The authors combine this approach into the JPEG 2000 encoder, and show that the obtained results improve JPEG 2000 compression scheme, even at low bitrates. (2)Progressive Transmission: the authors propose to modify the generation of the KSN. The image is decomposed into univariate functions that can be transmitted one after the other to add new data to the previously transmitted functions, which allows to progressively and exactly reconstruct the original image. They evaluate the transmission robustness and provide the results of the simulation of a transmission over packet-loss channels.

DOI: 10.4018/978-1-4666-3994-2.ch004

INTRODUCTION

The Superposition Theorem is the solution to one of the 23 mathematical problems conjectured by Hilbert in 1900. Hilbert suggested that solutions to high order equations were at least bivariate functions. This hypothesis was proven wrong by Kolmogorov in 1957 when he showed that continuous multivariate functions can be expressed as sums and compositions of univariate functions as

$$f\left(x_{1},\cdots,x_{n}\right) = \sum_{q=0}^{2n} \Phi_{q}\left(\sum_{p=1}^{n} \psi_{q,p}\left(x_{p}\right)\right). \tag{1}$$

Our goal is to investigate some aspects of this decomposition for images by considering a gray level discrete image as a sample of a continuous bivariate function. To achieve such decomposition, the univariate functions Φ_q and $\psi_{q,p}$ must be constructed. The functions Φ_q are called outer or external functions, and the functions $\psi_{q,p}$ are called inner or internal functions.

A construction method has been proposed in (Sprecher, 1996) and (Sprecher, 1997). Sprecher provides an explicit and exact computation algorithm for the values of the univariate functions at a user defined precision. The Kolmogorov superposition theorem, as reformulated and simplified by Sprecher, can be written as

$$f\left(x_{1},\cdots,x_{n}\right) = \sum_{q=0}^{2n} g_{q}\left(\sum_{i=1}^{n} \lambda_{i}\psi\left(x_{i}+bq\right)\right).$$
(2)

We have implemented Sprecher's algorithm, using the improvements proposed in (Braun and Griebel, 2007) to guarantee the monotonicity of the internal function ψ , and tested it on image decomposition in (Leni *et al.*, 2008). In this algorithm, the univariate functions can be exactly computed for any coordinates of the definition space of the multivariate function at a given precision, but no analytic expression exists. One of the main drawbacks of this approach is that the univariate function definitions cannot be modified without completely modifying the overall pipeline of this method. This issue has led us to consider Igelnik and Parikh's approach, known as Kolmogorov Spline Network (KSN), that approximates the univariate functions as well as offers a greater flexibility on several parameters of the algorithm (*i.e.*, univariate function constructions, number of layers, tile size, and so on).

We present in detail the original KSN introduced by Igelnik and Parikh, then we propose some modifications for two compression and progressive transmission.

In the KSN, a multivariate function f is approximated by

$$f(x) = f(x_1, \cdots, x_n)$$

$$\approx \sum_{q=1}^{N} a_q g_q \left(\sum_{i=1}^{n} \lambda_i \psi_{q,i}(x_i) \right) = \sum_{q=1}^{N} a_q g_q \left(\xi_q(x) \right).$$
(3)

The functions $\xi_q(x)$ play the role of hash functions, as illustrated in Figure 1, are mapping functions from $[0,1]^d$ to \mathbb{R} , and are used to evaluate the argument of the external functions $g_q(\bullet)$.

In this formulation, the number of layers is now variable, and the function ψ is no longer unique: a function $\psi_{a,i}$ is associated for each layer q along each dimension i. The algorithm for the construction of a KSN is divided into two parts: a construction step, in which the univariate functions are interpolated by cubic splines, and a second stage, in which the spline parameters and the weights of the layers a_{μ} are optimized to ensure the convergence of the approximation to the function f. A comparison between KSN and Sprecher's algorithm can be found in (Leni et al., 2008). To construct the functions g_a and $\psi_{a,i}$ a tilage over the definition space of the multivariate function to be approximated is constructed. By construction, the tiles are disjoint; therefore, in order to cover the entire space, several tilage layers are 23 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/kolmogorov-spline-network-image-

processing/77538

Related Content

Content Analysis from User's Relevance Feedback for Content-Based Image Retrieval

Chia-Hung Weiand Chang-Tsun Li (2009). Artificial Intelligence for Maximizing Content Based Image Retrieval (pp. 216-234).

www.irma-international.org/chapter/content-analysis-user-relevance-feedback/4158

Multi-Lingual Scene Text Detection Using One-Class Classifier

Anirban Mukhopadhyay, Sourav Kumar, Souvik Roy Chowdhury, Neelotpal Chakraborty, Ayatullah Faruk Mollah, Subhadip Basuand Ram Sarkar (2019). *International Journal of Computer Vision and Image Processing (pp. 48-65).*

www.irma-international.org/article/multi-lingual-scene-text-detection-using-one-class-classifier/226244

A Context Based Tracking for Similar and Deformable Objects

Bhavana Kaushik, Manoj Kumar, Charul Bhatanagarand Anand Singh Jalal (2018). *International Journal of Computer Vision and Image Processing (pp. 1-15).* www.irma-international.org/article/a-context-based-tracking-for-similar-and-deformable-objects/214070

Anomalous Event Detection Methodologies for Surveillance Application: An Insight

T. J. Narendra Rao, G N. Girish, Mohit P. Tahilianiand Jeny Rajan (2018). *Handbook of Research on Advanced Concepts in Real-Time Image and Video Processing (pp. 1-27).* www.irma-international.org/chapter/anomalous-event-detection-methodologies-for-surveillance-application/186271

A Multimodal Approach to Enhancing Automobile Security

Samuel Dayo Okegbile, Segun Aina, Sanmi Akinmodun, Adeniran Ishola Oluwarantiand Aderonke Rasheedat Lawal (2019). *International Journal of Computer Vision and Image Processing (pp. 32-47).* www.irma-international.org/article/a-multimodal-approach-to-enhancing-automobile-security/226243