

Chapter 65

Recent Advances on Graph-Based Image Segmentation Techniques

Chao Zeng

University of Technology-Sydney, Australia

Xiangjian He

University of Technology-Sydney, Australia

Wenjing Jia

University of Technology-Sydney, Australia

Min Xu

University of Technology-Sydney, Australia

ABSTRACT

Image segmentation techniques using graph theory has become a thriving research area in computer vision community in recent years. This chapter mainly focuses on the most up-to-date research achievements in graph-based image segmentation published in top journals and conferences in computer vision community. The representative graph-based image segmentation methods included in this chapter are classified into six categories: minimum-cut/maximum-flow model (called graph-cut in some literatures), random walk model, minimum spanning tree model, normalized cut model and isoperimetric graph partitioning. The basic rationales of these models are presented, and the image segmentation methods based on these graph-based models are discussed as the main concern of this chapter. Several performance evaluation methods for image segmentation are given. Some public databases for testing image segmentation algorithms are introduced and the future work on graph-based image segmentation is discussed at the end of this chapter.

INTRODUCTION

In computer vision applications, image segmentation is to separate an image into several regions, of which each has certain properties in terms of predefined rules. These regions can represent objects, parts of an object, or background. The

aim of image segmentation is to find the regions of interest (ROI) in an image according to a particular application.

As a very important technique in computer vision, image segmentation has been found in a wide variety of practical applications, such as medical image processing, satellite image analysis, biometric recognition (e.g. human face recognition, fingerprint recognition and palm recognition),

DOI: 10.4018/978-1-4666-3994-2.ch065

traffic control systems (e.g. vehicle number plate recognition, vehicle counting), digital photo editing, robotic vision and so on. Image segmentation approaches include clustering methods (Mignotte, 2008), compression-based methods (Rao, 2009), histogram-based methods (Otsu, 1979), edge detection methods (Senthilkumaran, 2009), region growing methods (Fan, 2005), partial differential equation-based methods (Zhang, 2010), graph-based methods (Boykov, 2001), watershed transformation methods (Grau, 2004) and so on. Among these image segmentation methods, the graph-based approach has attracted many attentions and become one of the most thriving research areas in computer vision in recent years. Meanwhile, many high quality papers on graph-based image segmentation techniques have been published in top journals and conferences in the field of image processing and computer vision. Therefore, this chapter is to gather the information on the most up-to-date graph-based image segmentation research together and give a clear overview of research work on this topic.

The remaining parts of this chapter are arranged as follows. Firstly, the background mathematical

knowledge of graph theory is given. We then present the five most representative graph-based models used for image segmentation and classify them into two major groups based on whether interactions of users are involved. The summary of the reviewed methods are illustrated in Table 1. Then, methods used for evaluating segmentation performance are discussed. Some benchmark image segmentation datasets are introduced. Conclusions are given in the end.

BACKGROUND

Mathematically, a graph $G=(V,E)$ is composed of a set of nodes (or vertices) $v \in V$ and a set of edges $e \in E \subseteq V \times V$ connecting two nodes $v_i \in V$ and $v_j \in V$. There are two types of edges: undirected edge and directed edge. An undirected edge is an unordered pair of nodes $e_{\{v_i, v_j\}}$. A directed edge is an ordered pair of nodes $e_{(v_i, v_j)}$, in which v_i is called the starting node and v_j is called the ending node. The weight of an edge is a value assigned

Table 1. Summary of the five reviewed graph-based image segmentation methods

	Min-Cut/Max-Flow	Random Walker	MST-Based	Normalized Cut	Isoperimetric Graph Partitioning
Applications	Psychological vision, Photo/video editing and medical image segmentation	Medical image segmentation and object/background segmentation	Object segmentation and image segmentation	Natural scene image segmentation	Natural scene image segmentation, medical image and psychological vision
Testing Dataset	Gestalt example, medical image and video sequence	2D/3D medical image and Berkeley dataset	Natural scene image, Columbia COIL image database	Natural scene image, weather radar image	Gestalt example, natural scene image
Performance	Less than a second for most 2D images (up to 512*512)	Around 3 seconds on a 256*256 image for an Intel Xeon 2.40GHz with 3GB RAM	None	2 mins on Intel Pentium 200MHz machines for 100*120 test image	0.5863 seconds are required on a 1.4GHz AMD Athlon with 512k RAM
Time Complexity	$O(mn^2)$ in worst case, n is the number of nodes and m is the number of edges	$O(n)$, n is the number of nodes in the graph	$O(m \log m)$ for m graph edges	$O(mn)$, n is the number of pixels and m is the number of steps for convergence	$O(m+n \log n)$, n is the number of nodes and m is the number of edges

13 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:
www.igi-global.com/chapter/recent-advances-graph-based-image/77599

Related Content

Some Fuzzy Tools for Evaluation of Computer Vision Algorithms

Andrey Osipov (2018). *International Journal of Computer Vision and Image Processing* (pp. 1-14).
www.irma-international.org/article/some-fuzzy-tools-for-evaluation-of-computer-vision-algorithms/201460

Fuzzy Shape of Objects in Images with Similarity Measure for Image Retrieval Applications

P. Sumathy, P. Shanmugavadivu and A. Vadivel (2015). *International Journal of Computer Vision and Image Processing* (pp. 58-80).
www.irma-international.org/article/fuzzy-shape-of-objects-in-images-with-similarity-measure-for-image-retrieval-applications/159807

Thermal Human Face Recognition for Biometric Security System

Ayan Seal, Debotosh Bhattacharjee, Mita Nasipuri and Dipak Kumar Basu (2018). *Computer Vision: Concepts, Methodologies, Tools, and Applications* (pp. 1838-1863).
www.irma-international.org/chapter/thermal-human-face-recognition-for-biometric-security-system/197028

A Novel Approach for Edge Detection in Images Based on Cellular Learning Automata

Farhad Soleimanian Gharehchopogh and Samira Ebrahimi (2012). *International Journal of Computer Vision and Image Processing* (pp. 51-61).
www.irma-international.org/article/novel-approach-edge-detection-images/75770

Enhancing Robustness in Speech Recognition using Visual Information

Omar Farooq and Sekharjit Datta (2012). *Speech, Image, and Language Processing for Human Computer Interaction: Multi-Modal Advancements* (pp. 149-171).
www.irma-international.org/chapter/enhancing-robustness-speech-recognition-using/65058