Chapter 65 Recent Advances on Graph-Based Image Segmentation Techniques

Chao Zeng University of Technology-Sydney, Australia Xiangjian He University of Technology-Sydney, Australia

Wenjing Jia University of Technology-Sydney, Australia Min Xu University of Technology-Sydney, Australia

ABSTRACT

Image segmentation techniques using graph theory has become a thriving research area in computer vision community in recent years. This chapter mainly focuses on the most up-to-date research achievements in graph-based image segmentation published in top journals and conferences in computer vision community. The representative graph-based image segmentation methods included in this chapter are classified into six categories: minimum-cut/maximum-flow model (called graph-cut in some literatures), random walk model, minimum spanning tree model, normalized cut model and isoperimetric graph partitioning. The basic rationales of these models are presented, and the image segmentation methods based on these graph-based models are discussed as the main concern of this chapter. Several performance evaluation methods for image segmentation are given. Some public databases for testing image segmentation algorithms are introduced and the future work on graph-based image segmentation is discussed at the end of this chapter.

INTRODUCTION

In computer vision applications, image segmentation is to separate an image into several regions, of which each has certain properties in terms of predefined rules. These regions can represent objects, parts of an object, or background. The

DOI: 10.4018/978-1-4666-3994-2.ch065

aim of image segmentation is to find the regions of interest (ROI) in an image according to a particular application.

As a very important technique in computer vision, image segmentation has been found in a wide variety of practical applications, such as medical image processing, satellite image analysis, biometric recognition (e.g. human face recognition, fingerprint recognition and palm recognition), traffic control systems (e.g. vehicle number plate recognition, vehicle counting), digital photo editing, robotic vision and so on. Image segmentation approaches include clustering methods (Mignotte, 2008), compression-based methods (Rao, 2009), histogram-based methods (Otsu, 1979), edge detection methods (Senthilkumaran, 2009), region growing methods (Fan, 2005), partial differential equation-based methods (Zhang, 2010), graph-based methods (Boykov, 2001), watershed transformation methods (Grau, 2004) and so on. Among these image segmentation methods, the graph-based approach has attracted many attentions and become one of the most thriving research areas in computer vision in recent years. Meanwhile, many high quality papers on graphbased image segmentation techniques have been published in top journals and conferences in the field of image processing and computer vision. Therefore, this chapter is to gather the information on the most up-to-date graph-based image segmentation research together and give a clear overview of research work on this topic.

The remaining parts of this chapter are arranged as follows. Firstly, the background mathematical

knowledge of graph theory is given. We then present the five most representative graph-based models used for image segmentation and classify them into two major groups based on whether interactions of users are involved. The summary of the reviewed methods are illustrated in Table 1. Then, methods used for evaluating segmentation performance are discussed. Some benchmark image segmentation datasets are introduced. Conclusions are given in the end.

BACKGROUND

Mathematically, a graph G=(V,E) is composed of a set of nodes (or vertices) $v \in V$ and a set of edges $e \in E \subseteq V \times V$ connecting two nodes $v_i \in V$ and $v_j \in V$. There are two types of edges: undirected edge and directed edge. An undirected edge is an unordered pair of nodes $e_{\{v_i, v_j\}}$. A directed edge is an ordered pair of nodes $e_{\{v_i, v_j\}}$, in which v_i is called the starting node and v_j is called the ending node. The weight of an edge is a value assigned

	Min-Cut/Max-Flow	Random Walker	MST-Based	Normalized Cut	Isoperimetric Graph Partitioning
Applications	Psychological vision, Pho- to/video editing and medi- cal image segmentation	Medical image segmentation and object/background segmentation	Object segmen- tation and image segmentation	Natural scene image segmentation	Natural scene image seg- mentation, medical image and psychological vision
Testing Dataset	Gestalt example, medical image and video sequence	2D/3D medical image and Berkeley dataset	Natural scene image, Colum- bia COIL im- age database	Natural scene image, weather radar image	Gestalt example, natural scene image
Performance	Less than a second for most 2D images (up to 512*512)	Around 3 seconds on a 256*256 image for an Intel Xeon 2.40GHz with 3GB RAM	None	2 mins on Intel Pentium 200MHz machines for 100*120 test image	0.5863 seconds are re- quired on a 1.4GHz AMD Athlon with 512k RAM
Time Complexity	$O(mn^2)$ in worst case, <i>n</i> is the number of nodes and <i>m</i> is the number of edges	O(n), <i>n</i> is the number of nodes in the graph	<i>O</i> (<i>m</i> log <i>m</i>) for <i>m</i> graph edges	O(mn), <i>n</i> is the number of pixels and <i>m</i> is the number of steps for convergence	$O(m+n\log n)$, <i>n</i> is the number of nodes and <i>m</i> is the number of edges

Table 1. Summary of the five reviewed graph-based image segmentation methods

13 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/recent-advances-graph-based-image/77599

Related Content

An Evaluation Framework and a Benchmark for Multi/Hyperspectral Image Compression

Jonathan Delcourt, Alamin Mansouri, Tadeusz Sliwaand Yvon Voisin (2013). *Intelligent Computer Vision and Image Processing: Innovation, Application, and Design (pp. 56-70).* www.irma-international.org/chapter/evaluation-framework-benchmark-multi-hyperspectral/77032

Brain Tumor Detection Using Multipath Convolution Neural Network (CNN)

Mukesh Kumar Chandrakarand Anup Mishra (2020). International Journal of Computer Vision and Image Processing (pp. 43-53).

www.irma-international.org/article/brain-tumor-detection-using-multipath-convolution-neural-network-cnn/264220

Recent Advances on Graph-Based Image Segmentation Techniques

Chao Zeng, Wenjing Jia, Xiangjian Heand Min Xu (2013). *Graph-Based Methods in Computer Vision:* Developments and Applications (pp. 140-154). www.irma-international.org/chapter/recent-advances-graph-based-image/69074

Feature Selection of Interval Valued Data Through Interval K-Means Clustering

D. S. Guru, N. Vinay Kumarand Mahamad Suhil (2017). *International Journal of Computer Vision and Image Processing (pp. 64-80).*

www.irma-international.org/article/feature-selection-of-interval-valued-data-through-interval-k-means-clustering/183661

Detection and Classification of Diabetic Retinopathy Using Image Processing Algorithms, Convolutional Neural Network, and Signal Processing Techniques

Sudha S., Srinivasan A., T. Gayathri Deviand Mardeni Bin Roslee (2023). Handbook of Research on Computer Vision and Image Processing in the Deep Learning Era (pp. 270-280).

www.irma-international.org/chapter/detection-and-classification-of-diabetic-retinopathy-using-image-processing-

algorithms-convolutional-neural-network-and-signal-processing-techniques/314002