Chapter 23 Distributed Task Allocation in Swarms of Robots

Aleksandar Jevtić Robosoft, France

Diego Andina E.T.S.I.T.-Universidad Politécnica de Madrid, Ciudad Universitaria, Spain

> **Mo Jamshidi** University of Texas, USA

ABSTRACT

This chapter introduces a swarm intelligence-inspired approach for target allocation in large teams of autonomous robots. For this purpose, the Distributed Bees Algorithm (DBA) was proposed and developed by the authors. The algorithm allows decentralized decision-making by the robots based on the locally available information, which is an inherent feature of animal swarms in nature. The algorithm's performance was validated on physical robots. Moreover, a swarm simulator was developed to test the scalability of larger swarms in terms of number of robots and number of targets in the robot arena. Finally, improved target allocation in terms of deployment cost efficiency, measured as the average distance traveled by the robots, was achieved through optimization of the DBA's control parameters by means of a genetic algorithm.

INTRODUCTION

The initial purpose of swarm intelligence algorithms was to solve optimization problems. However, in recent years, these algorithms have shown their full potential in terms of flexibility and autonomy when it comes to design and control of complex systems that consist of a large number of autonomous agents. In more general

DOI: 10.4018/978-1-4666-4607-0.ch023

terms, these can be referred to as systems of autonomous systems (Jamshidi, 2009). What distinguishes swarm intelligence algorithms in the broad field of soft-computing is that they exploit the decentralizing property of natural swarms in order to create autonomous, scalable, and adaptive multi-agent systems.

Swarm robotics emerged as a straight-forward application domain for swarm intelligence due to resemblance of large robot teams to animal swarms (Dorigo & Sahin, 2004; Trianni, Nolfi & Dorigo, 2008; Correll, Cui, Gao & Gross, 2010). In nature, swarming behavior has been studied in ant and bee colonies, bird flocks and fish schools, among others (Engelbrecht, 2005). However, the biological plausibility of swarm intelligence algorithms, and swarm-based systems in general, is not a must; in computer science and engineering researchers are guided by efficiency, flexibility, robustness and cost as main criteria.

In applications that require area coverage, swarms of mobile robots can use their ability to quickly deploy within a large area. Some of the possible applications include planetary exploration, urban search and rescue, communication networks, monitoring, surveillance, cleaning, maintenance, and so forth. In order to efficiently perform their tasks, robots require high level of autonomy and cooperation. They use their sensing abilities to explore an unknown environment and deploy on the sites of interest, i.e. targets. However, the coordination of a robot swarm is not an easy problem, especially when the resources for the deployment task are limited. Such a large group of robots, if organized in a centralized manner, could experience information overflow that can lead to the overall system failure (Gazi, Jevtić, Andina & Jamshidi, 2010). For this reason, the communication between the robots can be realized through local interactions, either directly with one another or indirectly via environment (Beni & Wang, 1989).

As a result of the growing interest in the coordination of swarms of robots, multi-robot task allocation (MRTA) has become an important research topic (Dudek, Jenkin & Milios, 2002; Gerkey & Matarić, 2004). The goal is to assign tasks to robots in a way that, through cooperation, the global objective is achieved more efficiently. In the scenario proposed in this work, tasks are represented by targets defined with their qualities and their location in the robot arena. For distributed task allocation the Distributed Bees Algorithm (DBA) was proposed (Jevtić, Gazi, Andina & Jamshidi, 2010), which was inspired by the foraging behavior of colonies of bees in nature. In the context of mobile multi-robot systems, scalability refers to the overall system's performance if the number of robots increases in relation to the number of tasks at hand (Rana & Stout, 2000). The resulting effect on the system's performance can be determined in terms of metrics associated with a particular platform or an operating environment, which in this work refers to dispatching a robot to a remote site marked as a target.

The objectives of this chapter are manifold. The following section describes the problem of MRTA and provides a summary of the related work. The Distributed Bees Algorithm (DBA) is then proposed as a solution to distributed MRTA. The DBA's performance is subsequently validated through experiments with physical robots. Moreover, simulator was developed to test the DBA's scalability in terms of number of robots and number of targets. The last experiments present analysis of DBA's performance through optimization of its control parameters. Finally, this chapter provides perspectives on future research directions and gives concluding remarks.

BACKGROUND

Multirobot systems offer the possibility of enhanced task performance, increased task reliability and decreased cost over more traditional singlerobot systems. Various architectures for multirobot systems that differ in size and complexity have been proposed. Dudek et al. (2002) provided a taxonomy that categorizes the existing multirobot systems along various axes, including size (number of robots), team organization (e.g., centralized vs. distributed), communication topology (e.g., broadcast vs. unicast), and team composition (e.g., homogeneous vs. heterogeneous).

Rather than characterizing architectures, Gerkey and Matarić (2004) categorized instead the underlying coordination problems with a focus on MRTA. The authors distinguish: single-task (ST) 22 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/distributed-task-allocation-in-swarms-ofrobots/84908

Related Content

A Neuromorphic Robot Vision System to Predict the Response of Visual Neurons

Kazuhiro Shimonomura (2014). *Robotics: Concepts, Methodologies, Tools, and Applications (pp. 812-818).*

www.irma-international.org/chapter/a-neuromorphic-robot-vision-system-to-predict-the-response-of-visualneurons/84925

Emotional State Recognition Using Facial Expression, Voice, and Physiological Signal

Tahirou Djara, Abdoul Matine Ousmaneand Antoine Vianou (2018). *International Journal of Robotics Applications and Technologies (pp. 1-20).*

www.irma-international.org/article/emotional-state-recognition-using-facial-expression-voice-and-physiologicalsignal/209440

The Emotions of Alan Turing: The Boy Who Explained Einstein's Theory of Relativity Aged 15¹/₂ for his Mother

Huma Shah (2014). *International Journal of Synthetic Emotions (pp. 23-30).* www.irma-international.org/article/the-emotions-of-alan-turing/113417

Modelling Hardwired Synthetic Emotions: TPR 2.0

Jordi Vallverdúand David Casacuberta (2009). Handbook of Research on Synthetic Emotions and Sociable Robotics: New Applications in Affective Computing and Artificial Intelligence (pp. 460-471). www.irma-international.org/chapter/modelling-hardwired-synthetic-emotions/21521

Kinematic Isotropic Configuration of Spatial Cable-Driven Parallel Robots

Hamoon Hadianand Abbas Fattah (2013). Advanced Engineering and Computational Methodologies for Intelligent Mechatronics and Robotics (pp. 266-290).

www.irma-international.org/chapter/kinematic-isotropic-configuration-spatial-cable/76453